



PHANTEKS Glacier G40 Asus GPU Block Graphic Card Installation Guide













[Home](#) » [PHANTEKS](#) » PHANTEKS Glacier G40 Asus GPU Block Graphic Card Installation Guide 

*PHANTEKS Glacier G40 Asus GPU Block Graphic
Card Installation Guide*

GLACIER G40 ASUS GPU BLOCK

INSTALLATION GUIDE V1.1

PH-GB4090AS_BK01/CR01/MW01_BP

PACKAGE CONTENTS					
	GB4090AS block QTY: 1		Block thermal pads QTY: 2 pre-cut pieces		GB4090AS backplate QTY: 1
	GLACIER stop fitting QTY: 2		M3x10 screws QTY: 1		Backplate thermal pads QTY: 2 pre-cut pieces
	Support bracket QTY: 1		M2.5x5 screws/washers QTY: 4/4		8x M2.5x8 flush screws 2x M2.5x6 flush screws
	Thermal compound QTY: 1		Phanteks D-RGB cable QTY: 1		Motherboard cable QTY: 1


⚠ WARNING – This product is intended for advanced users. Improper installation may result in damage to your equipment. While all efforts have been made to provide the most comprehensive information possible, Phantoms assumes no liability expressed or implied for any damage(s) occurring to your components as a result of using Phantoms cooling products, either due to mistake or omission on our part in the below instructions, or due to failure or defect in the Phantoms cooling products. Do not disassemble the water block. Warranty will be voided.

Contents

- 1 STEP 1. REMOVING STOCK COOLER
- 2 STEP 2. APPL YING THERMAL PASTE & PADS
- 3 STEP 3. MOUNT THE WATER BLOCK
- 4 STEP 4. APPL YING THERMAL PADS
- 5 STEP 5. INSTALL THE BACKPLATE
- 6 STEP 6. INSTALL INTO THE SYSTEM
- 7 Documents / Resources
- 8 Related Posts

STEP 1. REMOVING STOCK COOLER

Unscrew all highlighted screws to remove the stock cooler and backplate.



Make sure to unplug the LED and Fan cables when you remove the stock cooler.

ASUS ROG STRIX RTX 4090



ASUS TUF GAMING RTX 4090



Keep for step 3

STEP 2. APPL YING THERMAL PASTE & PADS


Clean off the original thermal compound. We recommend using isopropanol alcohol.

Remove the protective film and place the the thermal pads on the correct position on the PCB.

Apply the Phanteks Thermal Compound to the center of the GPU chip.

⚠ Make sure to remove the protective film on both sides of the thermal pads.

ASUS ROG STRIX / TUF RTX 4090



STEP 3. MOUNT THE WATER BLOCK




Secure the support bracket to the GPU block first.

Carefully position the water block onto the graphics card. Align the mounting holes on the PCB with the holes on the water block.

Secure the water block with 4 M2.Sx5mm screws and washers to the PCB.



Secure the Support Bracket with the original cooler screw.

Make sure to lay the GPU with the water block flat down without resting on the PC/bracket.



STEP 4. APPL YING THERMAL PADS


Remove the protective film on both sides and place the thermal pads on the correct position on the backplate.



STEP 5. INSTALL THE BACKPLATE

Carefully position the backplate onto the graphics card. Align the mounting holes on the PCB with the holes on the backplate.

Secure the backplate with 8x M2.Sx8mm and 2x M2.Sx6mm flush screws to the PCB.




STEP 6. INSTALL INTO THE SYSTEM

Connect the D-RGB cable to the D-RGB strip in the water block.

All Phanteks O-RGB products can be daisy-chained together.


2. Install the GPU into the system.
3. Install the water loop and Stop Fittings

⚠ Always perform a leak test before providing power to any system components.



PHANTEKS

Documents / Resources



[PHANTEKS Glacier G40 Asus GPU Block Graphic Card](#) [pdf] Installation Guide
PH-GB4090AS BP, Glacier G40 Asus GPU Block, Graphic Card, Glacier G40 Asus GPU Block
Graphic Card