



PHILIPS S Line 273S1 LCD Monitor With USB-C User Manual

May 11,
2025

Contents [[hide](#)]

- [1 S Line 273S1 LCD Monitor With USB-C](#)
- [2 Specifications](#)
- [3 Product Usage Instructions](#)
 - [3.1 2. Setting up the monitor](#)
 - [3.2 3. Image Optimization](#)
 - [3.3 4. Daisy-chain function](#)
 - [3.4 5. Designs to prevent computer vision syndrome \(CVS\)](#)
- [4 Frequently Asked Questions \(FAQ\)](#)
 - [4.1 Q: What should I do in case of severe burn-in or ghost image on the screen?](#)
 - [4.2 Documents / Resources](#)
 - [4.2.1 References](#)

S Line 273S1 LCD Monitor With USB-C

“

Specifications

- Model: S Line 273S1
- Website: www.philips.com/welcome

- User Manual Language: English
-

Product Usage Instructions

2. Setting up the monitor

Before using the monitor, follow these steps to set it up properly:

1. **Installation:** Unpack the monitor and connect it to the power source.
2. **Operating the monitor:** Power on the monitor and adjust settings as needed.
3. **Remove the Base Assembly for VESA Mounting:** If you plan to mount the monitor using a VESA mount, follow the instructions to remove the base assembly.

3. Image Optimization

Optimize your viewing experience with the following features:

- **SmartImage:** Use this feature to enhance image quality based on your content.
- **SmartContrast:** Adjust contrast settings for better visual clarity.

4. Daisy-chain function

If your monitor supports daisy-chaining, you can connect multiple monitors in a series for extended display capabilities.

5. Designs to prevent computer vision syndrome

(CVS)

This monitor is designed with features to reduce eye strain and prevent CVS. Adjust settings for optimal viewing comfort.

Frequently Asked Questions (FAQ)

Q: What should I do in case of severe burn-in or ghost image on the screen?

A: If you experience severe burn-in or ghost imaging symptoms, immediately activate a screen saver or a periodic screen refresh application to prevent further damage. Contact a service technician if the issue persists.

“

[View Fullscreen](#)



S Line

273S1

www.philips.com/welcome

EN User manual

1

Customer care and warranty 21

Troubleshooting & FAQs

Table of Contents

1. Important	1	1.1 Safety precautions and maintenance	1	1.2 Notational Descriptions	3	1.3 Disposal of product and packing material	4
2. Setting up the monitor	5	2.1 Installation	5	2.2 Operating the monitor	8	2.3 Remove the Base Assembly for VESA Mounting	11
3. Image Optimization	12	3.1 SmartImage	12	3.2 SmartContrast	13		
4. Daisy-chain function	14						
5. Designs to prevent computer vision syndrome (CVS)	15						
6. Technical Specifications	16	6.1 Resolution & Preset Modes	19				
7. Power Management	20						
8. Customer care and warranty ...	21	8.1 Philips' Flat Panel Monitors Pixel Defect Policy	21	8.2 Customer Care & Warranty	24		
9. Troubleshooting & FAQs	25	9.1 Troubleshooting	25	9.2 General FAQs	26		

1. Important

1. Important

This electronic user's guide is intended for anyone who uses the Philips monitor. Take time to read this user manual before you use your monitor. It contains important information and notes regarding operating your monitor.

The Philips guarantee applies provided the product is handled properly for its intended use, in accordance with its operating instructions and upon presentation of the original invoice or cash receipt, indicating the date of purchase, dealer's name and model and production number of the product.

1.1 Safety precautions and maintenance

Warnings Use of controls, adjustments or procedures other than those specified in this documentation may result in exposure to shock, electrical hazards and/or mechanical hazards.

Read and follow these instructions when connecting and using your computer monitor.

Operation

- Please Keep the monitor out of direct sunlight, very strong bright lights and away from any other heat source. Lengthy exposure to this type of environment may result in discoloration and damage to the monitor.
- Keep the display away from oil. Oil may damage the plastic cover of the display and void the warranty.
- Remove any object that could fall into ventilation holes or prevent proper cooling of the monitor's electronics.
- Do not block the ventilation holes on the cabinet.
- When positioning the monitor, make sure the power plug and outlet are easily accessible.
- If turning off the monitor by detaching the power cable or DC power cord, wait for 6 seconds before attaching the power cable or DC power cord for normal operation.
- Please use approved power cord provided by Philips all the time. If your power cord is missing, please contact with your local service center. (Please refer to Service contact information listed in Important Information Manual.)
- Operate under the specified power supply. Be sure to operate the monitor only with the specified power supply. Use of an incorrect voltage will cause malfunction and may cause fire or electric shock.
- Protect the cable. Do not pull or bend the power cable and signal cable. Do not place the monitor or any other heavy objects on the cables, if damaged, the cables may cause fire or electric shock.
- Do not subject the monitor to severe vibration or high impact conditions during operation.
- To avoid potential damage, for example the panel peeling from the bezel, ensure that the monitor does not tilt downward by more than -5 degrees. If the -5 degree downward tilt angle maximum is exceeded, the monitor damage will not be covered under warranty.
- Do not knock or drop the monitor during operation or transportation.
- The USB Type-C port could only be connected to specify equipment

with fire enclosure in compliance with IEC 62368-1 or IEC 60950-1.

- Excessive usage of monitor can cause eye discomfort, it's better to take shorter breaks more often at your workstation than longer breaks and less often; for example a 5-10 minute break after 50-60-minute continuous screen use is likely to be better than a 15-minute break every two hours. Try to keep your eyes from eye strain while using the screen for a constant period of time by :

- Looking at something varying distances after a long period focusing on the screen.
- Conscious Blinking often while you work.
- Gently closing and rolling your eyes to relax.
- Reposition your screen to appropriate height and angle according to your height.
- Adjusting the brightness and contrast to appropriate level.
- Adjusting the environment lighting similar to that of your screen brightness, avoid the fluorescent lighting, and surfaces that don't reflect too much light.
- Seeing a doctor if your symptoms.

Maintenance

- To protect your monitor from possible damage, do not put excessive pressure on the LCD panel. When moving your monitor, grasp the frame to lift; do not lift the monitor by placing your hand or fingers on the LCD panel.
- Oil-based cleaning solutions may damage the plastic parts and void the warranty.
- Unplug the monitor if you are not going to use it for an extensive period of time.
- Unplug the monitor if you need to clean it with a slightly damp cloth. The screen may be wiped with a dry cloth when the power is off. However, never use organic solvent, such as, alcohol, or ammonia-based liquids to clean your monitor.
- To avoid the risk of shock or permanent damage to the set, do not expose the monitor to dust, rain, water, or excessive moisture environment.
- If your monitor gets wet, wipe it with dry cloth as soon as possible.
- If foreign substance or water gets in your monitor, please turn the power off immediately and disconnect the power cord. Then, remove the foreign substance or water, and send it to the maintenance center.
- Do not store or use the monitor in locations exposed to heat, direct sunlight or extreme cold.
- In order to maintain the best performance of your monitor and use it for a longer lifetime, please use the monitor in a location that falls within the following temperature

and humidity ranges.

- Temperature: 0-40°C 32-104°F
- Humidity: 20-80% RH

Important information for Burn-in/ Ghost image

- Always activate a moving screen saver program when you leave your monitor unattended. Always activate a periodic screen refresh application if your monitor will display unchanging static content. Uninterrupted display of still or static images over an extended period may cause “burn-in”, also

2

1. Important

known as “after-imaging” or “ghost imaging”, on your screen.

- “Burn-in”, “after-imaging”, or “ghost imaging” is a well-known phenomenon in LCD panel technology. In most cases, the “burnin” or “after-imaging” or “ghost imaging” will disappear gradually over a period of time after the power has been switched off.

Warning Failure to activate a screen saver, or a periodic screen refresh application may result in severe “burn-in” or “afterimage” or “ghost image” symptoms that will not disappear and cannot be repaired. The damage mentioned above is not covered under your warranty.

Service

- The casing cover should be opened only by qualified service personnel.
- If there is any need for any document for repair or integration, please contact with your local service center. (Please refer to Service contact information listed in Important Information Manual.)
- For transportation information, please refer to “Technical Specifications”.
- Do not leave your monitor in a car/ trunk under direct sun light.

Note Consult a service technician if the monitor does not operate normally, or you are not sure what procedure to take when the operating instructions given in this manual have been followed.

1.2 Notational Descriptions

The following subsections describe notational conventions used in this document.

Notes, Cautions and Warnings

Throughout this guide, blocks of text may be accompanied by an icon and printed in bold or italic type. These blocks contain notes, cautions or warnings. They are used as follows:

Note This icon indicates important information and tips that help you make better use of your computer system.

Caution This icon indicates information that tells you how to avoid either potential damage to hardware or loss of data.

Warning This icon indicates the potential for bodily harm and tells you how to avoid the problem.

Some warnings may appear in alternate formats and may not be accompanied by an icon. In such cases, the specific presentation of the warning is mandated by the relevant regulatory authority.

3

1. Important

1.3 Disposal of product and packing material

Waste Electrical and Electronic Equipment-WEEE

This marking on the product or on its packaging illustrates that, under European Directive 2012/19/EU governing used electrical and electronic appliances, this product may not be disposed of with normal household waste. You are responsible for disposal of this equipment through a designated waste electrical and electronic equipment collection. To determine the locations for dropping off such waste electrical and electronic, contact your local government office, the waste disposal organization that serves your household or the store at which you purchased the product.

Your new monitor contains materials that can be recycled and reused. Specialized companies can recycle your product to increase the amount of reusable materials and to minimize the amount to be disposed of.

All redundant packing material has been omitted. We have done our utmost to make the packaging easily separable into mono materials.

Please find out about the local regulations on how to dispose of your old monitor and packing from your sales representative.

Taking back/Recycling Information for Customers

Philips establishes technically and economically viable objectives to optimize the environmental performance of the organization's product, service and activities. From the planning, design and production stages, Philips emphasizes the important of making products that can easily be recycled. At Philips, end-of-life management primarily entails participation in national takeback initiatives and recycling programs whenever possible, preferably in cooperation with competitors, which recycle all materials (products and related packaging material) in accordance with all Environmental Laws and taking back program with the contractor company.

Your display is manufactured with high quality materials and components which can be recycled and reused.

To learn more about our recycling program please visit
<http://www.philips.com/a-w/about/sustainability.html>

4

2. Setting up the monitor

2. Setting up the monitor

2.1 Installation

Package contents

S Line 273S1

Quick

Start

Register your product and get support at www.philips.com/welcome

Install the base

1. Place the monitor face down on a smooth surface. Pay attention not to scratch or damage the screen.

Power

*USB C-C

*USB C-A

*USB C-C/A

*HDMI

*DP

*Different according to region

2. Hold the stand with both hands. (1) Gently attach the base to the stand. (2) Use your fingers to tighten the screw located at the bottom of the base. (3) Gently attach the stand to the VESA mount area until the latch locks the stand.

2 1 3

Note Secure the arrow of the base towards the front and fix to the column tightly.

5

2. Setting up the monitor Connecting to your PC

Fast Charger

4 6 8 10

2

357 9

1

1

RJ45

USB docking (USB C-C)

a-1

a-2

USB Type-C

a

b

USBC

USB

OR

USB hub (USB A-C)

a-1 a-2

USB Type-A

a

b

USBC

USB

OR

Multi-stream transport

DP IN DP OUT DP IN

DP IN

USBC DP OUT USBC

DP IN

1 Kensington anti-theft lock

2 AC power input

3 HDMI input

4 DisplayPort input

5 USB C

6 RJ45 input

7 DisplayPort output

8 Audio out

9 USB downstream

10 USB downstream/USB fast charger

Connect to PC 1. Connect the power cord to the back of the monitor firmly. 2. Turn off your computer and unplug its power cable. 3. Connect the monitor signal cable to the video connector on the back of your computer. 4. Plug the power cord of your computer and your monitor into a nearby outlet. 5. Turn on your computer and monitor. If the monitor displays an image, installation is complete.

USB C driver installation for RJ45

Before using the USB C docking display, please ensure to install the USB C driver.

You can go to Philips website support page to download the “LAN Drivers”.

Please follow the steps for the installation: 1. Install the LAN driver that matches your system. 2. Double click driver to install, and follow Window’s instructions to proceed with installation. 3. It will show “success” when the installation is finished.

6

2. Setting up the monitor

4. You must reboot your computer after the installation has completed.

5. Now you will be able to see “Realtek USB Ethernet Network Adapter” from your program installed list.

6. We recommend to periodically visit the above web link to check for the availability of the most updated driver.

Note Please contact Philips service hotline for Mac address clone tool as necessary.

5 USB hub

To comply with International energy standards, the USB hub/ports of this display are disabled during Standby and Off modes.

Connected USB devices will not work in this state.

To permanently put the USB function in “ON” state, please go to OSD Menu, then select “USB standby mode”, and switch it to “ON” state. Somehow if your monitor reset to factory setting, ensure to select “USB standby mode” to “ON” state in OSD menu.

6 USB charging

This display has USB ports capable of standard power output including some with USB Charging function (identifiable with power icon). You can use these ports to charge your Smart phone or power your external HDD, for example. The display must be powered ON at all times to be able to use this function.

Some select Philips displays may not Power or Charge your device when it enters to “Sleep/standby ” mode (White

power LED blinking). In that case, please enter to OSD Menu and select “USB Standby Mode”, then, turn the function to “ON” mode (default=OFF). This will then keep the USB power and charging functions active even when the monitor is in sleep/standby mode.

Warning

USB 2.4Ghz wireless devices, such as, wireless mouse, keyboard, and headphones, maybe have interference by the high-speed signal of USB3.2 devices, which may result in a decreased efficiency of the radio transmission. Should this happen, please try the following methods to help reduce the effects of interference.

- Try to keep USB2.0 receivers away from USB3.2 connection port.
- Use a standard USB extension cable or USB hub to increase the space between your wireless receiver and the USB3.2 connection port.

7

2. Setting up the monitor

2.2 Operating the monitor

Description of the control buttons

4

2

1

Switch monitor's power ON and OFF.

Access the OSD menu. Confirm the OSD adjustment.

Adjust the OSD menu.

Adjust the brightness level.

Change the signal input source.

Return to previous OSD level.

SmartImage. There are multiple selections: EasyRead, Office, Photo, Movie, Game, Economy, LowBlue Mode, Off.

Description of the On Screen Display

What is On-Screen Display (OSD)?

On-Screen Display (OSD) is a feature in all Philips LCD monitors. It allows an end user to adjust screen performance or select functions of the monitors directly through an on-screen instruction window. A user friendly on screen display interface is shown as below:

Basic and simple instruction on the control keys

In the OSD shown above, you can press buttons at the front bezel of the monitor to move the cursor, and press OK button to confirm the choice or change.

8

2. Setting up the monitor

The OSD Menu

Below is an overall view of the structure of the On-Screen Display. You can use this as a reference when you want to work your way around the different adjustments later on.

Note If this display has "DPS" for ECO design, the default setting is "ON" mode: it makes

the screen looks slightly dim; for optimum brightness, enter to the OSD to set “DPS” to “OFF” mode.

Main menu

Sub menu

LowBlue Mode

On

Input

Off HDMI 1.4 DisplayPort USB C Auto

Picture

Picture Format

Brightness

Contrast

Sharpness SmartResponse

SmartContrast Gamma

Pixel Orbiting

Over Scan DPS

Audio

Volume Mute

Color

Color Temperature

sRGB

1, 2, 3, 4

On, Off Wide Screen, 4:3, 1:1 0~100 0~100 0~100 Off, Fast, Faster, Fastest On, Off 1.8, 2.0, 2.2, 2.4, 2.6 On, Off On, Off On, Off 0~100 On, Off Native, 5000K, 6500K, 7500K, 8200K, 9300K, 11500K

User Define

Red: 0~100 Green: 0~100

Language OSD Setting

USB Setting Setup

Blue: 0~100

English, Deutsch, Español, , Français, Italiano, Magyar, Nederlands, Português, Português do Brasil, Polski , , Svenska, Suomi, Türkçe, Cestina, , , , ,

Horizontal

0~100

Vertical

0~100

Transparency OSD Time Out USB-C Setting USB Standby Mode

Off, 1, 2, 3, 4 5s, 10s, 20s, 30s, 60s High Data Speed, High Resolution On, Off

Power LED Resolution Notification DP Out Multi-Stream Reset Information

0, 1, 2, 3, 4 On, Off Clone, Extend

Yes, No

Resolution notification This monitor is designed for optimal performance at its native resolution, 1920 x 1080. When the monitor is powered on at a different resolution, an alert is displayed on screen: Use 1920 x 1080 for best results.

Display of the native resolution alert can be switched off from Setup in the OSD (On Screen Display) menu.

Note If your Ethernet connection seems slow, please enter OSD menu and select High Data Speed which supports the LAN speed to 1G.

9

2. Setting up the monitor

Physical Function Tilt

25° -5°

Swivel

Height adjustment

Pivot

130mm

-180° -180°

+180° +180°

0°

0°

-90°

90°

Warning

· To avoid potential screen damage, such as panel peeling, ensure that the monitor does not tilt downward by more than -5 degrees.

- Do not press the screen while adjusting the angle of the monitor. Grasp only the bezel.
- It is important to note that when you adjust the angle of the monitor screen, the entire stand and rotating disk will also move with it as this is a swivel-adjustable monitor.

10

2. Setting up the monitor

2.3 Remove the Base Assembly for VESA Mounting

Before you start disassembling the monitor base, please follow the instructions below to avoid any possible damage or injury.

1. Place the monitor face down on a smooth surface. Pay attention not to scratch or damage the screen. Then lift the monitor stand.

Note This monitor accepts a 100mm x 100mm VESA-Compliant mounting interface. VESA Mounting Screw M4. Always contact manufacturer for wall-mount installation.

100mm

100mm

2. While keeping the release button pressed, tilt the base and slide it out.

0°

90°

-5°

* Display design may differ from those illustrated.

Warning

- To avoid potential screen damage, such as panel peeling, ensure that the monitor does not tilt downward by more than -5 degrees.
- Do not press the screen while adjusting the angle of the monitor. Grasp only the bezel.

11

3. Image Optimization

3. Image Optimization

3.1 SmartImage

What is it? SmartImage provides presets that optimize display for different types of content, dynamically adjusting brightness, contrast, color and sharpness in real time. Whether you're working with text applications, displaying images or watching a video, Philips SmartImage delivers great optimized monitor performance.

Why do I need it? You want a monitor that delivers optimized display all your favorite types of content, SmartImage software dynamically adjust brightness, contrast, color and sharpness in real time to enhance your monitor viewing experience.

How does it work? SmartImage is an exclusive, leading edge Philips technology that analyzes the content displayed on your screen. Based on a scenario you select, SmartImage dynamically enhances the contrast, color saturation and sharpness of images to enhance the contents being displayed all in real time with the press of a single button.

How to enable SmartImage?

1. Press to launch the SmartImage on screen display.
2. Keep pressing to toggle among EasyRead, Office, Photo, Movie, Game, Economy, LowBlue Mode, Off.
3. The SmartImage on screen display will remain on screen for 5 seconds, or you can also press "OK" to make confirmation.

There are multiple selections: EasyRead, Office, Photo, Movie, Game, Economy, LowBlue Mode, Off.

- EasyRead: Helps improve reading of text based application like PDF ebooks. By using a special algorithm which increases the contrast and boundary sharpness of text content, the display is optimized for a stress-free reading by adjusting the brightness, contrast and color temperature of the monitor.
- Office: Enhances text and dampens brightness to increase readability and reduce eye strain. This mode significantly enhances readability and productivity when you're working with spreadsheets, PDF files, scanned articles or other general office applications.
- Photo: This profile combines color saturation, dynamic contrast and

3. Image Optimization

sharpness enhancement to display photos and other images with outstanding clarity in vibrant colors all without artifacts and faded colors.

- **Movie:** Ramped up luminance, deepened color saturation, dynamic contrast and razor sharpness displays every details in darker areas of your videos without color washout in brighter areas maintaining a dynamic natural values for the ultimate video display.
- **Game:** Turn on over drive circuit for best response time, reduce jaggy edges for fast moving objects on screen, enhance contrast ratio for bright and dark scheme, this profile delivers the best gaming experience for gamers.
- **Economy:** Under this profile, brightness, contrast are adjusted and backlighting finetuned for just right display of everyday office applications and lower power consumption.
- **LowBlue Mode:** LowBlue Mode for easy on-the-eyes productivity Studies have shown that just as ultra-violet rays can cause eye damage, shortwave length blue light rays from LED displays can cause eye damage and affect vision over time. Developed for wellbeing, Philips LowBlue Mode setting uses a smart software technology to reduce harmful shortwave blue light.
- **Off:** No optimization by SmartImage. Note
Philips LowBlue mode, mode 2 compliance with TUV Low Blue Light certification, you can have this mode by simply press the hotkey , then press to select LowBlue Mode, see above SmartImage selection steps.

3.2 SmartContrast

What is it?

Unique technology that dynamically analyzes displayed content and automatically optimizes a Monitor's contrast ratio for maximum visual clarity and viewing enjoyment, stepping up backlighting for clearer, crisper and brighter images or dimming backlighting for clear display of images on dark backgrounds.

Why do I need it?

You want the very best visual clarity and viewing comfort for every type of content. SmartContrast dynamically controls contrast and adjusts backlighting for clear, crisp, bright gaming and video images or displays clear, readable text for office work. By reducing your monitor's power consumption, you save on energy costs and extend the lifetime of your monitor.

How does it work?

When you activate SmartContrast, it will analyse the content you are displaying in real time to adjust colors and control backlight intensity. This function will dynamically enhance contrast for a great entertainment experience when viewing videos or playing games.

13

4. Daisy-chain function

4. Daisy-chain function

DisplayPort Multi-Stream feature enables multiple monitor connections.

This Philips display is equipped with DisplayPort interface and DisplayPort over USB-C which enables daisy-chaining to multiple displays.

Now you can daisy chain and use multiple monitors via a single cable from one display to the next.

To daisy-chain monitors, first to check below:

Make sure the GPU on your PC support DisplayPort 1.2 MST (Multi-stream transport).

Note Depending on the capabilities of your graphic cards, you should be able to daisy chain multiple displays with various configurations. Your display configurations will depend on your graphic card capabilities. Please check with your graphic card vendor and always update your graphic card driver. DisplayPort multi-streaming over DisplayPort

DisplayPort multi-streaming over USB-C

USB-C DP OUT USB-C

DP IN

Display

USB-C Setting

Resolution

Maximum number of external monitors that can be supported

Extend mode (USBC)

1920 x 1080 High

3

@60Hz

Resolution

High Data Speed 1

Note We recommend to set USBC Setting to High Data Speed, please enter OSD menu and select High Data Speed which supports the LAN speed to 1G.

To select one of DP Out Multi-stream modes:

Press button, select Setup > DP Out Multi-stream > Extend.

DP IN DP OUT DP IN

DP IN

Display Resolution 1920 x 1080 @ 60Hz

Maximum number of external monitors that can be supported Extend mode (DisplayPort)

3

14

5. Designs to prevent computer vision syndrome

5. Designs to prevent computer vision syndrome (CVS)

Philips monitor is designed to prevent eye strain caused by prolonged computer use.

Follow below instructions and use Philips monitor to efficiently reduce fatigue and maximum working productivity.

1. Appropriate environment lighting:

- Adjusting the environment lighting similar to that of your screen brightness, avoid the fluorescent lighting, and surfaces that don't reflect too much light.

- Adjusting the brightness and contrast to appropriate level.

2. Good working habits:

- Excessive usage of monitor can cause eye discomfort, it's better to take shorter breaks more often at your workstation than longer breaks and less often; for example a 5-10 minute break after 50-60-minute continuous screen use is likely to be better than a 15-minute break every two hours.

- Looking at something varying distances after a long period focusing on the screen.

- Gently closing and rolling your eyes to relax.

- Conscious blinking often while working.

- Gently stretch your neck, and slowly tilt your head forward, backward, side for pain relief.

3. Ideal working posture

- Reposition your screen to appropriate height and angle according to your height.

4. Choose Philips monitor for easy-oneyes.

- Anti-glare screen: Anti-glare screen efficiently reduces annoying and distracting reflections that caused eye fatigue.

- Flicker-free technology designs to regulate brightness and reduce flicker for more comfortable viewing.

- LowBlue mode: Blue light may cause eye strains. Philips LowBlue mode allows you to set different blue light filter levels for variety working situation.

- EasyRead mode for a paperlike reading experience, giving a more comfortable viewing experience while dealing with long documents on the screen.

15

6. Technical Specifications

6. Technical Specifications

Picture/Display Monitor Panel Type Backlight Panel Size Aspect Ratio Pixel Pitch

Contrast Ratio(typ.) Native Resolution Maximum Resolution Viewing Angle Display

Colors Flicker Free Picture Enhancement Vertical Refresh Rate Horizontal Frequency

sRGB LowBlue Mode EasyRead Connectivity Signal Input source

Connectors

Sync input

IPS Technology W-LED 27" W (68.6 cm) 16:9 0.3114 (H) mm x 0.3114 (V) mm 1000:1

1920 x 1080 @ 60 Hz 1920 x 1080 @ 75 Hz 178° (H) / 178° (V) @ C/R > 10 (typ.)

16.7M (6-bit+FRC) YES SmartImage 48 Hz – 75 Hz 30 kHz – 85 kHz YES YES YES

HDMI, DisplayPort, USBC (DP Alt mode)

1x HDMI 1.4 (HDCP 1.4) 1x DisplayPort 1.2 (HDCP 1.4) 1x USBC (upstream) 1x RJ45,

Ethernet LAN (10M/100M/1000M) 4x USB-A (downstream with x1 fast charge BC 1.2)

(5V/1.5A) 1x DisplayPort out 1x Audio out

Separate Sync

USB USB Ports

Power Delivery

Super Speed Convenience User Convenience Built-in Speakers

USBC x 1 (upstream, DP Alt mode, HDCP 1.4) USB-A x 4 (downstream with x1 fast

charge BC 1.2) USBC: USB PD version 3.0, typical 65W (5V/3A, 7V/3A, 9V/3A, 10V/3A,

12V/3A, 15V/3A, 20V/3.25A) USB-Ax1: fast charge B.C 1.2, up to 7.5W (5V/1.5A)

USBC/USB-A: USB 3.2 Gen1, 5 Gbps

2 W x 2

16

6. Technical Specifications

OSD Languages

Other Convenience Plug & Play Compatibility Stand Tilt Swivel Height adjustment Pivot

Power

Consumption

Normal Operation Sleep (Standby mode) Off mode

Heat Dissipation*

Normal Operation

Sleep (Standby mode)

Off mode On Mode (ECO mode) Power LED indicator Power Supply Dimensions

Product with stand (WxHxD) Product without stand (WxHxD) Product with packaging (WxHxD) Weight Product with stand Product without stand Product with packaging Operating Condition Temperature range (operation)

English, German, Spanish, Greek, French, Italian, Hungarian, Dutch, Portuguese, Brazil Portuguese, Polish, Russian, Swedish, Finnish, Turkish, Czech, Ukranian, Simplified Chinese, Traditional Chinese, Japanese, Korean VESA mount (100 x 100 mm), Kensington Lock DDC/CI, sRGB, Windows 11/10/8.1/8/7, Mac OS X
-5 / +25 degree -180 / +180 degree 130 mm -90 / +90 degree

AC Input Voltage at 100VAC , 50Hz

AC Input Voltage at 115VAC , 50Hz

AC Input Voltage at 230VAC, 50Hz

24.6 W (typ.)

24.6 W (typ.)

24.1 W (typ.)

0.3 W (typ.)

0.3 W (typ.)

0.3 W (typ.)

0.3 W (typ.)

0.3 W (typ.)

0.3 W (typ.)

AC Input Voltage AC Input Voltage AC Input Voltage

at 100VAC ,

at 115VAC ,

at 230VAC ,

50Hz

50Hz

50Hz

83.96 BTU/hr

83.96 BTU/hr

82.25 BTU/hr

(typ.)

(typ.)

(typ.)

1.02 BTU/hr

1.02 BTU/hr

1.02 BTU/hr

(typ.)

(typ.)

(typ.)

1.02 BTU/hr

1.02 BTU/hr

1.02 BTU/hr

(typ.)

(typ.)

(typ.)

12.4 W (typ.)

On mode: White, Standby/Sleep mode: White (blinking)

Built-in, 100-240V AC, 50-60Hz

613 x 537 x 205 mm 613 x 366 x 54 mm 730 x 471 x 193 mm

6.79 kg 5.03 kg 10.29 kg

0°C to 40 °C

17

6. Technical Specifications

Relative humidity (operation) Atmospheric pressure (operation) Temperature range
(Non-operation) Relative humidity (Non-operation) Atmospheric pressure (Non-
operation)

Environmental and energy ROHS Packaging Specific Substances Cabinet Color Finish

20% to 80% 700 to 1060hPa -20°C to 60°C 10% to 90% 500 to 1060hPa

YES 100% recyclable 100% PVC BFR free housing

Black Texture

Note This data is subject to change without notice. Go to www.philips.com/support to
download the latest version of leaflet.

6. Technical Specifications

6.1 Resolution & Preset Modes

H. freq (kHz) 31.47 31.47 35.00 37.86 37.50 35.16 37.88 46.88 48.08 47.73 48.36 56.48
60.02 44.77
60 63.89 79.98 55.94 65.29 67.50 83.89

Resolution V. freq (Hz)

720 x 400 640 x 480 640 x 480 640 x 480 640 x 480 800 x 600 800 x 600 800 x 600 800
x 600 832 x 624 1024 x 768 1024 x 768 1024 x 768 1280 x 720 1280 x 960 1280 x 1024
1280 x 1024 1440 x 900 1680 x 1050 1920 x 1080 1920 x 1080
70.09 59.94 66.67 72.81 75.00 56.25 60.32 75.00 72.19 74.55 60.00 70.07 75.03 59.86
60 60.02 75.03 59.89 59.95 60.00 74.97

Note Please notice that your display works best at native resolution of 1920 x 1080. For best display quality, please follow this resolution recommendation.

7. Power Management

7. Power Management

If you have VESA DPM compliance display card or software installed in your PC, the monitor can automatically reduce its power consumption when not in use. If an input from a keyboard, mouse or other input device is detected, the monitor will 'wake up' automatically. The following table shows the power consumption and signaling of this automatic power saving feature:

Power Management Definition

VESA Mode

Video H-sync V-sync

Power LED Used Color

Active

ON

Yes

Sleep/

Standby OFF

No

mode

Off mode OFF

—

24.6 W

Yes

(typ.) 158.0 W

White

(max.)

No

0.3 W (typ.)

White (blink)

– 0.3 W (typ.) OFF

The following setup is used to measure power consumption on this monitor. · Native resolution: 1920 x 1080 · Contrast: 50% · Brightness: 80% · Color temperature: 6500k with full white pattern

Note This data is subject to change without notice.

20

8.Customer care and warranty

8. Customer care and warranty

8.1 Philips' Flat Panel Monitors Pixel Defect Policy

Philips strives to deliver the highest quality products. We use some of the industry's most advanced manufacturing processes and practice stringent quality control. However, pixel or sub pixel defects on the TFT Monitor panels used in flat panel monitors are sometimes unavoidable. No manufacturer can guarantee that all panels will be free from pixel defects, but Philips guarantees that any monitor with an unacceptable number of defects will be repaired or replaced under warranty. This notice explains the different types of pixel defects and defines acceptable defect levels for each type. In order to qualify for repair or replacement under warranty, the number of pixel defects on a TFT Monitor panel must exceed these acceptable levels. For example, no more than 0.0004% of the sub pixels on a monitor may be defective. Furthermore, Philips sets even higher quality standards for certain types or combinations of pixel defects that are more noticeable than others. This policy is valid worldwide.

subpixel

together form an image. When all sub pixels of a pixel are lit, the three colored sub pixels together appear as a single white pixel. When all are dark, the three colored sub pixels together appear as a single black pixel. Other combinations of lit and dark sub pixels appear as single pixels of other colors.

Types of Pixel Defects Pixel and sub pixel defects appear on the screen in different ways. There are two categories of pixel defects and several types of sub pixel defects within each category.

Bright Dot Defects Bright dot defects appear as pixels or sub pixels that are always lit or 'on'. That is, a bright dot is a sub-pixel that stands out on the screen when the monitor displays a dark pattern. There are the types of bright dot defects.

One lit red, green or blue sub pixel.

pixel

Pixels and Sub pixels A pixel, or picture element, is composed of three sub pixels in the primary colors of red, green and blue. Many pixels

Two adjacent lit sub pixels: – Red + Blue = Purple – Red + Green = Yellow – Green + Blue = Cyan (Light Blue)

21

8.Customer care and warranty

Three adjacent lit sub pixels (one white pixel).

Note A red or blue bright dot must be more than 50 percent brighter than neighboring dots while a green bright dot is 30 percent brighter than neighboring dots. **Black Dot Defects** Black dot defects appear as pixels or sub pixels that are always dark or 'off'. That is, a dark dot is a sub-pixel that stands out on the screen when the monitor displays a light pattern. These are the types of black dot defects.

Proximity of Pixel Defects Because pixel and sub pixels defects of the same type that are near to one another may be more noticeable, Philips also specifies tolerances for the proximity of pixel defects.

Pixel Defect Tolerances In order to qualify for repair or replacement due to pixel defects during the warranty period, a TFT Monitor panel in a Philips flat panel monitor must have pixel or sub pixel defects exceeding the tolerances listed in the following tables.

22

8.Customer care and warranty

BRIGHT DOT DEFECTS 1 lit subpixel 2 adjacent lit subpixels 3 adjacent lit subpixels (one white pixel) Distance between two bright dot defects* Total bright dot defects of all types

BLACK DOT DEFECTS 1 dark subpixel 2 adjacent dark subpixels 3 adjacent dark subpixels Distance between two black dot defects* Total black dot defects of all types
TOTAL DOT DEFECTS Total bright or black dot defects of all types
Note 1 or 2 adjacent sub pixel defects = 1 dot defect

ACCEPTABLE LEVEL 2 1 0

>15mm 2

ACCEPTABLE LEVEL 3 or fewer 2 or fewer 0 >15mm 3 or fewer

ACCEPTABLE LEVEL 5 or fewer

23

8.Customer care and warranty

8.2 Customer Care & Warranty

For warranty coverage information and additional support requirements valid for your region, please visit www.philips.com/support website for details or contact your local Philips Customer Care Center.

For Warranty Period please refer to Warranty Statement in Important Information Manual.

For extended warranty, if you would like to extend your general warranty period, an Out of Warranty service package is offered via our Certified Service Center.

If you wish to make use of this service, please be sure to purchase the service within 30 calendar days of your original purchase date. During the extended warranty period, the service includes pickup, repair and return service, however the user will be responsible for all costs accrued.

If the Certified Service Partner cannot perform the required repairs under the offered extended warranty package, we will find alternative solutions for you, if possible, up to the extended warranty period you have purchased.

Please contact our Philips Customer Service Representative or local contact center (by Consumer care number) for more details.

Philips Customer Care Center number listed below.

· Local Standard · Extended Warranty · Total Warranty Period

Warranty Period

Period

· Depend on

· + 1 Year

· Local Standard warranty period

different Regions

+1

· + 2 Years

· Local Standard warranty period

+2

· + 3 Years

· Local Standard warranty period

+3

**Proof of original purchase and extended warranty purchase required.

Note Please refer to Important Information Manual for regional service hotline, which is available on the Philips website support page.

9. Troubleshooting & FAQs

9. Troubleshooting & FAQs

9.1 Troubleshooting

This page deals with problems that can be corrected by a user. If the problem still persists after you have tried these solutions, contact Philips customer service representative.

Common Problems

No Picture (Power LED not lit) · Make sure the power cord is plugged into the power outlet and into the back of the monitor. · First, ensure that the power button on the front of the monitor is in the OFF position, then press it to the ON position.

No Picture (Power LED is White) · Make sure the computer is turned on. · Make sure the signal cable is properly connected to your computer. · Make sure the monitor cable has no bent pins on the connect side. If yes, repair or replace the cable. · The Energy Saving feature may be activated

Screen says

- Make sure the monitor cable is properly connected to your computer. (Also refer to the Quick Start Guide).
- Check to see if the monitor cable has bent pins.

- Make sure the computer is turned on.

AUTO button doesn't function · The auto function is applicable only in VGA-Analog mode. If the result is not satisfactory, you can do manual adjustments via the OSD menu.

Note The Auto Function is not applicable in DVI-Digital mode as it is not necessary.

Visible signs of smoke or sparks · Do not perform any troubleshooting steps · Disconnect the monitor from mains power source immediately for safety · Contact with Philips customer service representative immediately.

Imaging Problems

Image is not centered · Adjust the image position using the "Auto" function in OSD Main Controls. · Adjust the image position using the

Phase/Clock of Setup in OSD Main Controls. It is valid only in VGA mode.

Image vibrates on the screen · Check that the signal cable is properly securely connected to the graphics board or PC.

Vertical flicker appears

- Adjust the image using the “Auto” function in OSD Main Controls.
- Eliminate the vertical bars using the Phase/Clock of Setup in OSD Main Controls. It is valid only in VGA mode.

25

9.Troubleshooting & FAQs

Horizontal flicker appears

- Adjust the image using the “Auto” function in OSD Main Controls.
- Eliminate the vertical bars using the Phase/Clock of Setup in OSD Main Controls. It is valid only in VGA mode.

Image appears blurred, indistinct or too dark

- Adjust the contrast and brightness on On-Screen Display.

An “after-image”, “burn-in” or “ghost image” remains after the power has been turned off.

- Uninterrupted display of still or

static images over an extended period may cause “burn-in”, also known as “after-

imaging” or “ghost imaging”, on your screen. “Burn-in”, “after-imaging”, or “ghost

imaging” is a well-known phenomenon in LCD panel technology. In most cases, the

“burn-in” or “after-imaging” or “ghost imaging” will disappear gradually over a period of time after the power has been switched off.

- Always activate a moving screen saver program when you leave your monitor unattended.
- Always activate a periodic screen refresh application if your LCD monitor will display unchanging static content.
- Failure to activate a screen saver, or a periodic screen refresh application may result in severe “burn-in” or “after-imaging” or “ghost imaging” symptoms that will not disappear and cannot be repaired. The damage mentioned above is not covered under your warranty.

Image appears distorted. Text is fuzzy or blurred.

- Set the PC's display resolution to the same mode as monitor's recommended screen native resolution.

Green, red, blue, dark, and white dots appears on the screen

- The remaining dots are normal characteristic of the liquid crystal used in today's technology, Please refer the pixel policy for more detail.

- * The "power on" light is too strong and is disturbing

- You can adjust "power on" light using the power LED Setup in OSD main Controls.

For further assistance, refer to the Service contact information listed in Important Information Manual and contact Philips customer service representative.

- * Functionality different according to display.

9.2 General FAQs

Q1: Ans.:

When I install my monitor what should I do if the screen shows 'Cannot display this video mode'?

Recommended resolution for this monitor: 1920 x 1080.

- Unplug all cables, then connect your PC to the monitor that you used previously.

- In the Windows Start Menu, select Settings/Control Panel. In the Control Panel Window, select the Display icon. Inside the Display Control Panel, select the 'Settings' tab. Under the setting tab, in box labelled 'desktop area', move the sidebar to 1920 x 1080 pixels.

26

9.Troubleshooting & FAQs

- Open 'Advanced Properties' and set the Refresh Rate to 60 Hz, then click OK.

- Restart your computer and repeat step 2 and 3 to verify that your PC is set at 1920 x 1080.

- Shut down your computer, disconnect your old monitor and reconnect your Philips LCD monitor.

- Turn on your monitor and then turn on your PC.

Q2: What is the recommended refresh rate for LCD monitor?

Ans.: Recommended refresh rate in LCD monitors is 60 Hz, In case of any disturbance on screen, you can set it up to 75 Hz to see if that removes the disturbance.

Q3: What are the .inf and .icm files? How do I install the drivers (.inf and .icm)?

Ans.: These are the driver files for your monitor. Your computer may ask you for monitor drivers (.inf and .icm files) when you first install your monitor. Follow the instructions in your user manual, monitor drivers (.inf and .icm files) will be installed automatically.

Q4: How do I adjust the resolution?

Ans.: Your video card/graphic driver and monitor together determine the available resolutions. You can select the desired resolution under Windows® Control Panel with the “Display properties”.

Q5: What if I get lost when I am making monitor adjustments via OSD?

Ans.: Simply press

button, then

select `Setup' >'Reset' to recall all

of the original factory settings.

Q6: Is the LCD screen resistant to scratches?

Ans.:

In general it is recommended that the panel surface is not subjected to excessive shocks and is protected from sharp or blunt objects. When handling the monitor, make sure that there is no pressure or force applied to the panel surface side. This may affect your warranty conditions.

Q7: How should I clean the LCD surface?

Ans.:

For normal cleaning, use a clean, soft cloth. For extensive cleaning, please use isopropyl alcohol. Do not use other solvents such as ethyl alcohol, ethanol, acetone, hexane, etc.

Q8: Ans.:

Can I change the color setting of my monitor?

Yes, you can change your color setting through OSD control as the following procedures.

- Press “OK” to show the OSD (On Screen Display) menu
- Press “Down Arrow” to select the option “Color” then press “OK” to enter color setting, there are three settings as below.

1. Color Temperature: The settings are Native, 5000K, 6500K, 7500K, 8200K, 9300K and 11500K. With settings in the 5000K range the panel appears “warm, with a red-white color tone”, while a 11500K temperature yields “cool, bluewhite toning”.

2. sRGB: This is a standard setting for ensuring correct exchange of colors between different device (e.g. digital cameras, monitors, printers, scanners, etc).

27

9.Troubleshooting & FAQs

3. User Define: The user can choose his/her preference color setting by adjusting red, green, blue color.

Note A measurement of the color of light radiated by an object while it is being heated. This measurement is expressed in terms of absolute scale, (degrees Kelvin). Lower Kevin temperatures such as 2004K are red; higher temperatures such as 9300K are blue. Neutral temperature is white, at 6504K.

Q9: Can I connect my LCD monitor to any PC, workstation or Mac?

Ans.: Yes. All Philips LCD monitors are fully compatible with standard PCs, Macs and workstations. You may need a cable adapter to connect the monitor to your Mac system. Please contact your Philips sales representative for more information.

Q10: Are Philips LCD monitors Plugand- Play?

Ans.: Yes, the monitors are Plug-andPlay compatible with Windows 11/10/8.1/8/7, Mac

OSX.

Q11: What is Image Sticking, or Image Burn-in, or After Image, or Ghost Image in LCD panels?

Ans.: Uninterrupted display of still or static images over an extended period may cause “burn-in”, also known as “after-imaging” or “ghost imaging”, on your screen. “Burn-in”, “after-imaging”, or “ghost imaging” is a well-known phenomenon in LCD panel technology. In most cases, the “burn-in” or “after-imaging” or

“ghost imaging” will disappear gradually over a period of time after the power has been switched off. Always activate a moving screen saver program when you leave your monitor unattended. Always activate a periodic screen refresh application if your LCD monitor will display unchanging static content.

Warning Failure to activate a screen saver, or a periodic screen refresh application may result in severe “burn-in” or “afterimage” or “ghost image” symptoms that will not disappear and cannot be repaired. The damage mentioned above is not covered under your warranty.

Q12: Ans.:

Why is my Display not showing sharp text, and is displaying jagged characters?

Your LCD monitor works best at its native resolution of 1920 x 1080. For best display, please use this resolution.

Q13: How to unlock/lock my hot key?

Ans.:

To lock the OSD, press and hold

the

button while the

monitor is off and then press button to turn the monitor on.

To un-lock the OSD, press and

hold the

button while the

monitor is off and then press button to turn the monitor on.

28

9.Troubleshooting & FAQs

Q14: Where can I find Important Information Manual mentioned in EDFU?

Ans.: Important Information Manual can be download on the Philips website support page.

Q15:

Why I cannot automatically switch to the connected input source after daisy chain over USB-C?

Ans.: It's because your primary monitor connects to more than one input source at the same time. When you use the primary monitor to the notebook with USB-C, and also daisy chain to the secondary monitor. Once the notebook goes into standby mode, if you want to show the content from HDMI or DisplayPort, please press to change the signal input source.

29

2022 © TOP Victory Investments Ltd. All rights reserved.

This product has been manufactured by and is sold under the responsibility of Top Victory Investments Ltd., and Top Victory Investments Ltd. is the warrantor in relation to this product. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V. and are used under license.

Specifications are subject to change without notice.

Version: M10273SE1T

Documents / Resources



[PHILIPS S Line 273S1 LCD Monitor With USB-C \[pdf\]](#) User Manual
S Line 273S1 LCD Monitor With USB-C, S Line 273S1, LCD Monitor With USB-C, Monitor With USB-C, With USB-C

References

- [User Manual](#)

Philips
LCD Monitor With USB-C, Monitor with USB C, Philips, S Line 273S1, S Line 273S1 LCD Monitor With USB-C, with USB C

Leave a comment

Your email address will not be published. Required fields are marked *

Comment *

Name

Email

Website

☐ Save my name, email, and website in this browser for the next time I comment.

Post Comment

Search:

e.g. whirlpool wrf535swhz

Search

[Manuals+](#) | [Upload](#) | [Deep Search](#) | [Privacy Policy](#) | [@manuals.plus](#) | [YouTube](#)

This website is an independent publication and is neither affiliated with nor endorsed by any of the trademark owners. The "Bluetooth®" word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. The "Wi-Fi®" word mark and logos are registered trademarks owned by the Wi-Fi Alliance. Any use of these marks on this website does not imply any affiliation with or endorsement.