

PHOTON TEK Full Spectrum LED Warranty

Home » PHOTON TEK » PHOTON TEK Full Spectrum LED Warranty ™

Contents

- 1 X 465W PRO
- **2 FULL CONTROL**
- **3 ITEMS INCLUDED IN THE BOX:**
- 4 PPFD: PHOTOSYNTHETIC PHOTON FLUX DENSITY (µmol/m2/s)
- 5 Documents / Resources
 - **5.1 References**
- **6 Related Posts**



X 465W PRO

PHOTONTEK FULL-SPECTRUM LED
EFFICACY - 2.7 µmol/J
PPF - 1256 µmol/s
INPUT VOLTAGE - 120-270V
POWER CONSUMPTION - 465W
COVERAGE AREA - 3' x 3' - 4' x 4'
APPLICATION - Multi-layer, Room, Tent
WATERPROOF & DUSTPROOF - IP65

LIFETIME (LED BARS) - 60 000 hrs

LIGHT DISTRIBUTION - 120°

LIGHT SOURCE - Osram & Lumileds Philips Diodes

DIODES RATIO - Red 15%, White 85%

DIODES EFFICIENCY - Osram Dark Red 660NM 3.3 µmol/J; Lumileds Philips White 2.9 µmol/J

DIMMABLE OFF-25%-50%-75%-100% with 0-10V Light Dimmer (Included)

EXTERNAL CONTROL PHOTONTEK - Digital Controller

WEIGHT - 24.25 Lbs

DIMENSIONS - 39.29" x 35.43" x 2.92"

SPECTRUM - Full Spectrum

THERMAL MANAGEMENT - Passive


BTU (With Driver Attached): 1706 BTUs/h (With Driver Remote): 1586 BTUs/h


POWER FACTOR >0.95

DRIVER LOCATION – Fixed in structure or detachable for remote use (Extension Cables Sold Separately)

WARRANTY - 5 Years

CERTIFICATIONS FCC, CSA, IC, IP65





INPUT CURRENT (A/W) PER DIMMING RANGE

POWER (DIMMING)	25%	50%	75%	100%
AMPS	0.65	1.3	1.96	2.61
WATTAGE	116.3W	232.5W	348.8W	465W



FULL CONTROL

PhotonTek Pro LED Fixtures can be fully controlled with either the PhotonTek Digital Controller or with any other Control System that utilizes a 0-10V output signal.

ITEMS INCLUDED IN THE BOX:

- 6 x PHOTONTEK 100W Full-Spectrum Magnet LED Bars
- 1 x PHOTONTEK 465W Driver with Connecting Cables
- 1 x LED Structure with Connecting Cables
- 1 x Power Cable (NEMA 5-15P Plug for 120V)
- 1 x 0-10V Light Dimmer + Velcro
- 2 x Metal Cable Hangers
- 1 x Manual

PPFD: PHOTOSYNTHETIC PHOTON FLUX DENSITY (µmol/m2/s)

ALL TESTS CONDUCTED WITH 100% DRIVER POWER

FACTORS THAT CAN INFLUENCE PPFD TESTS

- TEST EQUIPMENT.
- LAMP BEADS DEVIATION
- AMBIENT TEMPERATURE DEVIATION
- PC COVER TRANSMITTANCE DEVIATION
- POWER SOURCE EFFICIENCY DEVIATION
- REFLECTION CONSIDERED OR NOT

RECOMMENDED PPFD (mol/m2/s)

PLANT	SEED	CLONES	VEGETATIVE	FLOWERING
CANNABIS	100-300	75-150	300-550	650+
TOMATOES	150-350	75-150	350-550	650+
CUCUMBERS	100-300		300-550	650+
PEPPERS	150-350	_	300-550	650+

PHOTONTEK X 465W PRO PPFD MAPS
TEST AREA 4' X 4'
TEST POINTS 25
TEST EQUIPMENT INTEGRATING 2 METER SPHERE
& EVERFINE PLA20
AMBIENT TEMPERATURE 25°
HEIGHT FROM CANOPY 5.9", 11.8", 19.7", 39.4", 59"
REFLECTION 0%

HEIGHT TO TEST POINT - 5.9"


CANOPY AVERAGE PPFD 4'x4': 783.52 µmol/m2/s

HEIGHT TO TEST POINT 11.8"

CANOPY AVERAGE PPFD 4'x4': 653.28 µmol/m2/s

HEIGHT TO TEST POINT 19.7"

CANOPY AVERAGE PPFD 4'x4': 578.8 µmol/m2/s





HEIGHT TO TEST POINT 39.4"

CANOPY AVERAGE PPFD 4'x4': 452.96 µmol/m2/s

HEIGHT TO TEST POINT 59"

CANOPY AVERAGE PPFD 4'x4': 361.54 µmol/m2/s





General contact:

info@photontek-lighting.com

FOR MORE INFORMATION ON LUMATEK PRODUCTS VISIT WWW.PHOTONTEK-LIGHTING.COM

Documents / Resources



PHOTON TEK Full Spectrum LED [pdf] Warranty Full Spectrum LED, X 465W PRO

References

- 5 LED & Conventional lighting solutions | Philips lighting
- PHOTONTEK Lighting | LED lighting | LED grow lights | LED Fixtures

Manuals+,