




## PLT SOLUTIONS PLT-12399 Selectable Ultra Thin LED Downlight Fixture User Manual

[Home](#) » [PLT SOLUTIONS](#) » PLT SOLUTIONS PLT-12399 Selectable Ultra Thin LED Downlight Fixture User Manual 

PLT SOLUTIONS PLT-12399 Selectable Ultra Thin LED Downlight Fixture



## Contents

- [1 COLOR SELECTABLE ULTRA-THIN LED DOWNLIGHT](#)
- [2 PERFORMANCE SUMMARY](#)
- [3 DIMMER COMPATIBILITY](#)
- [4 DIMENSIONS](#)
- [5 WARNINGS](#)
- [6 Documents / Resources](#)
  - [6.1 References](#)
- [7 Related Posts](#)

## COLOR SELECTABLE ULTRA-THIN LED DOWNLIGHT

project name	type
catalog number	
comments	voltage
approved by	date

### APPLICATIONS

- Offices
- Lobbies
- Conference Rooms
- Living Rooms
- Hallways
- Bathrooms
- Laundry Rooms

### DESCRIPTION

Add downlights as part of new construction or renovation projects with these easy to install ultra-thin LED downlights featuring 5 selectable color temperatures.

### FEATURES

- Energy efficient replacement for 60W, 75W, and 100W approved by date incandescents
- High color rendering index (CRI) of 90 makes color appear more naturally
- Comes with remote junction box that allows for installation around obstructions
- IC Rated and air-tight
- Dimmable; see Compatible Dimmers section for full list of compatible dimmers
- Color temperature can be adjusted via switch on back of fixture; see installation instructions for more information

### LISTINGS

- ETL Listed for damp locations
- IC Rated
- RoHS
- JA8
- Energy Star

## **PERFORMANCE**

- CRI: 90
- CCT: 2700K, 3000K, 3500K, 4000K, and 5000K
- Rated Lifetime L70: 50,000 hours

## **ELECTRICAL**

- Power Factor: >0.9
- Input Voltage: 120V
- Surge Protection: 2.5kV

## **THERMAL**

- -4°F to 104°F (-20°C to 40°C) operating temperature

## **CONSTRUCTION**

- Aluminum body with aluminum trim, both with white finish
- White translucent acrylic lens

## **WARRANTY**

- 3 year limited warranty; see [pltsolutions.com](https://www.pltsolutions.com) for warranty details

PERFORMANCE	<b>Power Consumption</b>	9, 12, 14, 22 Watt
	<b>Lumens</b>	600, 800, 900, 1600
	<b>Efficacy (LPW)</b>	64, 67, 73
	<b>CRI</b>	90
	<b>CCT</b>	2700K, 3000K, 3500K, 4000K, 5000K
	<b>Beam Angle</b>	110°
	<b>Life (L70)</b>	50,000
ELECTRICAL	<b>Power Factor</b>	>0.9
	<b>Input Voltage</b>	120V
CONSTRUCTION	<b>Finish</b>	White
	<b>Lens</b>	Frosted
LISTINGS	<b>Certifications</b>	ETL Listed; JA8; Energy Star
	<b>Material Usage</b>	RoHS – No mercury or lead
	<b>Environment</b>	Damp Location Rated

## PERFORMANCE SUMMARY

Item #	Size	Lumens	Wattage	LPW	Voltage	Replaces	CCT	CRI	Life/ Hours	Dimmable
PLT-12399	4"	600	9	67	120V	60W Incandescent	2700K/ 3000K/ 3500K/ 4000K/ 5000K	90	50,000	Yes
PLT-12404	4"	800	12	67	120V	75W Incandescent	2700K/ 3000K/ 3500K/ 4000K/ 5000K	90	50,000	Yes
PLT-12405	6"	900	14	64	120V	75W Incandescent	2700K/ 3000K/ 3500K/ 4000K/ 5000K	90	50,000	Yes
PLT-12406	8"	1600	22	73	120V	100W Incandescent	2700K/ 3000K/ 3500K/ 4000K/ 5000K	90	50,000	Yes

## DIMMER COMPATIBILITY

Brand	Model #
Lutron	PD-6WCL
Lutron	DVCL-153P
Lutron	SFTU-5A3P
Lutron	DMD-LE3-D
Lutron	CTCL-153P
Lutron	DV-600P
Leviton	6621
Leviton	6672
Leviton	IPL06-10Z
Cooper	SI06P

## DIMENSIONS

### 4" DIMENSIONS:

**Outside Diameter:** 5"

**Inside Diameter:** 3.25"

**Height:** 1"

**Cable Length (downlight half):** 6.5"


**Weight:** 0.72 lbs

**Junction Box Length:** 3.5"

**Junction Box Width:** 4"

**Junction Box Height:** 1.5"

**Combined Cable Length:** 14"



**CUT OUT: Ø 4.25"**

#### **6" DIMENSIONS:**

**Outside Diameter: 6.89"**

**Inside Diameter: 4.96"**

**Height: 0.94"**

**Cable Length (downlight half): 6.30"**


**Weight: 0.86 lbs**

**Junction Box Length: 3.54"**

**Junction Box Width: 4.17"**

**Junction Box Height: 1.30"**

**Combined Cable Length: 11.81"**



**CUT OUT: Ø 6.25"**

#### **8" DIMENSIONS:**

**Outside Diameter: 9"**


**Inside Diameter: 7"**

**Height: 0.94"**

**Cable Length (downlight half): 6.5"**

**Weight: 1.25 lbs**

**Junction Box Length: 3.5"**  
**Junction Box Width: 4"**  
**Junction Box Height: 1.5"**  
**Combined Cable Length: 14"**



**CUT OUT: Ø 8.25"**

## WARNINGS

- Only use this LED downlight with the dimmers listed in the compatibility list. Using this downlight with incompatible dimmers may cause performance issues including humming, buzzing, flickering, and poor dimming performance.
- Cutout size requirements: 4"–4.25"; 6"–6.25"; 8"–8.25"



RoHS  
Compliant



JA8



## Documents / Resources



[PLT SOLUTIONS PLT-12399 Selectable Ultra Thin LED Downlight Fixture](#) [pdf] User Manual  
 PLT-12399, PLT-12404, PLT-12405, PLT-12406, PLT-12399 Selectable Ultra Thin LED Downlight Fixture, Selectable Ultra Thin LED Downlight Fixture, Ultra Thin LED Downlight Fixture, Thin LED Downlight Fixture, LED Downlight Fixture, Downlight Fixture, Fixture

## References

-  [PLT Solutions](#)

Manuals+.