



## plus opto FUT Series RF LED Controller User Guide

[Home](#) » [plus opto](#) » plus opto FUT Series RF LED Controller User Guide 

### plus opto FUT Series RF LED Controller User Guide



The Mi-Light, Mi-Boxer series RF LED controllers comprises of 5 types, compatible with hand-held remotes and wall mount Touch Panel controllers. Utilising advanced RF 2.4GHz wireless with high output signal to achieve long transmission distances and reduce interference by obstacles.

#### Contents

- 1 FUT-036 LED Wireless Receiver/Driver Dimming
- 2 FUT-035 LED Wireless Receiver/Driver CT Control
- 3 FUT-043 LED Wireless Receiver/Driver RGB
- 4 FUT-044 LED Wireless Receiver/Driver RGBW
- 5 FUT-045 LED Wireless Receiver/Driver RGB+CT
- 6 Compatible with Hand-held LED controllers and Touch Panel Wall plates
- 7 WL-BOX1 Gateway RF to WiFi
- 8 Voice control from 3rd party voice control and smartphone Apps
- 9 Documents / Resources
  - 9.1 References
- 10 Related Posts

### FUT-036 LED Wireless Receiver/Driver Dimming



Wireless RF 2.4GHz Receiver Driver  
 Low Voltage 12-24VDC  
 Single channel Dimming  
 1-Channel 12A/channel  
 Signal auto-transmitting  
 Auto sync between controllers  
 Transmission distance up to 30 metres  
 Compatible with hand-held remotes and wall touch panel controllers

### **FUT-035 LED Wireless Receiver/Driver CT Control**



Wireless RF 2.4GHz Receiver Driver  
 Low Voltage 12-24VDC  
 CT (Colour Temperature)  
 2-Channel 6A/channel  
 Signal auto-transmitting  
 Auto sync between controllers  
 Transmission distance up to 30 metres  
 Compatible with hand-held remotes and wall touch panel controllers

### **FUT-043 LED Wireless Receiver/Driver RGB**



Wireless RF 2.4GHz Receiver Driver  
 Low Voltage 12-24VDC  
 RGB  
 3-Channel 6A/channel  
 Signal auto-transmitting  
 Auto sync between controllers

Transmission distance up to 30 metres  
Compatible with hand-held remotes and wall touch panel controllers

### **FUT-044 LED Wireless Receiver/Driver RGBW**



Wireless RF 2.4GHz Receiver Driver  
Low Voltage 12-24VDC  
RGBW  
4-Channel 6A/channel  
Signal auto-transmitting  
Auto sync between controllers  
Transmission distance up to 30 metres  
Compatible with hand-held remotes and wall touch panel controllers

### **FUT-045 LED Wireless Receiver/Driver RGB+CT**



Wireless RF 2.4GHz Receiver Driver  
Low Voltage 12-24VDC  
RGB+CT  
5-Channel 6A/channel  
Signal auto-transmitting  
Auto sync between controllers  
Transmission distance up to 30 metres  
Compatible with hand-held remotes and wall touch panel controllers

**Compatible with Hand-held LED controllers and Touch Panel Wall plates**



## WL-BOX1 Gateway RF to WiFi



Compatible with Mi-Light RF 2.4GHz FUT series RF LED controllers

Input: DC5V/500mA (Micro USB)

Communication Mode: WiFi-IEEE 802.11b/g/n

Transmitting power: 6dBm

Supports 3rd party Apps

Voice control from 3rd party voice control and smartphone Apps



We offer an extensive range of LED driver power supplies compatible with the FUT series.  
 For a wide range of LED strip products please visit our web site at [www.plusopto.co.uk/flexistrip.html](http://www.plusopto.co.uk/flexistrip.html)

Specifications may be subject to change without notice.

T +44 (0) 1942 671122 E [sales@plusopto.co.uk](mailto:sales@plusopto.co.uk) W [www.plusopto.co.uk](http://www.plusopto.co.uk)  
 B13 Derwent Court William Way Moss Industrial Estate Leigh Lancashire WN7 3PT



### Documents / Resources

	<p><a href="#">plus opto FUT Series RF LED Controller</a> [pdf] User Guide          FUT Series RF LED Controller, FUT Series, RF LED Controller, LED Controller, Controller</p>
--	---

### References

- [Flexible LED Strip](#)