



polarpro Helix MagLock VND-25 Filter System VND Kit User Guide

[Home](#) » [polarpro](#) » polarpro Helix MagLock VND-25 Filter System VND Kit User Guide 

Contents

- 1 polarpro Helix MagLock VND-25 Filter System VND Kit
- 2 Product Information
- 3 HELIX FILTERS & COMPONENTS
- 4 What's Included
- 5 HELIX FILTERS & COMPONENTS
- 6 Base Plates
- 7 INSTALLATION
- 8 REMOVAL
- 9 Filters
- 10 INSTALLATION
- 11 REMOVAL
- 12 More Info
- 13 Documents / Resources
- 14 Related Posts



polarpro Helix MagLock VND-25 Filter System VND Kit



Product Information

What's Included

Available Kits / Filters / Components.

HELIX FILTERS & COMPONENTS

VND 2-5 Kit

VND 2-5 Filter | 77mm Base Plate | 82mm Base Plate | Defender Caps (Front & Rear) Base Plate Defender Cap

VND 2-5 Filter

VND 2-5 Filter | Defender Caps (Front & Rear)

VND 6-9 Filter

VND 6-9 Filter | Defender Caps (Front & Rear)

VND 2-5 Mist Filter

VND 2-5 Mist Filter | Defender Caps (Front & Rear)

VND 6-9 Mist Filter

VND 6-9 Mist Filter | Defender Caps (Front & Rear)

Mist Filter

Mist Filter | Defender Caps (Front & Rear)

Mist Heavy Filter

Mist Heavy Filter | Defender Caps (Front & Rear)

What's Included

Available Kits / Filters / Components.

HELIX FILTERS & COMPONENTS

Blue Morphic Filter

Blue Morphic Filter | Defender Caps (Front & Rear)

GoldMorphic Filter

GoldMorphic Filter I Defender Caps (Front & Rear)

Base Plates (All Sizes)

Base Plate I Base Plate Defender Cap

Base Plates

Installing the Helix Base Plates



INSTALLATION

- **Step 1**

Install the correct size Base Plate on your lens by threading on until secure.

- **Step 2**

Install the Base Plate Defender Cap on your Base Plate to keep your lens protected when no filter is installed by aligning the white lines on the push tabs with the tan lines on the Base Plate.

- **Step 3**

Once aligned, the Defender Cap will magnetize and snap to the Base Plate. Once seated, rotate the Defender Cap clockwise until it locks into place.

REMOVAL

Step 1

To remove the Defender Cap, simply squeeze the tabs and rotate counter-clockwise until the push tabs line up with the tan lines on the Base Plate. Once aligned, continue to depress the tabs and pull to remove.

Filters

How to use Helix filters.



INSTALLATION

- **Step 1**

First, remove the Rear Defender Cap from the Filter by squeezing the tan Filter push tabs and rotating counter-clockwise until the push tabs line up with the white marks on the Rear Defender Cap. Once aligned, continue to depress the tabs and pull to remove.

- **Step 2**

Simply align the tan Filter push tabs with the tan lines on the Base Plate.

- **Step 3**

Once aligned, the Filter will magnetize and snap to the Base Plate. Once seated, rotate the filter clockwise until it locks into place. Follow the same steps above to remove the Front Defender Cap and get shooting!

REMOVAL

Step 1

To remove the Filter from the Base Plate, simply squeeze the tan push tabs and rotate counter-clockwise until the tabs line up with the tan lines on the Base Plate. Once aligned, continue to depress the tabs and pull Filter to remove.

More Info


Questions and support.

QUESTIONS?

Reach out any time via live-chat on our website, or shoot us an email. We're happy to help!

polarpro.com support@polarpro.com 949.220.9395

Documents / Resources



[polarpro Helix MagLock VND-25 Filter System VND Kit](#) [pdf] User Guide
Helix MagLock VND-25, Helix MagLock VND-25 Filter System VND Kit, Filter System VND Kit, VND Kit

