



Pool Patch Pool Deck Paint Coating User Manual

[Home](#) » [Pool Patch](#) » **Pool Patch Pool Deck Paint Coating User Manual**



Contents

- [1 Pool Patch Pool Deck Paint Coating](#)
- [2 Specifications](#)
- [3 DIRECTIONS FOR USE](#)
- [4 FAQs](#)
- [5 Documents / Resources](#)
 - [5.1 References](#)



Pool Patch Pool Deck Paint Coating



Specifications

| STEP | Instructions |
|------|---|
| 1 | Deck surface must be free of all grease, oil, dirt, dust, efflorescence and foreign matter. Clean the surface with a high-pressure nozzle or pressure washer and use a quality cleanser like TSP, or Simple Green, and let the deck dry out for the day. |
| 2 | Fix any damaged areas, if necessary, using Pool Patch Deck Patch. Proceed when the patch is dry. |
| 3 | If you have the old-style kool decking material or natural concrete (that was never painted and turns dark when it gets wet), apply Pool Patch Deck Bonder with a 1/2" roller cover. BUT, if you already have an acrylic deck system instead, skip Step #3. Do NOT apply the Pool Patch Deck Bonder. Before proceeding, the DECK temperature should be between 60-100°F with no chance of rain. |
| 4 | If using multiple pails of Pool Deck Coating Paint, mix all pails in a larger pail and mix thoroughly to reduce color variances. Do Not thin product with water. |
| 5 | Can be applied with airless sprayer or paint roller. Paint roller is recommended. Using a 3/4" roller cover, apply two coats, letting the first coat dry completely before applying the second coat. Spread rate is approximately 200-250 per 2 gallon pail. Coverage may vary depending on surface conditions and application techniques. Do not walk on the deck or expose to water for 48 hours. Do not place heavy items like furniture on the deck for one week. Cleanup using soap and water. |

DIRECTIONS FOR USE



1. The deck surface must be free of all grease, oil, dirt, dust, efflorescence and foreign matter. Clean the surface with a high-pressure nozzle or pressure washer and use a quality cleanser like TSP, or Simple Green, and let the deck dry out for the day.



2. Fix any damaged areas, if necessary, using the Pool Patch Deck Patch. Proceed when the patch is dry.



3. If you have the old-style kool decking material or natural concrete (that was never painted and turns dark when it gets wet), apply Pool Patch Deck Bonder with a $\frac{1}{2}$ " roller cover. BUT, if you already have an acrylic deck system instead, skip Step #3. Do NOT apply the Pool Patch Deck Bonder. Before proceeding, the DECK temperature should be between 60-100°F with no chance of rain.



4. If using multiple pails of Pool Deck Coating Paint, mix all pails into a larger pail and mix thoroughly to reduce colour variances. Do Not thin the product with water.



5. Can be applied with an airless sprayer or paint roller. A paint roller is recommended. Using a $\frac{3}{4}$ " roller cover, apply two coats, letting the first coat dry completely before applying the second coat. The spread rate is approximately 200-250 per 2 gallon pail. Coverage may vary depending on surface conditions and applicator techniques. Do not walk on the deck or be exposed to water for 48 hours. Do not place heavy items like furniture on the deck for one week. Cleanup using soap and water.

FAQs

Can I use a sprayer to apply the Pool Deck Coating Paint?

Yes, the product can be applied with an airless sprayer or a paint roller, though a paint roller is recommended.

Do I need to apply Pool Patch Deck Bonder on my deck?

If you have old-style kool decking material or natural concrete that was never painted, apply the Pool Patch Deck Bonder. If your deck has an acrylic system, do not apply the bonder.

What should I do if I have multiple pails of paint?

Mix all the pails in a larger one to ensure consistent color. Do not thin the product with water.

How long should I wait before applying the second coat?

Allow the first coat to dry completely before applying the second coat.

What precautions should I take after applying the paint?

Do not walk on the deck or expose it to water for 48 hours. Avoid placing heavy items like furniture on the deck for one week.

Documents / Resources

| | |
|---|--|
|  | <p>Pool Patch Pool Deck Paint Coating [pdf] User Manual Pool Deck Paint Coating, Pool, Deck Paint Coating, Paint Coating, Coating</p> |
|---|--|

References

- [User Manual](#)

[Manuals+](#), [Privacy Policy](#)

This website is an independent publication and is neither affiliated with nor endorsed by any of the trademark owners. The "Bluetooth®" word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. The "Wi-Fi®" word mark and logos are registered trademarks owned by the Wi-Fi Alliance. Any use of these marks on this website does not imply any affiliation with or endorsement.