

Power Dynamics WOLFVISION PD528 Series UHF Wireless Microphone Set Instruction Manual

Home » Power Dynamics » Power Dynamics WOLFVISION PD528 Series UHF Wireless Microphone Set Instruction Manual

Contents

- 1 Power Dynamics WOLFVISION PD528 Series UHF Wireless Microphone Set
- 2 Product Usage Instructions:
- **3 UNPACKING INSTRUCTION**
- **4 RECEIVER OVERVIEW FRONT**
- **5 RECEIVER OVERVIEW REAR**
- 6 Transmitter function:
- 7 FAQs
- 8 Documents / Resources
 - 8.1 References



Power Dynamics WOLFVISION PD528 Series UHF Wireless Microphone Set



Specifications:

• Product Name: PD528 Series UHF Wireless Microphone Set

• Reference Numbers: 179.020; 179.022

Version: V1.1

· Certification: CE Certified

Product Information:

The PD528 Series UHF Wireless Microphone Set is a high-quality audio product designed for professional and amateur use. It features wireless technology for freedom of movement during performances or presentations. The set includes a transmitter, receiver, and microphone for clear and reliable audio transmission.

Product Usage Instructions:

Important Safety Instructions:

- Read the manual thoroughly before using the unit.
- Do not open the housing as it contains voltage-carrying parts.
- · Avoid placing metal objects or liquids into the unit.
- · Avoid heat sources, vibrating surfaces, and covering ventilation holes.
- Do not use cleaning sprays on switches.
- Keep the unit out of reach of children and do not leave it unattended.

Unpacking Instructions:

When unpacking the product, ensure all components are included as per the user manual. Check the power supply label on the back/underside to verify the correct mains voltage before connecting.

Power Supply:

The unit must be connected directly to the mains voltage specified on the label. Do not use dimmers or adjustable power supplies to avoid damage.

Congratulations to the purchase of this Power Dynamics product. Please read this manual thoroughly before using the unit to benefit fully from all features.

Read the manual before using the unit. Follow the instructions in order not to invalidate the warranty.

Take all precautions to avoid fire and/or electrical shock. Repairs must only be carried out by a qualified technician to avoid electrical shock. Keep the manual for future reference.

- Before using the unit, please ask for advice from a specialist. When the unit is switched on for the first time, some smell may occur. This is normal and will disappear after a while.
- The unit contains voltage-carrying parts. Therefore do NOT open the housing.
- Do not place metal objects or pour liquids into the unit This may cause electrical shock and malfunction.
- Do not place the unit near heat sources such as radiators, etc. Do not place the unit on a vibrating surface. Do not cover the ventilation holes.
- The unit is not suitable for continuous use.
- Be careful with the mains lead and do not damage it. A faulty or damaged mains lead can cause electrical shock and malfunction.
- When unplugging the unit from a mains outlet, always pull the plug, never the lead.
- Do not plug or unplug the unit with wet hands.

- If the plug and/or the mains lead are damaged, they need to be replaced by a qualified technician.
- If the unit is damaged to such an extent that internal parts are visible, do NOT plug the unit into a mains outlet, and DO NOT switch the unit on. Contact your dealer.
- To avoid fire and shock hazards, do not expose the unit to rain and moisture.
- All repairs should be carried out by a qualified technician only.
- Connect the unit to an earthed mains outlet (220-240Vac/50Hz) protected by a 10-16A fuse.
- During a thunderstorm or if the unit will not be used for a long period, unplug it from the mains. The rule is to unplug it from the mains when not in use.
- If the unit has not been used for a longer period, condensation may occur. Let the unit reach room temperature before you switch it on.
- Never use the unit in humid rooms or outdoors.
- To prevent accidents in companies, you must follow the applicable guidelines and follow the instructions.
- Do not repeatedly switch the fixture on and off. This shortens the lifetime
- Keep the unit out of the reach of children. Do not leave the unit unattended.
- Do not use cleaning sprays to clean switches. The residues of these sprays cause deposits of dust and grease. In case of malfunction, always seek advice from a specialist.
- Do not force the controls.
- This unit is with a speaker inside which can cause a magnetic field. Keep this unit at least 60cm away from the computer or TV.
- If this product has a built-in lead-acid rechargeable battery: please recharge every 3 months if you are not going to use the product for a long period. Otherwise, the battery may be permanently damaged.
- If the battery is damaged please replace it with the same specifications battery. And dispose of the damaged battery environment-friendly.
- If the unit has fallen, always have it checked by a qualified technician before you switch the unit on again.
- Do not use chemicals to clean the unit. They damage the varnish. Only clean the unit with a dry cloth.
- Keep away from electronic equipment that may cause interference.
- Only use original spares for repairs, otherwise, serious damage and/or dangerous radiation may occur.
- Switch the unit off before unplugging it from the mains and/or other equipment. Unplug all leads and cables before moving the unit.
- Make sure that the main lead cannot be damaged when people walk on it. Check the mains lead before every
 use for damages and faults!
- The mains voltage is 220-240Vac/50Hz. Check if the power outlet matches. If you travel, make sure that the mains voltage of the country is suitable for this unit.
- Keep the original packing material so that you can transport the unit in safe conditions.

This mark attracts the attention of the user to high voltages that are present inside the housing and that are of sufficient magnitude to cause a shock hazard.

This mark attracts the attention of the user to important instructions that are contained in the manual and that he should read and adhere to.

The unit has been certified CE. It is prohibited to make any changes to the unit. They would invalidate the CE certificate and their guarantee!

NOTE: To make sure that the unit will function normally, it must be used in rooms with a temperature between 5°C/41°F and 35°C/95°F.

Electric products must not be put into household waste. Please bring them to a recycling center. Ask your local authorities or your dealer about the way to proceed. The specifications are typical. The actual values can slightly change from one unit to the other. Specifications can be changed without prior notice.

Do not attempt to make any repairs yourself. This would invalidate your warranty. Do not make any changes to the unit. This would also invalidate your warranty. The warranty is not applicable in case of accidents or damages caused by inappropriate use or disrespect of the warnings contained in this manual. Power Dynamics cannot be held responsible for personal injuries caused by disrespect of the safety recommendations and warnings. This is also applicable to all damages in whatever form.

UNPACKING INSTRUCTION

CAUTION! Carefully unpack the box upon receipt. Check the contents to ensure that all parts are present and have been received in good condition. Notify the shipper immediately and retain packaging material if any parts appear damaged from shipping or the package itself shows signs of mishandling. Save the package and all packaging materials. If the product must be returned, the product must be returned in the original factory box and packaging. If the device has been exposed to drastic temperature fluctuation (e.g. after transportation), do not switch it on immediately. The rising condensation water might damage your device. Leave the device switched off until it has reached room temperature.

POWERSUPPLY

The label on the back/underside of the product indicates the mains voltage to which it must be connected. Check that the mains voltage corresponds to this. Any other voltage than the one indicated may cause irreparable damage to the unit. The unit must also be connected directly to the mains voltage and no dimmer or adjustable power supply may be used.

Always connect the device to a protected circuit (circuit breaker or fuse). Make sure the device has an appropriate electrical ground to avoid the risk of electrocution or fire.

RECEIVER OVERVIEW FRONT



1. Power On/Off

Switch to turn the device on/off.

- 2. Shows the frequency, channel, volume, and signal.
- 3. Lock button

Locks the group (1-4 or 5-8).

4. Group button

With this button, you can set the frequency by group.

5. IR sensor

Infrared transmitter for synchronizing frequencies between receiver and handheld transmitters.

6. IR button

Button to select the channel to be synchronized with a handheld transmitter.

Set

Press to switch between frequency- and volume setting modes. Rotate the rotary dial to select the desired values.

8. Rotary dial

Rotate to change the volume- and frequency values.

RECEIVER OVERVIEW REAR



1. Antenna connectors

2. Mix out

Unbalanced microphone output connector (6.3mm jack) for channels 1-8.

3. XLR connector

XLR balanced microphone outputs for connecting to (for example) mixers, power amplifiers, or other audio devices.

4. Power input for 12V adapter

Connector for inserting the supplied power adapter.

5. Transmitter charge

USB connectors for recharging the handheld transmitters.

RECEIVER OPERATION

- Switch on the receiver. The LCD will light up.
- Select the frequency by pressing the SET button. Turn the rotary dial to the desired setting and then press SET to save. By pressing SET twice you can adjust the volume level.
- Pressing the group button allows you to set the desired frequency for the group by rotating the rotary dial.
- When you press the lock button the group (1-4 or 5-8) is locked and no changes can be made in the settings.

RECEIVER DISPLAY

1. Channel

Shows the corresponding channel.

2. Volume

Shows the volume level of the corresponding channel.

3. Lock

Shows frequency lock status of the corresponding channel.

4. Frequency


Indicates the channels' frequency.

5. RF signal

Indicates the RF signal strength.

6. AF signal

Indicates the audio signal strength.



For optimum receiving:

- Position the receiver if something is obstructing a line of sight to the microphones.
- Avoid placing microphones and receivers where metal or other dense materials may be present.
- Remove nearby sources of wireless interference, such as cell phones, two-way radios, computers, media players, Wi-Fi devices, and digital signal processors.
- Make sure that the microphone batteries are fully charged.
- Keep microphones more than two meters (6 feet) from each other.
- Keep the microphones and receiver more than 5 meters (16 feet) apart.

HANDHELD TRANSMITTER


1. On/off

Press to turn the handheld microphone on/off.

2. IR sensor

Infrared sensor for synchronizing frequencies between receiver and transmitter. Rotate the battery cover to open and expose the IR sensor.

Transmitter function:



- Open the battery covers of the microphone. Press the power switch on the microphones. On the receiver: select your transmission channel. Hold the IR sensor of the corresponding microphone close to the
 - IR transmitter of the receiver. Press the IR button of the respective channel shortly to synchronize the microphone.
- When the receiver and the microphone have been synchronized to the same channel, the RFbar graph on the receiver's display will indicate that a radio signal is being received.
 - Note: the more bars are displayed, the better the reception is.
- Reinstall the battery cover onto the microphone again.

BODYPACK TRANSMITTERLCD

1. ay

Shows the frequency, channel, battery status, and signal.

2. IR sensor

Infrared sensor for synchronizing frequencies between receiver and transmitter.

3. Microphone input

3.5mm microphone input jack for connecting lavalier microphone.

4. Antenna

5. LED charge indicator

Shows charging status. Red = charging, blue = full charge.

6. Charge port

5V USB type-C charging port.

7. On/off

Press to turn the bodypack microphone on/off.



Transmitter function:

- Press the power switch on the microphones. On the receiver: select your transmission channel.
 - Hold the IR sensor of the corresponding microphone close to the IR transmitter of the receiver. Press the
 IR button of the respective channel shortly to synchronize the microphone.
- When the receiver and the microphone have been synchronized to the same channel, the RF bar graph on the receiver's display will indicate that a radio signal is being received.
 - Note: the more bars are displayed, the better the reception is.

UHF

No license is required (excluding geographical restrictions)

BE	DK	F	FI	DE
HU	IT	NL	NO	PL
PT	RO	SI	ES	SE
CH	GB			

Belgium (BE), Denmark (DK), France (F), Finland (FI), Germany (DE), Hungary (HU), Italy (IT), Netherlands (NL), Norway (NO), Poland (PL), Portugal (PT), Romania (RO), Slovenia (SI), Spain (ES), Sweden (SE), Switzerland (CH), Great Britain (GB).

The products referred to in this manual conform to the European Community Directives to which they are subject:

European Union

- Tronios B.V., Bedrijvenpark Twente Noord 18, 7602KR Almelo, The Netherlands
- 2014/35/EU
- 2014/30/EU
- 2011/65/EC
- 2014/53/EU



United Kingdom

- Tronios Ltd., 130 Harley Street, London W1G 7JU, United Kingdom
- S.I. 2016:1101
- S.I. 2016:1091
- S.I. 2012:3032
- S.I. 2017:1206



FAQs

Q: Can I repair the unit myself if an issue arises?

A: No, it is recommended to seek advice from a qualified technician for repairs to avoid electrical shock and warranty invalidation.

Q: What should I do if I encounter a malfunction with the unit?

A: Always consult a specialist for advice and repairs in case of any malfunction to ensure proper functioning and safety.

Documents / Resources



Power Dynamics WOLFVISION PD528 Series UHF Wireless Microphone Set [pdf] Instruction Manual

179.020, 179.022, WOLFVISION PD528 Series UHF Wireless Microphone Set, WOLFVISION, PD528 Series, UHF Wireless Microphone Set, Wireless Microphone Set, Set

References

- Samen zijn we open. Samen staan we sterk. Stichting Open
- Samen zijn we open. Samen staan we sterk. Stichting Open
- Sound & Light distributor Tronios.com
- Plesk Obsidian 18.0.66
- Plesk Obsidian 18.0.66
- User Manual

Manuals+, Privacy Policy