

Proaim P-A21-JS Alphabet 21ft Jib Crane Instruction Manual

Contents

- [1 Proaim P-A21-JS Alphabet 21ft Jib Crane](#)
- [2 Product Information](#)
- [3 Product Usage Instructions](#)
- [4 Introduction](#)
- [5 What's In The Box](#)
- [6 Supporting Accessories](#)
- [7 Cables With Length And Quantity](#)
- [8 Storage Bag](#)
- [9 Assembling](#)
- [10 Connecting Jib Arm Sections](#)
- [11 Assembling Cables](#)
- [12 Balancing Chart](#)
- [13 Documents / Resources](#)
 - [13.1 References](#)

Proaim P-A21-JS Alphabet 21ft Jib Crane

Product Information

Specifications

- Product Name: Alphabet 21ft Jib Crane with 100mm Bowl Tripod Stand (P-21-JS)
- Warranty: 1 year from the date of purchase

Introduction

Welcome to Proaim! We are dedicated to providing affordable, quality products and ensuring 100% customer satisfaction. This instruction manual will guide you through the assembly and usage of your Alphabet 21ft Jib Crane with 100mm Bowl Tripod Stand.

What's In The Box

Please inspect the contents of your shipped package to ensure you have received everything listed below:

- Jib Sections
- Jib Stand With Aluminum Spreader
- Supporting Accessories
- Cables With Length And Quantity
- Storage Bag

Product Usage Instructions

Assembling

Spreader Assembly

1. Take out the Spreader and spread it on the floor.
2. Open the legs of the spreader according to your requirement using the provided knob.
3. Mount the Tripod Stand on the spreader and lock it in place with the rubber grips.

Jib Sections Assembly

1. Install the Hub (Section 2 of Jib) into the bowl of your 100mm tripod stand.
2. Tighten the hub with the center locking knob.
3. Loosen the provided knob at the end of section 2 to slide the bars of section 3 into the end of section 2.
4. Tighten both sections together using the provided knobs.

Cable Guide and Support Rod Assembly

1. Attach the cable guide to the cable guide clamp on the 2nd section properly.
2. Loosen the knob ahead of the cable guide clamp to attach the cable guide support rod.
3. Retighten the knob to secure properly.

Cables Assembly

1. Attach one end of the 14.5ft blue cable to the blue hook on the back side of jib (section 3).
2. Attach the other end of the blue cable to the blue hook on the front section of jib (section 1).
3. Align both blue cables to the side of the support rod.
4. Similarly, attach the second blue cable.
5. Attach one end of the 14.3ft red cable to the red hook on the back side of jib (section 3).
6. Align the red cable to the cable guide from the top.
7. Attach the other end of the red cable to the red hook on the front section of jib (section 1).

Adjusting The Wire Tensioner

The wires have a screw-in wire adjustment system to adjust the wire tension and level the jib.

1. Insert the weight rod and weights (not supplied) to both ends and secure with the help of closers.
2. The central fork has a free hole to attach an LCD mount bracket (not included).
3. The camera plate can be tilted upwards and downwards with the help of the provided handle.

FAQ

Q: What is the warranty period for the Alphabet 21ft Jib Crane with 100mm Bowl Tripod Stand?

A: The product comes with a 1-year warranty from the date of purchase.

At Proaim, our goal is to ensure 100% Customer Satisfaction in all that we do.

We back our sales with a 1 year warranty from the date of purchase and work hard to resolve any problems in the unlikely event one should arise.

With our commitment to continuous improvement and your Feedback, building on our reputation of providing affordable, quality products is PRIORITY #1.

Welcome To Proaim

Dear Client,

On behalf of all the people that work so hard to provide you with the most up-to-date, flexible and cost-efficient production gear, we would like to welcome you into the Proaim family.

By purchasing your Proaim Alphabet 21ft Jib Crane with 100mm Bowl Tripod Stand, you have just joined a host of designers, engineers, machinists, assembly, customer service and office staff that take great pride in all that they do. Our mantra of continuous improvement has been the guiding principle of how we conduct our business since day one.

Once you have the opportunity to experience your new Proaim Alphabet 21ft Jib Crane with 100mm Bowl Tripod Stand, we hope you will agree that we craft quality products at a competitive price. Products designed to meet and exceed the standards of today's real production world.

Standards set by our valued clients and standards we strive to maintain.

With Best Wishes,

Proaim Team3

Introduction

Proaim introduces its new Alphabet 21ft Jib Crane with 100mm CST-100 stand, fully loaded with features like fastest tool-less setup capability, high-strength build and enhanced stability. Considering the need of film productions, this travel friendly camera jib crane with unbeatable high-end quality and technicalities offers promising performance and reliability. Either wedding shoot or any indoor sports event it allows every videographer to expand his shooting range. Take a deeper look at Proaim Alphabet 21ft video Jib Crane with 100mm CST-100 stand, and you'll find innovation on every level.

What's In The Box

Please inspect the contents of your shipped package to ensure you have received everything that is listed below

Supporting Accessories

Cables With Length And Quantity

Storage Bag

Assembling

- In case of spreader, Take out the Spreader and spread it on the floor and open the legs (as per your requirement) of the spreader with the help of a provided knob. Now mount the Tripod Stand on the Spreader, and lock it in place with the rubber grips.

Assembling Jib Sections

- Install the Hub (Section 2 of Jib) into a bowl of your 100 mm tripod stand and tighten the hub with center locking knob

Connecting Jib Arm Sections

Section 2 with 3 :

- Loosen the provided knob at the end of section 2 to slide the bars of section 3 into the end of section 2 .
- Then tighten both the sections together using the provided knobs

Assembling Cable Guide And Support Rod

For Attaching Section 2a with 2, 2b with 2a, 2c with 2b & 1 with 2c :

- Attach cable guide to cable guide clamp on 2nd section properly. Loosen the knob, ahead of cable guide clamp to attach the cable guide support rod to it.
- Retighten the knob to secure it properly

Assembling Cables

- Now attach one end of the 14.5ft blue cable to the blue hook on the back side of the jib (section 3) and the other end of the blue cable to the blue hook on the front section of the jib (section 1).
- Similarly, attach the second blue cable and align both the blue cables to the side of the support rod.
- Now attach one end of the 14.3ft red cable to the red hook on back side of the jib (section 3) and align the red cable to the cable guide from the top.
- Then, attach the other end of the red cable to the red hook on the front section of the jib(section 1).

Adjusting The Wire Tensioner

- The wires have a screw-in wire adjustment system to adjust the wire tension to level the jib .
- The jib arm can be locked (tilting) with the help of this knob.
- Insert the weight rod & weights (not supplied) to both ends and secure with the help of closers.
- The central fork has a free hole to attach the LCD mount bracket (not included).
- The camera plate can be tilted upwards & downwards with the help of provided handle.

Balancing Chart

Documents / Resources



[Proaim P-A21-JS Alphabet 21ft Jib Crane](#) [pdf] Instruction Manual
P-A21-JS Alphabet 21ft Jib Crane, P-A21-JS, Alphabet 21ft Jib Crane, 21ft Jib Crane, Jib Crane

References

- [User Manual](#)