



PROJECT SOURCE L-5 Refrigerator Water Filter User Manual

[Home](#) » [PROJECT SOURCE](#) » PROJECT SOURCE L-5 Refrigerator Water Filter User Manual 



Contents

- [1 PROJECT SOURCE L-5 Refrigerator Water Filter User Manual](#)
- [2 TROUBLESHOOTING](#)
- [3 CARE AND MAINTENANCE](#)
- [4 WARRANTY](#)
- [5 SAFETY INFORMATION](#)
- [6 INSTALLATION OVERVIEW](#)
- [7 SPECIFICATIONS](#)
- [8 Documents / Resources](#)
- [9 Related Posts](#)



MODEL/MODELO L-5/L-5-2

PROJECT SOURCE and logo design are trademarks or registered trademarks of LF, LLC. All rights reserved.

Thank you for purchasing this Project Source Refrigerator Water Filter. We've created these easy-to-follow instructions to ensure you have a simple installation process. But, if you need more information than what is provided here, please visit [Lowes.com](https://www.Lowes.com), search the item number and refer to the Guides & Documents tab on the product's page.

If the item is no longer for sale, or if you have any questions or problems, please call our customer service department at 1-866-389-8827, 8 a.m. • 8 p.m., EST, Monday· Sunday. You could also contact us at partsplus@lowes.com or visit www.lowespartsplus.com.

TROUBLESHOOTING

PROBLEM PROBLEMA	POSSIBLE CAUSE CAUSA POSIBLE	CORRECTIVE ACTION ACCION CORRECTIVA
Missing O-Ring Falta una junta tórica	Manufacturer Error Error del fabricante	Call Customer Service for replacement: 866-389-8827 Llame al Departamento de Servicio al Cliente para obtener un reemplazo: 866-389-8827
Leaking Fugas	Improper Installation Instalación inadecuada	Remove and reinstall, ensuring the filter is securely installed within the refrigerator housing. Retire y vuelva a instalar, asegurándose de que el filtro esté instalado de manera segura dentro de la carcasa del refrigerador.
Slow Flow/No Flow Flujo lento/sin flujo	Improper Installation/Trapped Air Inside of the Filter Instalación indebida/aire atrapado en el interior del filtro	Submerge filter without safety cap in a bowl or sink full of water for 45 minutes to 1 hour, reinstall. Sumerja el filtro sin tapa de seguridad en un recipiente o fregadero lleno de agua durante 45 minutos a 1 hora, vuelva a instalar.

CARE AND MAINTENANCE

Replace filter every 6 months or 300 gallons, whichever precedes./Reemplace el filtro cada 6 meses o 1135,62 litros, lo que ocurra antes.

WARRANTY

This replacement filter cartridge is warranted to be free from defects in material and manufacture for one (1) year from the date of purchase. This warranty does not cover any failures resulting from abuse, misuse, alteration, or damage not caused by the manufacturer or failure to follow proper installation and use instructions. If the product fails to satisfy this limited warranty during the described period, the manufacturer will replace or refund the purchase price of the product. This warranty does not cover additional costs such as labor.






SAFETY INFORMATION

WARNING

To reduce the risk of property damage due to water leakage, this filter **MUST** be installed in accordance with the manufacturers specifications and instructions. Installation shall comply with applicable state and local regulations. For cold water applications only. Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system. Systems certified for cyst reduction may be used on disinfected waters that may contain filterable cysts. This filter unit must be replaced every 6 months, at the rated capacity, or sooner if reduced water flow occurs. Failure to follow instructions and operating specifications will void your warranty. Further, manufacturer assumes no responsibility or liability for damages arising out of misuse of the product. Protect from freezing.

INSTALLATION OVERVIEW


<div data-bbox="114 1200 782 1377">1 </div> <div data-bbox="114 1377 782 1803"><p>Pull the cartridge cover down by pressing the sides of the cover for the cover to drop down. Note: If the top shelf in the refrigerator is in the highest position, please remove your top shelf of your refrigerator in order for the cover to drop all the way down.</p></div>	<div data-bbox="810 1200 1129 1377">2 </div> <div data-bbox="810 1377 1129 1803"><p>Pull the water filter down and rotate counter clockwise to remove it. Note: Be sure that the filter is completely downward prior to removing it out of the housing head.</p></div>	<div data-bbox="1152 1200 1474 1377">3 </div> <div data-bbox="1152 1377 1474 1803"><p>Carefully remove the sanitary cap from the top of the new filter.</p></div>
---	--	---

4



With the filter tabs in the horizontal position, insert the new filter into the housing head. Turn filter 1/4 turn clockwise. Push the filter upwards into the housing and close the cartridge cover. **Note:** Please ensure the filter is fully installed as it is required to activate the internal water valve. If the filter isn't properly installed, you may experience a slow flow or a chattering noise. If this occurs, please uninstall and reinstall the filter ensuring the filter is fully installed.

5



Run about 2.5-3 gallons of water from your water dispenser to clear the system and prevent sputtering. **Note:** Initial flow rate may be slower than expected. Full flow rate should be restored within 24-36 hours.


6



Inspect the filter for any noticeable leaks. If leaks are detected, please repeat Step 4.


7

Reset



To reset the filter monitor light, please refer to your refrigerator owner's manual for specific instructions.

8



Locate the included Water Filter Replacement Calendar and follow the instructions on the label.

SPECIFICATIONS

Flow Rate:	.5 gpm (1.89 lpm)
Operating Temperature:	33°-100°F (0.6°-38°C)
Min Operating Pressure:	30 psi (207 kPa)
Max Operating Pressure:	100 psi (689 kPa)
Capacity:	6 months or 300 gallons (1,136 liters)



This L-5/L-5-2 is Tested and Certified by NSF International against NSF/ANSI Standard 42 and 53 for the reduction of chlorine taste and odor, Tetrachlorethylene, Endrin, Carbon Tetrachloride, Trichlorobenzene, p-Dichlorobenzene. Refer to performance data sheet for complete list of claims.




This L-5/L-5-2 is Certified by IAPM O R&T against NSF/ANSI Standard 42, 53, 372, 401, P473 and CSA 8483.1 for the reduction of Chlorine taste and odor, Lead, Cyst, VOC's, Mercury, Asbestos, Phannaceuticals (such as Naproxen, Ibuprofen and Phenytoin), BPA, PFOA/PFOS. Refer to Perfonnance Data Sheet for complete list of claims.

The compounds under NSF/ANSI 401 have been deemed as 'incidental contaminants / emerging compounds'.

Read More About This Manual & Download PDF:

Documents / Resources

	<p>PROJECT SOURCE L-5 Refrigerator Water Filter [pdf] User Manual L-5, L-5-2, L-5 Refrigerator Water Filter, L-5, Refrigerator Water Filter, Water Filter, Filter</p>
---	---