

QwikProducts QT6100 OEM Constant Torque ECM w PSC Board Instructions

Home » QwikProducts » QwikProducts QT6100 OEM Constant Torque ECM w PSC Board Instructions





HVAC/R Performance Products Indoor Air Quality Products Training / Certifications QwikSwap® X1 & X3 Troubleshooting Steps

Contents

- 1 QT6100 OEM Constant Torque ECM w PSC **Board**
- 2 Documents / Resources
 - 2.1 References
- **3 Related Posts**

QT6100 OEM Constant Torque ECM w PSC Board

PROBLEM	SOLUTION		
I don't know if I need to us e the R terminal on the Q wikSwap Board (X1 or X3).	Use of the R terminal on the QwikSwap (X1 or X3) in most installations is optional (some installations will require the use of the R terminal if the air handler fan control board outputs a DC voltage or if there is a resistor in the control wiring). Connecting the R terminal activates a delay that keeps the fan running for 3 minutes after the thermostat tells it to shut off. If you want this delay connect the R terminal to the 24 VAC terminal on the low voltage transformer (typically the red wire that also goes to the thermost at R terminal) and remove the jumper next to the R terminal.		
I connected the R terminal but now the Qwik Swap (X1 or X3) will not t urn off.	Connecting the R terminal activates the 3 minute delay after break feature. Sometimes the blower control board in the air handler has an additional delay that adds to the 3 minute delay of the QwikSwap. If you wish to disable the 3 minute delay on the QwikSwap, install the jumper on the two pin header next to the R terminal.		
I have read all of the troub leshooting steps but I still cannot solve the problem I am having. C L G N I L G	Using insulated test leads carefully measure and record the voltage across the ter minals listed below (measure for both AC and DC) and call: Mainstream Engineering for technical support (321-631-3550).		
	Measure Across These Terminals	Normal Measured Voltage "Expected" Voltage	
	C and 1 (if there is a wire on 1)		20-30 AC or DC
	C and 2 (if there is a wire on 2)		20-30 AC or DC
	C and 3 (if there is a wire on 3)		20-30 AC or DC
	C and 4 (if there is a wire on 4)		20-30 AC or DC
	C and 5 (if there is a wire on 5)		20-30 AC or DC
	C and R (if there is a wire on R)		20-30 AC
	L and N		120-240 VAC
	Speed and COM		120-240 VAC





QwikProducts® and QwikSwap® are registered trademarks of Mainstream Engineering Corporation, Rockledge, Florida 32955,

(321) 631-3550

 © 2022 Mainstream Engineering Corporation
 All QwikProducts® are made in the USA. Patents Pending Mainstream Engineering Corporation 1-800-866-3550

> <u>www.qwik.com</u> 5010162_REV-B / 1201820002

Documents / Resources



QwikProducts QT6100 OEM Constant Torque ECM w PSC Board [pdf] Instructions QT6100 OEM Constant Torque ECM w PSC Board, QT6100, OEM Constant Torque ECM w PSC Board, Constant Torque ECM w PSC Board, Torque ECM w PSC Board, ECM w PSC Board, PSC Board, Board

References

• @ Home - Qwik.com

Manuals+,