



RACKMOUNTH RM-CI-T3 CISRACK Instruction Manual

[Home](#) » [RACKMOUNTH](#) » RACKMOUNTH RM-CI-T3 CISRACK Instruction Manual 

Contents

- [1 RACKMOUNTH RM-CI-T3 CISRACK](#)
- [2 Product Information](#)
- [3 Dimensions](#)
- [4 Product Usage Instructions](#)
- [5 Documents / Resources](#)
 - [5.1 References](#)



RACKMOUNTH RM-CI-T3 CISRACK



Product Information

- **Product Line:** CISRACK
- **Type:** RM-CI-T3
- **Supported Models:** MERAKI GO GS110-8, MERAKI GO GS110-8P, MS120-8, MS120-8LP

Dimensions

- **1U**
- **Color:** Metallic Blue
- **Packing Dimensions:** 80 x 520 x 270 mm / 3.14 x 20.47 x 10.63 in
- **Product Dimensions:** 44 x 482 x 217 mm (height x width x depth) / 1.73 x 18.98 x 8.54 in

Mounting Instructions:

1. Fully slide the mounting slides outwards so the holes line up with the upright threaded pins.
2. Place your Cisco appliance on the rackmount kit.
3. Fix the nuts on the threaded pins with the provided nut tool.
4. Place the power supply on the rack and tie it down with 2 zip ties.
5. Tie the excess length of the power cable down with the 3rd zip tie.
6. Place your Cisco in your 19 inch rack.

Please ensure proper ventilation according to the network appliance manufacturer guidelines.

Package Contents

- **CisRack** (Qty 1)
- **Zip ties** (Qty 3)
- **Nut** (Qty 2)
- **Nut tool** (Qty 1)

Other Information

- Rackmount.IT rack mount kits are RoHS compliant, developed & manufactured in the Netherlands and made of first quality parts.
- In case of problems please contact your reseller or sales@rackmount.it.
- Consider the environment, recycle where applicable.
- Revision 4 – 24-11-2020

Product Usage Instructions

1. Ensure proper ventilation according to the network appliance manufacturer guidelines before mounting the CISRACK.
2. Slide the mounting slides outwards so that the holes line up with the upright threaded pins.
3. Place your Cisco appliance on the rackmount kit
4. Fix the nuts on the threaded pins using the provided nut tool.
5. Place the power supply on the rack and tie it down with 2 zip ties.
6. Tie the excess length of the power cable down with the 3rd zip tie.
7. Place your Cisco in your 19 inch rack.

Consider the environment, recycle where applicable.

- Rackmount.IT rack mount kits are RoHS
- compliant, developed & manufactured in the
- Netherlands and made of first quality parts.

In case of problems please contact your reseller or sales@rackmount.it

EMEA Office

- **ADDREESS:** Nonnenveld 27 4811 HN Breda The Netherlands
- **T** +31 76 200 37 40
- **E** sales@rackmount.it
- WWW.RACKMOUNT.IT

US Office

- **ADDREESS:** 9201 Metric Blvd – Unit A Austin – TX 78758 United States
- **T** +1 512 521 03 33
- **E** sales-us@rackmount.it

Documents / Resources

	RACKMOUNT RM-CI-T3 CISRACK [pdf] Instruction Manual RM-CI-T3, MERAKI GO GS110-8, MERAKI GO GS110-8P, MS120-8, MS120-8LP, RM-CI-T3 CISRACK, CISRACK
--	--

References

-  Home - Rackmount.IT

Manuals+.