

RACKSBRAX RB-REF-014D Howling Moon User Guide

Home » RACKSBRAX » RACKSBRAX RB-REF-014D Howling Moon User Guide 🖺



Contents

- 1 RACKSBRAX RB-REF-014D Howling Moon
- **2 Product Information**
- **3 Wall Mounts Optional**
- **4 Product Usage Instructions**
- **5 HOWLING MOON**
- **6 BRACKETS OPTIONAL**
- **7 WALL MOUNTS OPTIONAL**
- **8 BRACKETS OPTIONAL**
- 9 Documents / Resources



RACKSBRAX RB-REF-014D Howling Moon



Product Information

- Product Model: Howling Moon RB-REF-014D (Revision 0, December 2022) Hitches Required Minimum for Fast On, Fast Off!
- Mounting Points: 2
- Compatible with Hitch Models: 8162*, 8180* Will also work with the triple versions of each if you already have/are more comfortable with 3 mounting points on your vehicle.
- Note: HD hitches fit to 2 of the 3 available mounting tracks.
- · Brackets Optional
 - Mounting Points for Bar-Style: 2
 - Mounting Points for Platform-Style (with no perimeter lip): 2 Will also work with the triple versions of each if you already have/are more comfortable with 3 mounting points on your vehicle.

Wall Mounts Optional

Benefits:

- Allows you to remove your roof rack accessory from your vehicle so that it can be fixed to a wall when not in
 use.
- · Secured Location: Locked garages, workshop walls
- Unsecured Location: Open carports, public/shared garage area

Product Usage Instructions

To install the Howling Moon RB-REF-014D awning/accessory, follow these steps:

- 1. Ensure you have the required hitches for fast on and fast off installation. The minimum number of mounting points required is 2.
- 2. If you prefer or already have 3 mounting points on your vehicle, the awning/accessory can also work with the triple versions of the hitch models.
- 3. If using HD hitches, make sure they are fitted to 2 of the 3 available mounting tracks.
- 4. If using bar-style or platform-style mounting, brackets are optional. For bar-style mounting, you will need 2 brackets. For platform-style mounting with no perimeter lip, you will also need 2brackets.
- 5. If you prefer or already have 3 mounting points on your vehicle, the awning/accessory can also work with the triple versions of the hitch models.
- 6. If you want to fix the awning/accessory to a wall when not in use, wall mounts are optional. This allows you to remove the roofrack accessory from your vehicle and secure it to a wall.
- Choose a secured location such as locked garages or workshop walls if you want to ensure maximum security for your awning/accessory.
- 8. If a secured location is not available, you can use open carports or public/shared garage areas as an unsecured location.

HOWLING MOON

HOWLING MOON® ALU AWN 2.1m, 2.5m

HITCHES: REQUIRED MINIMUM FOR FAST ON, FAST OFF!

- MOUNTING POINTS 2
- HITCHES NEEDED 8159 HD Hitch Standard
- ALSO WORKS WITH 8162*, 8180*
 - WILL ALSO WORK WITH THE TRIPLE VERSIONS OF EACH IF YOU ALREADY HAVE/ARE MORE COMFORTABLE WITH 3 MOUNTING POINTS ON YOUR VEHICLE
 - NOTE: HD HITCHES FIT TO 2 OF THE 3 AVAILABLE MOUNTING TRACKS.

BRACKETS OPTIONAL

• MOUNTING POINTS 2

BRACKETS NEEDED

- FOR BAR OR PLATFORM-STYLE (WITH NO PERIMETER LIP)
 - 8300 HD L50 L Brackets (DOUBLE)*; OR
- FOR BAR-STYLE
 - 8304 HD Adjustable Brackets Short (DOUBLE)*; OR
- FOR PLATFORM-STYLE (WITH NO PERIMETER LIP)
 - WILL ALSO WORK WITH THE TRIPLE VERSIONS OF EACH IF YOU ALREADY HAVE/ARE MORE COMFORTABLE WITH 3 MOUNTING POINTS ON YOUR VEHICLE.

WALL MOUNTS OPTIONAL

- BENEFITS
 - ALLOWS YOU TO REMOVE YOUR ROOF RACK ACCESSORY FROM YOUR VEHICLE SO THAT IT CAN BE FIXED TO A WALL WHEN NOT USING IT.
- SECURED LOCATION
 - 8160 HD Wall Mounts+
 - ✓ LOCKED GARAGES
 - ✓ WORKSHOP WALLS
- UNSECURED LOCATION
 - 8161 HD Lockable Wall Mounts+

NOTE: You cannot use Wall Mounts to mount anything to the vehicle – these were intended for static wall use ONLY.

- HOWLING MOON® HALF MOON 1.4m
 - NOT COMPATIBLE
- HOWLING MOON® LEISURE AWN 2.5m

- NOT COMPATIBLE
- HOWLING MOON® SAFARI AWN 2.5m
 - NOT COMPATIBLE
- HOWLING MOON® SWALLOW AWN 1.4m
 - NOT COMPATIBLE

HOWLING MOON® 180 SWING AWN 2m

HITCHES REQUIRED MINIMUM FOR FAST ON, FAST OFF!

- MOUNTING POINTS 2
- HITCHES NEEDED 9000 XD Hitch (DOUBLE)*
 - WILL ALSO WORK WITH THE TRIPLE VERSIONS OF EACH IF YOU ALREADY HAVE/ARE MORE COMFORTABLE WITH 3 MOUNTING POINTS ON YOUR VEHICLE.

BRACKETS OPTIONAL

• MOUNTING POINTS 2

BRACKETS NEEDED

- ✓ FOR BAR-STYLE
 - 9100 XD Adjustable Brackets Short (DOUBLE)*; OR
- ✓ FOR PLATFORM-STYLE (WITH NO PERIMETER LIP)
 - 9102 XD Adjustable Brackets Long (DOUBLE)*. WILL ALSO WORK WITH THE TRIPLE VERSIONS
 OF EACH IF YOU ALREADY HAVE/ARE MORE COMFORTABLE WITH 3 MOUNTING POINTS ON
 YOUR VEHICLE.

WALL MOUNTS OPTIONAL

• BENEFITS

 ALLOWS YOU TO REMOVE YOUR ROOF RACK ACCESSORY FROM YOUR VEHICLE SO THAT IT CAN BE FIXED TO A WALL WHEN NOT USING IT.

• SECURED LOCATION

- 9010 XD Wall Mounts

 - ✓ WORKSHOP WALLS

• UNSECURED LOCATION

- 9011 XD Lockable Wall Mounts+

NOTE: You cannot use Wall Mounts to mount anything to the vehicle – these were intended for static wall use ONLY.

HOWLING MOON® 180 SWING AWN 2.5m

HITCHES: REQUIRED MINIMUM FOR FAST ON, FAST OFF!

- MOUNTING POINTS 3
- HITCHES NEEDED 9001 XD Hitch (TRIPLE)

BRACKETS OPTIONAL

- MOUNTING POINTS 3
- BRACKETS NEEDED
 - ∘ ✓ FOR BAR-STYLE
 - 9101 XD Adjustable Brackets Short (TRIPLE); OR
 - ✓ FOR PLATFORM-STYLE (WITH NO PERIMETER LIP)
 - 9103 XD Adjustable Brackets Long (TRIPLE).

WALL MOUNTS OPTIONAL

BENEFITS

 ALLOWS YOU TO REMOVE YOUR ROOF RACK ACCESSORY FROM YOUR VEHICLE SO THAT IT CAN BE FIXED TO A WALL WHEN NOT USING IT.

SECURED LOCATION

- 9010 XD Wall Mounts+

 - ✓ WORKSHOP WALLS

UNSECURED LOCATION

- 9011 XD Lockable Wall Mounts+

NOTE: You cannot use Wall Mounts to mount anything to the vehicle – these were intended for static wall use ONLY.

HOWLING MOON® 270 SWING AWN 4 panel (2m, 2.5m)

HITCHES: REQUIRED MINIMUM FOR FAST ON, FAST OFF!

• MOUNTING POINTS 2

• HITCHES NEEDED

- 9000 XD Hitch (DOUBLE)
- WILL ALSO WORK WITH THE TRIPLE VERSIONS OF EACH IF YOU ALREADY HAVE/ARE MORE COMFORTABLE WITH 3 MOUNTING POINTS ON YOUR VEHICLE.

BRACKETS OPTIONAL

- MOUNTING POINTS 2
- BRACKETS NEEDED
 - ∘ ✓ FOR BAR-STYLE
 - 9100 XD Adjustable Brackets Short (DOUBLE)*; OR
 - ✓ FOR PLATFORM-STYLE (WITH NO PERIMETER LIP)
 - 9102 XD Adjustable Brackets Long (DOUBLE)*.
 - WILL ALSO WORK WITH THE TRIPLE VERSIONS OF EACH IF YOU ALREADY HAVE/ARE
 MORE COMFORTABLE WITH 3 MOUNTING POINTS ON YOUR VEHICLE.

WALL MOUNTS OPTIONAL

BENEFITS

 ALLOWS YOU TO REMOVE YOUR ROOF RACK ACCESSORY FROM YOUR VEHICLE SO THAT IT CAN BE FIXED TO A WALL WHEN NOT USING IT.

• SECURED LOCATION

- 9010 XD Wall Mounts+

 - ✓ WORKSHOP WALLS

UNSECURED LOCATION

- 9011 XD Lockable Wall Mounts+

NOTE: You cannot use Wall Mounts to mount anything to the vehicle – these were intended for static wall use ONLY.

HOWLING MOON® 270 SWING AWN 6 panel (2m, 2.5m)

HITCHES: REQUIRED MINIMUM FOR FAST ON, FAST OFF!

- MOUNTING POINTS 3
- HITCHES NEEDED 9001 XD Hitch (TRIPLE)

BRACKETS OPTIONAL

- MOUNTING POINTS 3
- BRACKETS NEEDED
 - - 9101 XD Adjustable Brackets Short (TRIPLE); OR
 - ✓ FOR PLATFORM-STYLE (WITH NO PERIMETER LIP)
 - 9103 XD Adjustable Brackets Long (TRIPLE).

WALL MOUNTS OPTIONAL

BENEFITS

ALLOWS YOU TO REMOVE YOUR ROOF RACK ACCESSORY FROM YOUR VEHICLE SO THAT IT
 CAN BE FIXED TO A WALL WHEN NOT USING IT.

• SECURED LOCATION

- 9010 XD Wall Mounts+

 - ✓ WORKSHOP WALLS

• UNSECURED LOCATION

- 9011 XD Lockable Wall Mounts+

NOTE: You cannot use Wall Mounts to mount anything to the vehicle – these were intended for static wall use ONLY.

RB-REF-014D – Howling Moon Rev 0 (December 2022) CLICK OR TAP ON AN AWNING/ACCESSORY BELOW TO TAKE YOU TO THE PAGE TO FIND OUT WHAT YOU NEED

Documents / Resources



RACKSBRAX RB-REF-014D Howling Moon [pdf] User Guide RB-REF-014D Howling Moon, RB-REF-014D, Howling Moon, Moon

Manuals+,