



Remote Tech RT-HK1608 Smart Key User Manual

[Home](#) » [Remote Tech](#) » Remote Tech RT-HK1608 Smart Key User Manual 

Contents

- [1 Remote Tech RT-HK1608 Smart Key](#)
- [2 Specifications](#)
- [3 Product Usage Instructions](#)
- [4 FCC Compliance Statement](#)
- [5 Documents / Resources](#)
 - [5.1 References](#)



Remote Tech RT-HK1608 Smart Key



Specifications

- FCC ID: 2AOKM-HK25
- IC: 24223-HK25
- MODEL: RT-HK1608

Product Usage Instructions

LOCK Button

Pressing the LOCK button will lock all the doors of the vehicle.

UNLOCK Button

Pressing the UNLOCK button will unlock the driver's door. Pressing the button again within 5 seconds will unlock the other doors.

Liftgate Unlock Hold Button

If your vehicle is equipped with a power liftgate, press and hold the Liftgate Unlock Hold Button to open the liftgate.

PANIC HOLD Button

Pressing the PANIC HOLD button will activate the vehicle's alarm system. The horn will start sounding and the hazard lamps will flash. To stop the alarm, press any button on the electronic key.

FCC Compliance Statement


This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation. Changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

IC WARNING

This device contains licence-exempt transmitter(s)/receiver(s) that comply with Innovation, Science and Economic Development Canada's licence-exempt RSS(s). Operation is subject to the following two conditions:

1. This device may not cause interference.
2. This device must accept any interference, including interference that may cause undesired operation of the device.

Documents / Resources

	Remote Tech RT-HK1608 Smart Key [pdf] User Manual RT-HK1608 Smart Key, RT-HK1608, Smart Key, Key
---	---

References

- [User Manual](#)