



## RemotePro Garage Remote Programming M802 Instructions

[Home](#) » [RemotePro](#) » RemotePro Garage Remote Programming M802 Instructions 

### RemotePro Garage Remote Programming M802 Instructions



#### Contents

- [1 M802 Instructions](#)
- [2 Documents / Resources](#)
- [3 Related Posts](#)

### M802 Instructions

1. Unscrew the small screw at the back of the new remote and remove the small tab from the battery.
2. Open your original remote (if you do not have one, please remove the tab at the back of your motor which is labelled 'code dip switches' or remove the light cover of the motor to find the switches.

- 3. Change the switches of the new remote to match either your old remote or your motor.
- 4. Close the remote and test.



**WARNING**

To prevent possible SERIOUS INJURY or DEATH:


- Battery is hazardous: NEVER allow children near batteries.
- If battery is swallowed, immediately notify a doctor.

To reduce risk of fire, explosion or chemical burn:

- Replace ONLY with the same size and type battery
- DO NOT recharge, disassemble, heat above 100° C or incinerate

Battery will cause SEVERE or FATAL injuries in 2 hours or less if swallowed or placed inside any part of the body.

**Documents / Resources**

	<p><a href="#">RemotePro Garage Remote Programming M802</a> [pdf] Instructions RemotePro, Garage, Remote, Programming, M802</p>
---	---