



RemotePro Installing Receiver to MB-T304 Instructions

[Home](#) » [RemotePro](#) » RemotePro Installing Receiver to MB-T304 Instructions 

RemotePro Installing Receiver to MB-T304



Contents

- [1 Installing Receiver to MB-T304](#)
- [2 WARNING](#)
- [3 Documents / Resources](#)
- [4 Related Posts](#)

Installing Receiver to MB-T304

1. **TURN OFF POWER FROM THE POWER POINT**
2. View the diagram below and ensure that it matches with the back of your motor.
3. Loosen each of the three screws, 1, 2, 3 on the back of your motor.
4. Connect the black receiver cable to the 1 screw and ghten.
5. Connect the blue receiver cable to the 2 screw and ghten.
6. Connect the brown receiver cable to the 3 screw and ghten.
7. Turn power back on and ensure the receiver powers up.
8. Your two new remotes have been pre-programmed to the receiver.
Press buon 1 on your new remote to ensure it can operate the door.

Note: Please ensure your motor looks like the image below



Coding new remotes

Please Note: Your original remotes will connue to work

1. Press the black learn buon inside the receiver located next to the LED light unl the LED illuminates.
2. Press and hold any buon on your new remote unl the LED flashes 3 mes.
3. The remote is now coded, please test the remote to ensure it can operate the motor.
4. If you have more than one new remote, please repeat steps 1-3.

WARNING




- To prevent possible SERIOUS INJURY or DEATH:

- Battery is hazardous: NEVER allow children near batteries.
- If battery is swallowed, immediately notify a doctor.
- To reduce risk of fire, explosion or chemical burn:
 - Replace ONLY with the same size and type battery
 - DO NOT recharge, disassemble, heat above 100° C or incinerate
- Battery will cause SEVERE or FATAL injuries in 2 hours or less if swallowed or placed inside any part of the body.

www.remotepro.com.au

Documents / Resources

 <p>Installing Receiver to MB-T304</p> <ol style="list-style-type: none"> 1. Remove the battery cover from the back of the receiver. 2. Insert the battery into the battery compartment. 3. Close the battery cover. 4. Connect the receiver to the antenna. 5. Connect the receiver to the power source. 6. Turn on the receiver. 7. Test the receiver. 8. Turn off the receiver. 9. Remove the receiver from the power source. 10. Remove the receiver from the antenna. 11. Remove the receiver from the battery compartment. 12. Remove the receiver from the back of the receiver. <p>WARNING: Do not touch the battery terminals. Do not short the battery terminals. Do not dispose of the battery in fire.</p>	<p>RemotePro Installing Receiver to MB-T304 [pdf] Instructions</p> <p>RemotePro, Installing, Receiver, to, MB-T304</p>
---	--