

remotepro M802 Garage Remote Programming Instructions

Home » RemotePro » remotepro M802 Garage Remote Programming Instructions



Remote Pro

M802 Garage Remote Programming Instructions



Contents

- 1 Coding Instructions
- **2 WARNING**
- 3 Documents /

Resources

- 3.1 References
- **4 Related Posts**

Coding Instructions

- 1. Open the original working remote (which may be located under the battery cover or you may need to remove the screws at the back of the remote). Please note: If you do not have an original remote you will need to locate the DIP switches on the motor or receiver.
- 2. Open the new remote (may be located under the battery cover or you may need to remove the screws at the back of the remote).
- 3. Change the DIP switches in the new remote, by moving these up or down to match the switches in either your old remote or your motor.
- 4. Close the remotes and test.

WARNING



To prevent possible SERIOUS INJURY or DEATH:

- Battery is hazardous: NEVER allow children near batteries.
- If the battery is swallowed, immediately notify a doctor.

To reduce the risk of fire, explosion, or chemical burn:

- Replace ONLY with the same size and type of battery
- DO NOT recharge, disassemble, heat above 100° C, or incinerate

The battery will cause SEVERE or FATAL injuries in 2 hours or less if swallowed or placed inside any part of the body.



Documents / Resources



<u>remotepro M802 Garage Remote Programming</u> [pdf] Instructions

M802 Garage Remote Programming, Garage Remote Programming, Remote Programming

References

• R Garage Door Remotes | Car Remotes | Free Shipping AU Wide - Remote Pro

