



REOLINK RLK8-410B6-5MP 8CH 5MP Home Security Camera System Instructions

[Home](#) » [reolink](#) » REOLINK RLK8-410B6-5MP 8CH 5MP Home Security Camera System Instructions 

REOLINK RLK8-410B6-5MP 8CH 5MP Home Security Camera System



Contents

- [1 Limited Warranty](#)
- [2 Documents / Resources](#)
 - [2.1 References](#)
- [3 Related Posts](#)

Limited Warranty

RLK8-410B4-NVR-Kit-NVR-Specifications		
	Model	RLN8-410
Hardware	Hardware	V2
Video/Audio Input	IP Video Input	PoE IP camera x 8
	Audio Input	Cameras with built-in mic
	Video Output	VGA, HDMI

Video/Audio Output	Display Resolution	HDMI: 3840×2160, 1920×1080, 1280×1024, 1280×720, 1024×768
		VGA: 1920×1080, 1280×1024, 1280×720, 1024×768
	Audio output	1-channel, RCA
Decoding	Video Format	H.264, H.265
	Live View/Playback Resolution	4096*3072/3840*2160/2560*1920/2560*1440/2048*1536/2304*1296/1080p/720p
	Synchronous Playback	Up to 4 channels
HDD	SATA	1 x SATA interface (1 x 2TB HDD included)
	External HDD	1 eSATA interface for HDD
	Capacity	Up to 12TB (max. 6TB capacity for each HDD)
External Interface	USB Interface	2 x USB 2.0
	Network Interface	1, RJ-45 10/100 Mbps self-adaptive Ethernet interface for LAN/WAN
		8, RJ-45 10/100 Mbps self-adaptive PoE Ethernet interface for IP camera
PoE	Max. Power Per Port	25W
	Supported Standard	IEEE 802.3af/at
Network	Network Protocols	HTTP, TCP/IP, UDP, DHCP, P2P, UPNP, RTSP, SMTP, SSL/TLS, DNS, DDNS, NTP, FTP
	Browsers Supported	Edge, Firefox, Chrome, Safari
	OS Supported	PC: Windows, Mac OS; smartphone: iOS, Android
	Max. User Access	20 users (1 admin account & 19 user accounts); up to 12 simultaneous video streams (10 substreams & 2 mainstreams)
	Power Supply	DC 48V~53V

General	Power Consumption	<10W (without HDD & PoE)
	Working Environment	Temperature: -10°C~+45°C (14°F~113°F); humidity: 10%~90%
	Dimensions	260 x 41 x 230mm
	Weight	1.4kg
Warranty	Limited Warranty	2-year limited warranty. For support, visit https://support.reolink.com/hc/en-us/ .

RLK8-410B4-NVR-Kit-IP-Camera-Specifications		
	Model	B500
Note:	The cameras of the kit cannot work without the NVR.	
Camera	Image Sensor	1/2.7" CMOS Sensor
	Effective Pixels	2560×1920(5.0 Megapixels)
	Lens	f=4.0 mm Fixed, F=2.0
	Angle of View	Horizontal: 80°, Vertical: 58°
	Day/Night Mode	Auto Switchover
	Min. Illumination	0 Lux (With IR Illuminator)
	IR Distance	30 Meters (100ft)(LED: 18pcs/14mil/850nm)
	Backlight Compensation	Support
	Noise Reduction	3D DNR
Video	Compression	H.264
	Resolution	Mainstream: 2560×1920, 2560×1440, 2048×1536, 2304×1296; Substream: 640×480
	Bitrate	Mainstream: 1024Kbps~8192Kbps; Substream: 64Kbps~512Kbps
	Frame Rate	Mainstream@30fps, Substream@7fps

Audio	Interface	Built-in Microphone
Network	Interface	One 10M/100Mbps RJ45
General	Power Supply	DC12V & PoE (IEEE 802.3af 48V Active)
	Power Consumption	<10W
	Working Environment	-10°C~+55°C (14°F~131°F), Humidity: 10%~90%
	Ingress Protection	IP66
	Dimension	Φ67×186 mm
	Weight	350g
Warranty	Limited Warranty	2-year limited warranty. For support, visit https://support.reolink.com/hc/en-us/ .

Documents / Resources

	REOLINK RLK8-410B6-5MP 8CH 5MP Home Security Camera System [pdf] Instructions RLK8-410B6-5MP 8CH 5MP Home Security Camera System, RLK8-410B6-5MP, 8CH 5MP Home Security Camera System, Home Security Camera System, Security Camera System, Camera System
---	---

References

- [🔗 Not Found - Reolink Support](#)
- [🔗 Reolink Support - Official Reolink Help Center](#)
- [User Manual](#)