



# rocstor Y10P028-S1 USB-C 11 in 1 Dual Display Portable Dock User Manual

[Home](#) » [rocstor](#) » rocstor Y10P028-S1 USB-C 11 in 1 Dual Display Portable Dock User Manual 

## Rocstor Y10P028-S1 USB-C 11 in 1 Dual Display Portable Dock



## Contents

- [1 Congratulations](#)
- [2 Features](#)
- [3 Introduction](#)
- [4 Package Contents](#)
- [5 Specification](#)
- [6 Connection Diagram](#)
- [7 Warranty Information](#)
- [8 Safety Information:](#)
- [9 Customer Support](#)
- [10 Documents / Resources](#)
  - [10.1 References](#)
- [11 Related Posts](#)

## Congratulations

Thank you for purchasing this premium Rocstor product. For optimum performance and safety, please read these instructions carefully before connecting, operating or using this product. Please keep this manual for future reference.

## Features

### Upstream:



**Type-C Male X1** Host Computer

- Support DP1.4 Alt mode

### Downstream:



**HDMI X2**

- The HDMI port close to Type-C male supports max 8K/30Hz, another one supports max 4K/60Hz
- Supports Dual 4K/30Hz simultaneously under MST mode
- Supports Dual 4K/60Hz simultaneously under SST mode
- Supports High Dynamic Range(HDR)
- Supports multiple color formats: RGB;YCbCr4:4:4; YCbCr4:2:2; YCbCr4:2:0 8/10/12bpc
- Supports HDCP2.3&1.4

**Note:** The actual output resolution of the product is determined by the host and the display together. 2. The product worked on some hosts that support DP1.4&DSC can output dual 4K/60Hz simultaneously with different pictures



**Type-C Data X1** Close to USB-A

- Max 5Gbps data transmission

- Max 900mA downstream charging
- Supports short-circuit, over-current, over-voltage protection



#### **USB-A X3**

- Max 5Gbps data transmission per port
- Max 900mA downstream charging per port
- Supports short-circuit, over-current, over-voltage protection
- The Type-C data port and 3 USB-A Ports share max 12W



#### **SD4.0 / TF3.0 X1**

- TF card slot supports UHS-I up to 104MBps data rate
- SD card slot supports UHS-II up to 312MBps data rate
- Allow 2 card slots to work simultaneously
- TF card slot is equipped with press self-spring device




#### **RJ45 X1**

- Supports Gigabit Ethernet, 10M/100M/1000M
- Supports Wake-On-LAN
- Supports full duplex flow control
- Light indicates the state, no light when no Internet connected, orange light turns on when network connection is established, green light flashes when transmitting data.



#### **3.5 mm Audio Port X1**

- DAC supports 44.1/48/96KHz Sample Rate, 16/24-bit
- ADC input supports 44.1/48KHz Sample Rate, 16bit
- Support CTIA&OMTP auto detection
- Support voice adjustment function when connected to original headset



#### **Type-C PD Charging X1**

- Supports max 100W PD charging
- Supports PD3.0 Fast Role Swap, the connected device will not get disconnected while plugging in and out PD Adapter
- Supports smart power which allows to distribute power according to actual consumption of the connected devices, making full use of supplied power, the host can get power ranging from 82w to 96w

Introduction

Rocstor introduces the Type-C 11-in-1 Portable Dock, a comprehensive solution featuring 2 HDMI ports, 3 USB-A ports, SD/TF card slots, Ethernet connectivity, audio support, Type-C data transfer, and Type-C PD charging capability. Designed to seamlessly extend the port options of Type-C or Thunderbolt hosts such as PCs, laptops, and mobile phones, especially beneficial for devices with a single Type-C port. Equipped with DP1.4 Alt mode supported IC, enabling HDMI video output up to 8k/30Hz while simultaneously transferring USB 3.1 data at speeds of up to 5Gbps. Connect up to 4 USB devices concurrently with the 3 USB-A and Type-C data ports. Easily access data with the SD and TF card slots. Enjoy music through the 3.5mm audio port. The Type-C PD Charging port supports PD3.0 with a maximum power supply of 100W. Compatible with all DP Alt mode supported Type-C hosts, ensuring versatility and efficiency.

Package Contents

Before attempting to use this unit, please check the packaging and make sure the following items are contained in the packaging:

- Main Unit x1
- User Manual

Specification

Input / Output Connector	
Input	Type-C Male x1
Output	HDMI x2 Type-C Data x1 USB-A x3 SD/TF x1 RJ45 x1 3.5mm Audio port x1 Type-C PD Charging x1
Physical	
Weight	6.5lbs-(186g)
Physical	
Size	8.6×1.5×0.6in – (220x40x16mm)
Warranty	
Limited Warranty	3 Years

<b>Environmental</b>	
Operating Temperature	0°C to 45°C (32°F to 113°F)
Operating Humidity	10% to 90% RH (no condensation)
Storage Temperature	-10°C to 70°C (14°F to 158°F)
Storage Humidity	10% to 90 % RH (no condensation)
<b>Power Supply</b>	
Type-C PD Charging	Max 100W
<b>Regulatory Approvals</b>	
Certifications	FCC, CE
<b>Accessory Adapter</b>	
User Manual	English Version

**Connection Diagram**



## Warranty Information

### Warranty Information

This product is backed by a (3) three-year warranty. Rocstar warrants its products against defects in materials and workmanship for the periods noted, following the initial date of purchase. During this period, the products may be returned for repair, or replacement with equivalent products at our discretion. The warranty covers parts and labor costs only. Rocstar does not warrant its products from defects or damages arising from misuse, abuse, alteration, or normal wear and tear.

### Limitation of Liability

In no event shall the liability of Rocstar, Inc. and Rocstar (or their officers, directors, employees or agents) for any damages (whether direct or indirect, special, punitive, incidental, consequential, or otherwise), loss of profits, loss of business, or any pecuniary loss, arising out of or related to the use of the product exceed the actual price paid for the product. Some states do not allow the exclusion or limitation of incidental or consequential damages. If such laws apply, the limitations or exclusions contained in this statement may not apply to you.

## Safety Information:



### WARNING:

Please follow these safety instructions. Failure to do so may result damages or injury. It is normal that the device becomes very warm during use.

## Please note that:

Continuous contact with warm surfaces for extended time may cause discomfort or injury. In order to reduce the possibility of overheating or heat-related injuries, always allow needed ventilation around the device and use care when handling it. Avoid instances where your skin is in extended contact with the device when plugged into the host computer. It is not recommended to sleep with the device when plugged into a host computer. Avoid placing the device under a pillow, blanket, or your body when connected to a host computer. If you have a medical condition that affects your ability to detect heat against the body, extra care should be used. Never use the device in locations with water, such as a sink, bathtub, or shower stall. Never connect or disconnect the device with wet hands.

©2024 Rocstor, Inc. All rights reserved. Rocstor is registered trademark of Rocstor, Inc.

Apple®, the Apple logo, Mac®, MacBook®, MacBook Pro®, MacBook Air®, iPad®, iPad Air®, iPad mini®, iPad Air®, iPhone®, MacOS® are registered trademarks of Apple, Inc. Google® and Chromebook™ are registered trademarks of Google, LLC. Microsoft® is registered trademarks of Microsoft corporation. All other product names and logos mentioned herein may be trademarks of their respective companies.

Thunderbolt is a trademark of Intel Corporation or its subsidiaries. USB Type-C® and USB-C® are registered trademark of USB Implementers Forum. The terms HDMI, HDMI High-Definition Multimedia Interface, HDMI Trade dress and the HDMI Logos are trademarks or registered trademarks of HDMI Licensing Administrator, Inc. Feature and specification are subject to change without notice.

All trademarks and registered trademarks are the property of their respective. All rights reserved.



## Customer Support

Technical support is available to all the registered users of Rocstor products.

### Technical Support / RMA

**Hours:** 9:00 am – 5:00 pm PST

Monday to Friday (except holidays)

**Tell:** +1 [818-727-7000](tel:818-727-7000) (National and international)


**Fax:** +1 [818-875-0002](tel:818-875-0002)

**Email:** [support@rocstor.com](mailto:support@rocstor.com)



---

## Documents / Resources

	<p><a href="#">rocstor Y10P028-S1 USB-C 11 in 1 Dual Display Portable Dock</a> [pdf] User Manual Y10P028-S1 USB-C 11 in 1 Dual Display Portable Dock, Y10P028-S1, USB-C 11 in 1 Dual Display Portable Dock, 11 in 1 Dual Display Portable Dock, Dual Display Portable Dock, Display Portable Dock, Portable Dock, Dock</p>
---	--

## References

- [User Manual](#)

[Manuals+](#), [Privacy Policy](#)

This website is an independent publication and is neither affiliated with nor endorsed by any of the trademark owners. The "Bluetooth®" word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. The "Wi-Fi®" word mark and logos are registered trademarks owned by the Wi-Fi Alliance. Any use of these marks on this website does not imply any affiliation with or endorsement.