



ROG SWIFT Specifications

[Home](#) » [ROG](#) » ROG SWIFT Specifications 

ROG SWIFT PG258Q

Contents

- [1 SPECIFICATIONS](#)
- [2 Documents / Resources](#)
- [3 Related Posts](#)

SPECIFICATIONS

- **Display**

Panel Size : Wide Screen 24.5"(62.23cm) 16:9

Panel Backlight / Type : TN

True Resolution : 1920×1080 *

Display Viewing Area(HxV) : 0.2832 x 0.2802 mm

Display Surface: Non-glare

Brightness(Max) : 400 cd/

Contrast Ratio (Max) : 1000:1

Viewing Angle (CR $\geq$ 10) : 170°(H)/160°(V)

Response Time : 1ms (Gray to Gray)

Display Colors : 16.7M

Flicker free

- **Video Feature**

Trace Free Technology : Yes

Color Temperature Selection : 4 Modes

GamePlus(modes) : Yes (Crosshair/Timer/FPS Counter/Display Alignment)

Low Blue Light: Yes

HDCP support: Yes

GameVisual :6 Modes(Scenery/Racing/Cinema/RTS/RPG/FPS/sRGB Modes)

- **Convenient Hotkey**

GamePlus

5-way OSD Navigation Joystick

GameVisual

- **I/O Ports**

Signal Input: HDMI, DisplayPort

USB Port(s) : 3.0×2

- **Power Consumption**

Power ON mode: <65W (measuring a screen brightness of 200 nits without audio/ USB/Card reader connection)

Power Saving/Off mode: <0.5W

Voltage: 100-240V, 50/60Hz

- **Mechanical Design**

Chassis Colors: Dark gray, Plasma copper

Tilt : +20°~-5°

Swivel: +50°~-50°

Pivot: 0°~+90°

Height Adjustment: 0~120 mm

VESA Wall Mounting: 100x100mm

Super Narrow Bezel Design: Yes

- **Security**

Kensington lock

- **Dimensions**

Phys. Dimension with Stand(WxHxD):564.1x(383.7 ~ 503.7)x 253.7 mm

Phys. Dimension without Stand(WxHxD):564.1×330.6×72.5 mm

Box Dimension(WxHxD):661x443x239 mm

- **Weight**

Net Weight(Esti.):5.6kg

Net Weight without Stand :3.14 kg

Gross Weight(Esti.):7.9kg

- **Accessories**

Power cord

Power adapter

DisplayPort cable

USB 3.0 cable

Quick start guide

Acrylic LED light covers

HDMI cable

Support CD

Warranty Card

- **Compliance and Standards**

CB, CCC, CE, CEL level 1, CU, ErP, FCC, J-MOSS, KCC, PSE, RoHS, UL/cUL, VCCI, WEEE, WHQL

(Windows 10, Windows 8.1, Windows 7), RCM, TUV Flicker-free, standby, TUV Low Blue Light

- **Note**

*PG258Q supports 1920×1080 @ 240Hz (native)**Digital Signal Frequency:

DP: 67~255KHz (H) / 30~240Hz (V)

HDMI: 30~90KHz (H) / 24~60Hz (V)

Documents / Resources

[illegible]

Manuals+.