

RuiJie Reyee RG-EW Series Router User Guide

Home » RuiJie » RuiJie Reyee RG-EW Series Router User Guide 🖺





Ruijie Reyee RG-EW Series Router **POC Guide**

Document Version: V1.0 Date: January 30, 2023 Copyright © 2023 Ruijie Networks

Contents

- 1 RuiJie Reyee RG-EW Series Router
- 2 Preface
- **3 Product Introduction**
- 4 Lists of Test Devices and Software
- **5 Function Test Guide**
- 6 Documents / Resources
 - **6.1 References**

RuiJie Reyee RG-EW Series Router

Copyright

Copyright © 2023 Ruijie Networks

All rights are reserved in this document and this statement.

Without the prior written consent of Ruijie Networks, any organization or individual shall not reproduce, extract, back up, modify, or propagate the content of this document in any manner or in any form, or translate it into other languages or use some or all parts of the document for commercial purposes.

Reyee and other Ruijie networks logos are trademarks of Ruijie Networks.

All other trademarks or registered trademarks mentioned in this document are owned by their respective owners.

Disclaimer

The products, services, or features you purchase are subject to commercial contracts and terms, and some or all of the products, services, or features described in this document may not be available for you to purchase or use. Except for the agreement in the contract, Ruijie Networks makes no explicit or implicit statements or warranties

with respect to the content of this document.

The content of this document will be updated from time to time due to product version upgrades or other reasons, Ruijie Networks reserves the right to modify the content of the document without any notice or prompt.

This manual is designed merely as a user guide. Ruijie Networks has tried its best to ensure the accuracy and reliability of the content when compiling this manual, but it does not guarantee that the content of the manual is completely free of errors or omissions, and all the information in this manual does not constitute any explicit or implicit warranties.

Preface

Intended Audience

This document is intended for:

- · Network engineers
- Technical support and servicing engineers
- Network administrators

Technical Support

- Official website of Ruijie Reyee: https://www.ruijienetworks.com/products/reyee
- Technical Support Website: https://www.ruijienetworks.com/support
- Case Portal: https://caseportal.ruijienetworks.com
- Community: https://community.ruijienetworks.com
- Technical Support Email: service rj@ruijienetworks.com

Conventions

1. Signs

This document also uses signs to indicate some important points during the operation. The meanings of these signs are as follows.



Warning

An alert that calls attention to important rules and information that if not understood or followed can result in data loss or equipment damage.



Caution

An alert that calls attention to essential information that if not understood or followed can result in function failure or performance degradation.



Note

An alert that contains additional or supplementary information that if not understood or followed will not lead to serious consequences.



Specification

An alert that contains a description of product or version support.

2. Note

This manual is used to guide users to understand the product, install the product, and complete the

Product Introduction

Powerful Mesh Wi-Fi for Full Area Coverage

- Support Reyee Mesh, zero-configuration networking for multiple devices.
- Support next generation chip, delivering stable connection and better performance.
- Support Seamless Roaming, dead-zone killer, signal-amplifier offering strong signals.
- Support Ruijie Cloud Management, operation and maintenance remotely by mobile APP.
- Support scenario-oriented features with Parental Control, Xpress Acceleration Mode, etc.

Lists of Test Devices and Software

2.1 Test Device List

Device Type	Device Name	Quantity	Remarks
Mesh Wi-Fi			

2.2 Test Software List

Software Name	Quantity	Unit	Remarks
WiFi Moho	1	PCS	RSSI test
Speedtest	1	PCS	Speed test


Function Test Guide

3.1 Reyee mesh

Test Item	Reyee Mesh
Test Purpose	Zero-Configuration Networking for Pairing Multiple Reyee device
Test Procedure and Expected Results	(1) The WAN port of the primary router is connected to the Internet and completes initialization. Clients such as mobile phones or PCs can find the SSID of the primary router and access the Internet. (2) Move the secondary router next to the primary router. You are advised to place the secondary router within 2 m (6.56 ft) away from the primary router without any obstacle. Power up and turn on the secondary router. (3) Press the Mesh button on the primary router. The Mesh LED of the primary router starts blin king. After 1 to 3 seconds, the LED on the secondary router starts fast blinking. When the LED s on the primary and secondary routers are solid on, a Reyee mesh connection is successfully set up. (4) Disconnect the secondary router and move it to the position to be tested for Wi-Fi coverage. Power up the router, and wait for 3 minutes until the LED is solid on. (5) Log in to the Eweb of the primary router. You can check the mesh connection status on the homepage.
Test Records	
Test Conclusi on	

3.2 Extreme Performance tests


Test Item	Extreme performance tests of household products
Test Purpose	Test the extreme performance of a household device.
Test Fulpose	The WAN port of the primary router is connected to the Internet and completes initialization. Clients such as mobile phones or PCs can find the SSID of the primary router and access the Internet. (1) Install WiFi Moho or another app with the Wi-Fi scanning function on your mobile phone, check the interference analysis result, and find the optimal channel.



(2) Log in to the Eweb of the router to configure a specified channel. Choose More > WLAN > Radio Frequency.


If the interference is severe, choose a lower channel bandwidth to prevent network freezing. The router supports channel bandwidths of 20 MHz and 40 MHz. You are advised to select 20 MHz at 2.4 GHz and keep the default bandwidth at 5 GHz. You are advised to select 80 MHz at 5 GHz when testing the network speed. Click Save to make the configuration take effect imme diately.





(3) Choose WLAN > Wi-Fi.

Disable Dual-Band Single SSID. Configure SSIDs for 2.4 GHz and 5 GHz respectively. Connect to the SSID of 5 GHz when testing speeds.




3.3 Signal Coverage Tests

Test Item	Signal Coverage Tests	
Test Purpose	Test the signal coverage of the router.	
Test Procedure and Expected Results	(1) The WAN port of the primary router is connected to the Internet and completes initialization. Clients such as mobile phones or PCs can find the SSID of the primary router and access the Internet. (2) Connect the client to the SSID and move it to the specified testing position. (3) Enable WiFi Moho and record the signal strength of the position. (4) Enable Speedtest to test the speed and record the values. (5) Record signal strength of different positions and speed testing results.	
Test Records	First test O Distance: m RSSi: dBm Upload: Mbps Download: Mbps Second test Distance: m RSSi: dBm Upload: Mbps O Download: Mbps	
Test Conclusi on		

3.4 Repeater

Test Item	Repeater Tests
Test Purpose	Verify the Reyee Mesh function and the Other Router repeater function of the repeater.
	Connecting the Device to a Reyee Router (Reyee Mesh)



- (1) Connect the mesh repeater to a power source, and wait for 1-2 minutes until the status of the center green LED changes from blinking to solid on. The mesh repeater is started.
- (2) Press the Reyee mesh button on the primary Reyee router or connect the network cable to the primary Reyee router for automatic networking. When the three bars of the LED are on, Re yee mesh is successfully set up. Then the default Wi-Fi disappears, and the Wi-Fi name and p assword are synchronized with the primary router. When the signal LED is solid white, the net work connection is successful. Clients can connect to the amplified Wi-Fi of the primary router to access the Internet.
- (3) If the center dot LED is solid red, the network connection fails. Check whether the primary r outer can access the Internet. If the center dot is solid orange, the connection with the primary router fails. Move the mesh repeater to a position closer to the primary router, remove obstacles, and press the Reyee mesh button on the primary router again.
- (4) Place the repeater in a position requiring signal coverage.


Note


The distance between the repeater and the primary router is less than two walls for a faster net work speed.


Connect the Device to a Modem or the Other Router


- (1) Connect the mesh repeater to a power source, and wait for 1-2 minutes until the status of the center green LED changes from blinking to solid on. The mesh repeater is started.
- (2) Search for the wireless network with the Wi-Fi name @Ruijie-sXXXX by using a mobile phone or laptop. The mobile phone or laptop can log in to the web management page through a browser.
- (3) Select Wireless Repeater

Test Procedure and Expected Results











Test Procedure and Expected Results

(4) When the time reaches the specified block time, it will block completely within 40sec, client can access Wi-Fi but cannot access the internet.




(5) When the non-blocking time is reached, customer access to the Internet will be fully restore d within 40sec.



3.6 WISP

Test Item	WISP
Test Purpose	Verify the WSIP function.
	Note: Only the EW1200G-PRO, EW300-PRO, EW1200R, and EW300R support the WSIP function. (1) Log in to the Eweb of the router and click WISP.
	Wizard




(2) On the displayed network setup page, click Next to automatically obtain an IP address.



(3) Select the SSID of the primary router and enter the Wi-Fi password to connect to the primar y router.

Test Procedure and Expected Results





(4) Set the SSID and password and save the settings. Then settings of the Wi-Fi network are re set.







(5) In wireless ISP mode, the device still supports routing and DHCP functions, IP addresses of clients connected to the primary router are assigned by the primary router and the IP addresse s of clients connected to the secondary router are assigned by the secondary router.

Test Records	
Test Conclusi	
on	



Documents / Resources



References

- R csm
- R csm
- R ruijienetworks
- Rruijienetworks
- Ruijie Reyee Redefine Your Easy Network
- R Support | Ruijie

Manuals+,