

SATECHI Mobile XR Hub With Audio User Guide

Home » SATECHI » SATECHI Mobile XR Hub With Audio User Guide 🖔



Contents

- 1 Mobile XR Hub With Audio
- 2 Documents / Resources
 - 2.1 References

Mobile XR Hub With Audio



Connect the adapter to a compatible host device. The LED indicator will turn on once connected.

Compatible with iPhone 15 & 16 series.



Insert an audio device into the 3.5mm auxiliary port.

Supports 3.5mm audio jack, 2.1 channel audio, and microphone input. Supports CTIA & OMTP standard and includes volume control functionality.



Connect a Thunderbolt 4, USB4, or USB-C to HDMI/DP cable to the USB-C port. Supports USB 3.0 at 10 Gbps, 2-lane DP1.4 with 8.1 Gbps per lane, 4-lane DP1.2 for iPhone 15, 4K@60Hz mode depending on the host and screen.



Connect a USB-C charging cable to either USB-C PD port. Supports USB 2.0, plug & play; PD3.1 SPR, with a maximum input up to 100W depending on the host device.

Note: This product may not be compatible with all cases. Maximum supported case thickness is 2.5mm. For cases that exceed this thickness, compatibility cannot be guaranteed.



Documents / Resources



SATECHI Mobile XR Hub With Audio [pdf] User Guide Mobile XR Hub With Audio, XR Hub With Audio, Hub With Audio, Audio

References

• User Manual

Manuals+, Privacy Policy

This website is an independent publication and is neither affiliated with nor endorsed by any of the trademark owners. The "Bluetooth®" word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. The "Wi-Fi®" word mark and logos are registered trademarks owned by the Wi-Fi Alliance. Any use of these marks on this website does not imply any affiliation with or endorsement.