



Schumacher SPR1630 Jump Starter and DC Power Source Owner's Manual

[Home](#) » [Schumacher](#) » Schumacher SPR1630 Jump Starter and DC Power Source Owner's Manual 

Contents

- 1 Schumacher SPR1630 Jump Starter and DC Power Source
- 2 IMPORTANT SAFETY INSTRUCTIONS – SAVE THESE INSTRUCTIONS
- 3 PERSONAL SAFETY PRECAUTIONS
- 4 Features
- 5 CHARGING THE INTERNAL BATTERY OF THE JUMP STARTER
- 6 OPERATING INSTRUCTIONS
- 7 MAINTENANCE INSTRUCTIONS
- 8 MOVING AND STORAGE INSTRUCTIONS
- 9 TROUBLESHOOTING
- 10 ACCESSORIES
- 11 LIMITED WARRANTY
- 12 Documents / Resources
 - 12.1 References
- 13 Related Posts

Schumacher

Schumacher SPR1630 Jump Starter and DC Power Source



IMPORTANT SAFETY INSTRUCTIONS – SAVE THESE INSTRUCTIONS

WARNING:

RISK OF EXPLOSIVE GASES WORKING IN THE VICINITY OF A LEAD-ACID BATTERY IS DANGEROUS. BATTERIES GENERATE EXPLOSIVE GASES DURING NORMAL OPERATION. IT IS IMPORTANT THAT YOU FOLLOW THESE INSTRUCTIONS EACH TIME YOU USE THE UNIT. To reduce the risk of battery explosion, follow these instructions and those published by the battery manufacturer and the manufacturer of any equipment you intend to use in the vicinity of a battery. Review cautionary markings on these products and on the engine.

WARNING! RISK OF ELECTRIC SHOCK OR FIRE.

1. Keep out of reach of children.
2. Do not disassemble the jump starter. Take it to a qualified service professional if service or repair is required. Incorrect assembly may result in fire or electrical shock.
3. Do not use the jump starter to jump a vehicle while charging the internal battery.
4. Do not recharge the jump starter with a damaged extension cord.
5. The jump starter gets hot during charging and must have proper ventilation.
6. Do not set the jump starter on flammable materials, such as carpeting, upholstery, paper, cardboard, etc. 1.7 Place the jump starter as far away from the battery being jumped as the cables will permit.
7. Do not expose the jump starter to rain or snow.
8. Never attempt to jump start a frozen battery.
9. Never place the jump starter directly above battery being jumped.
10. To prevent arcing, never allow the clamps to touch together or to contact the same piece of metal. 1.12 Use of an attachment not recommended or sold by the jump starter manufacturer may result in damage to the unit or personal injury.
11. Never operate the jump starter if it is damaged.
12. If someone else uses the jump starter, ensure they are well informed on how to use it safely, and have read and understood the operating instructions.

13. The jump starter is NOT designed to be installed as a replacement for a vehicle battery.
14. Use ONLY on vehicles, boats and garden tractors powered with a 12V DC battery system.
15. If the engine fails to start after the recommended number of attempts, disconnect the unit and look for other problems that may need to be corrected.
16. Use the jump starter for jump starting lead-acid batteries only. Do not use for dry cell batteries that are commonly used with home appliances.

PERSONAL SAFETY PRECAUTIONS

1. Wear complete eye protection and protective clothing when working near lead-acid batteries. Always have someone nearby for help.
2. Have plenty of fresh water, soap and baking soda nearby for use, in case battery acid contacts your eyes, skin, or clothing. Wash immediately with soap and water and seek medical attention.
3. If battery acid comes in contact with eyes, flush eyes immediately for a minimum 10 minutes and get medical attention.
4. Neutralize any acid spills thoroughly with baking soda before attempting to clean up.
5. Remove all personal metal items from your body, such as rings, bracelets, necklaces and watches. A battery can produce a short circuit current high enough to weld a ring to metal,

Features



1. Worklight ON/OFF switch
2. Rotary switch for USB and jump starter
3. Built-in work light
4. Battery status indicators
5. Battery status button

6. USB port
7. 12V DC power outlet
8. Battery clamps
9. Air compressor gauge
10. Air compressor ON/OFF switch
11. Internal battery charger port
12. Air compressor hose wrap cleats
13. Air compressor hose
14. Air compressor adapters and storage bag

CHARGING THE INTERNAL BATTERY OF THE JUMP STARTER

IMPORTANT:

CHARGE IMMEDIATELY AFTER PURCHASE, AFTER EACH USE AND EVERY 30 DAYS, TO KEEP THE UNIT'S INTERNAL BATTERY FULLY CHARGED AND PROLONG BATTERY LIFE.

CHECKING THE LEVEL OF THE INTERNAL BATTERY

Press the Battery Status button on the front of the unit. The LED lights will indicate the current charge level as follows:

- RED – less than 20% of full charge; immediately charge the unit.
- YELLOW/ORANGE – 20-80% of full charge.
- GREEN – more than 80% of full charge.

CHARGING THE INTERNAL BATTERY

Charge the unit's internal battery using an extension cord (not included).

NOTE:

Use of an improper extension cord could result in a risk of fire and electric shock.

1. To charge, flip the AC connector on the back of the unit DOWN and plug in an 18 AWG or larger extension cord.
2. Plug the extension cord into a 120VAC electrical wall outlet.
3. While the jump starter is charging, the RED LED will be on. Complete charging may take up to 72 hours. When the RED LED turns off, the jump starter is ready to use.
4. When the internal battery is fully charged, the charger will automatically go into maintain mode and maintain the battery at full charge without damaging it. When in maintain mode, the GREEN LED will light, as long as there is an AC cord connected to the charging port.
5. Charge the jump starter as soon as possible after use.

CHARGING THE INTERNAL BATTERY WHILE DRIVING

You may also charge the internal battery while driving, using a male-to-male charger cable (part number 94500109 – not included).

IMPORTANT:

DO NOT CHARGE INTERNAL BATTERY FOR MORE THAN 30 MINUTES OR LEAVE THE BATTERY UNATTENDED. IT COULD EXPLODE, CAUSING PROPERTY DAMAGE OR PERSONAL INJURY.

1. Make sure the car is running.

2. Insert one end of the accessory cable into the 12V DC power outlet.
3. Insert the other end of the accessory cable into the vehicle's accessory outlet (lighter socket).

NOTE:

The RED LED does not operate during this method of charging. Using this method to charge the battery overrides the maintain mode and the battery can be overcharged.

4. Monitor the progress of the charge by pressing the Battery Status button on the front of the unit. When the battery is fully charged, disconnect the accessory cable from the unit, and then from the lighter socket of the vehicle.

OPERATING INSTRUCTIONS

1. Turn the ignition OFF.
2. Lay the DC cables away from any fan blades, belts, pulleys and other moving parts.
3. For a negative-ground vehicle (as in most vehicles), connect the Instant Power's POSITIVE (RED) clamp to the POSITIVE (POS, P, +) battery post. Next, connect the NEGATIVE (BLACK) clamp to the vehicle chassis or engine block, away from the battery.
4. For a positive-ground vehicle, connect the Instant Power's NEGATIVE (BLACK) clamp to the NEGATIVE (NEG, N, -) battery post. Next, connect the POSITIVE (RED) clamp to the vehicle chassis or engine block away from the battery.
5. Turn the switch to the ON position
6. Crank the engine for no more than 8 seconds. If the engine does not start, wait 2 minutes before cranking again.
7. After the engine starts, turn the switch to the OFF position and remove the unit from the battery.
8. Charge the unit.

USING THE USB PORT

1. Ensure the battery clamps are securely clipped on the storage holders.
2. Turn the unit ON.
3. Plug your device into the USB port.
4. When finished using the USB port, turn the switch to the OFF position.
5. Charge the unit.

USING THE WORK LIGHT

- Make sure the lamp is turned OFF when the unit is being recharged or stored.
- Position the unit on a flat, stable surface near the intended work area.
- Ensure the battery clamps are securely clipped on the storage holders.

POWERING A 12V DC DEVICE

1. Make sure the device to be powered is OFF before inserting the 12V DC accessory plug into the 12V DC accessory outlet.
2. Open the protective cover of the DC power outlet on the unit.

3. Plug the 12V DC device into the DC power outlet and turn on the 12V DC device (if required).
4. When finished, turn off the DC device (if required) and unplug from the DC power outlet. CAUTION: Do not use the unit to run appliances that draw more than 20A DC.

NOTE:

Extended operation of a 12V DC device may result in excessive battery drain. Recharge the unit immediately after unplugging the 12V DC device.

Estimated run-times

APPLIANCE TYPE	EST WATTAGE	APPROX. USAGE
Cell phone, fluorescent light	4 watts	34 hrs
Radio, fan, depth finder	9 watts	14 hrs
Camcorder	15 watts	7 hrs
Electrical tool	24 watts	5 hrs
Electric cooler	48 watts	2 hours
Car vacuum, air compressor	80 watts	1.8 hrs

NOTE:

Actual time may vary. Times are based on the internal battery being fully charged.

FOR MODELS WITH AN AIR COMPRESSOR

WARNING.

Read the instructions of the product being inflated before using the compressor. Avoid overinflation; do not exceed the manufacturer's recommended pressures. Do not leave the air compressor unattended during use.

NOTE:

Wrap cleats are provided for convenient storage of the air compressor hose. Wrap the hose around these cleats when the hose is not in use.

1. Ensure the battery clips are securely on the storage holders.
2. Remove the air compressor hose from the storage cleats.
3. Connect the adapter to the valve stem by threading it onto the end. If necessary, use one of the additional adaptors.
4. Press the air compressor power switch to turn ON and inflate to the desired pressure or fullness (refer to the gauge next to the switch).
5. When the desired pressure is reached, press the air compressor power switch to turn OFF and remove the connector from the valve stem.
6. Allow unit to cool.
7. Recharge the unit before storing.

NOTE:

The air compressor is rated for 150 PSI.

Estimated time for inflating

Vehicle tires 13-16"	6-24 minutes
Bike tires	1-3 minutes
Sports balls	30 seconds

MAINTENANCE INSTRUCTIONS

1. After use and before performing maintenance, unplug and disconnect the jump starter.
2. Use a dry cloth to wipe all battery corrosion and other dirt or oil from the battery clips, cords and the jump starter case.
3. Ensure that all of the jump starter components are in place and in good working condition.
4. All servicing should be performed by qualified service personnel.

MOVING AND STORAGE INSTRUCTIONS

1. Store inside, in a cool, dry place.
2. Do not store the clips on the handle, clipped together, on or around metal, or clipped to cables. The clips on the jump starter are live when the switch is in the ON position and will produce arcing or sparking if they come in contact with each other. To prevent accidental arcing, always place the switch in the OFF position and keep the clips on the storage holders when not using it to jump start a vehicle.
3. If the jump starter is moved around the shop or transported to another location, take care to avoid/ prevent damage to the cords, clips and jump starter. Failure to do so could result in personal injury or property damage.

IMPORTANT:

Do not use and/or store the jump starter in or on any area or surface where damage could occur if the internal battery should unexpectedly leak acid.

CHARGE IMMEDIATELY AFTER PURCHASE

Charge the jump starter's internal battery immediately after purchase, after every use and every 30 days. All batteries are affected by temperature. The ideal storage temperature is at 70°F. The internal battery will gradually self-discharge (lose power) over time, especially in warm environments. Leaving the battery in a discharged state may result in permanent battery damage. To ensure satisfactory performance and avoid permanent damage, charge the internal battery every month.

TROUBLESHOOTING

PROBLEM	POSSIBLE CAUSE	SOLUTION
---------	----------------	----------

The unit won't jump start my car.	<p>Clamps are not making a good connection to the battery.</p> <p>Connections are reversed.</p> <p>The internal battery is not charged.</p> <p>The vehicle's battery is defective. The unit is not turned on.</p>	<p>Check for poor connection to battery and frame. Make sure connection points are clean.</p> <p>Disconnect the unit and reverse the clamps.</p> <p>Press the Battery Status button on the front of the unit. The LEDs will indicate the status of charge.</p> <p>Have the battery checked.</p> <p>Turn the unit's ON/OFF switch to the ON position.</p>
The unit won't power my 12V device.	<p>The 12V device is not turned on.</p> <p>The internal battery is not charged.</p> <p>The 12V device draws more than 20A, has a short circuit, or the internal fuse has blown.</p>	<p>Turn on the 12V device.</p> <p>Check the battery charge status by pressing the Battery Status button.</p> <p>Disconnect the 12V device.</p> <p>The internal 20A fuse needs replacement by a qualified service person.</p>
The internal battery won't hold a charge.	The battery is bad (will not accept a charge).	Have the battery checked.
The compressor shuts off.	The compressor is overheated.	Allow to cool for a few minutes, then try again.

REPLACEMENT PARTS

- Air compressor accessory kit (3 hose adapters) 2299001425Z

ACCESSORIES

- Male-to-male accessory cable
.....94500109

BEFORE RETURNING FOR REPAIRS

- For REPAIRS OR RETURNS, visit 365rma.com
- Visit batterychargers.com for Replacement Parts.


LIMITED WARRANTY

SCHUMACHER ELECTRIC CORPORATION, 14200 FAA BLVD., FORT WORTH, TX 76155, MAKES THIS LIMITED WARRANTY TO THE ORIGINAL RETAIL PURCHASER OF THIS PRODUCT. THIS LIMITED WARRANTY IS NOT TRANSFERABLE OR ASSIGNABLE.

Schumacher Electric Corporation (the "Manufacturer") warrants this jump starter for one (1) year and the internal battery for ninety (90) days from the date of purchase at retail against defective material or workmanship that may occur under normal use and care. If your unit is not free from defective material or workmanship, Manufacturer's obligation under this warranty is solely to repair or replace your product with a new or reconditioned unit at the option of the Manufacturer. It is the obligation of the purchaser to forward the unit, along with proof of purchase and mailing charges prepaid to the Manufacturer or its authorized representatives in order for repair or replacement to occur. Manufacturer does not provide any warranty for any accessories used with this product that are not manufactured by Schumacher Electric Corporation and approved for use with this product. This Limited Warranty is void if the product is misused, subjected to careless handling, repaired, or modified by anyone other than Manufacturer or if this unit is resold through an unauthorized retailer. Manufacturer makes no other warranties, including, but not limited to, express, implied or statutory warranties, including without limitation, any implied warranty of merchantability or implied warranty of fitness for a particular purpose. Further, Manufacturer shall not be liable for any incidental, special or consequential damage claims incurred by purchasers, users or others associated with this product, including, but not limited to, lost profits, revenues, anticipated sales, business opportunities, goodwill, business interruption and any other injury or damage. Any and all such warranties, other than the limited warranty included herein, are hereby expressly disclaimed and excluded. Some states do not allow the exclusion or limitation of incidental or consequential damages or length of implied warranty, so the above limitations or exclusions may not apply to you. This warranty gives you specific legal rights and it is possible you may have other rights which vary from this warranty.

THIS LIMITED WARRANTY IS THE ONLY EXPRESS LIMITED WARRANTY AND THE MANUFACTURER NEITHER ASSUMES OR AUTHORIZES ANYONE TO ASSUME OR MAKE ANY OTHER OBLIGATION TOWARDS THE PRODUCT OTHER THAN THIS WARRANTY.

Documents / Resources

	Schumacher SPR1630 Jump Starter and DC Power Source [pdf] Owner's Manual BE01254, FR01240, SJ1330, SJ1331, SJ1426, SPR1630, Jump Starter and DC Power Source, SPR1630 Jump Starter and DC Power Source
---	--

References

-  **** 365RMA.COM ****
-  **[Home Page - Schumacher Electric](#)**
-  **[Home Page - Schumacher Electric](#)**

