

# **SEALEY 9007 P3R Particulate Filter User Manual**

Home » SEALEY » SEALEY 9007 P3R Particulate Filter User Manual



#### Contents

- 1 SEALEY 9007 P3R Particulate
- **2 REFER TO INSTRUCTIONS**
- **3 INTRODUCTION**
- **4 FILTER PROTECTION**
- **5 STORAGE & CLEANING**
- **6 OBSOLESCENCE**
- **7 FILTER DISPOSAL**
- 8 Documents / Resources
  - 8.1 References
- 9 Related Posts



**SEALEY 9007 P3R Particulate Filter** 



# **Specifications**

• Product Name: Particulate Filter P3R - Pack of 2

• Model Number: 9007

• Conforms to: EN 143:2000

• Maximum Filtration Levels: 30 x OEL

# **Threat Types**

- 1. Fine particles and dust
- 2. Particles and fine particles
- 3. Metallic dusts, particles
- 4. Dust, fine particles
- 5. Fumes
- 6. Fine particles, dusts

# **Product Usage Instructions Mounting the Filter**

The VENT EMKA T-BM P2 (P3) R and T-BM A P2 (P3) R filters have a bayonet connector for mounting with compatible face masks or half masks with a bayonet connector.

## **User Adjustment**

Respirators and masks should be properly adjusted to the user's face before each use, following the instructions provided with the protective gear.

#### Q: Can these filters be used with any type of face mask?

A: The filters are suitable for use with Sealey 9000 half face mask or masks with a compatible bayonet connector. For other facepieces, check compatibility first.

#### PARTICULATE FILTER P3R - PACK OF 2 MODEL NO: 9007

Thank you for purchasing a Sealey product. Manufactured to a high standard, this product will, if used according to these instructions, and properly maintained, give you years of trouble free performance.

#### **REFER TO INSTRUCTIONS**

IMPORTANT: PLEASE READ THESE INSTRUCTIONS CAREFULLY. NOTE THE SAFE OPERATIONAL REQUIREMENTS, WARNINGS & CAUTIONS. USE THE PRODUCT CORRECTLY AND WITH CARE FOR THE PURPOSE FOR WHICH IT IS INTENDED. FAILURE TO DO SO MAY CAUSE DAMAGE AND/OR PERSONAL INJURY AND WILL INVALIDATE THE WARRANTY. KEEP THESE INSTRUCTIONS SAFE FOR FUTURE USE.

#### INTRODUCTION

AP3R Particulate filter provides protection against solid particles and water based aerosols. Suitable for use with the Sealey 9000 half face mask. Conforms to EN 143:2000. Maximum filtration levels 30 x OEL

#### Type Examination Ref.: UE/557/2021/1437

Notified Body: Centralny Instytut Ochrony Pracy – Panstwowy Instytut Badawczy (CIOPPIB) (notified body number 1437)



# **FILTER PROTECTION**

T-B filters of class P2 (P3) when completed with an appropriate two-filter face part (half mask, mask) protect the respiratory system against non-toxic and moderately toxic (P3 - toxic) solid aerosols or water-based aerosols (dust, smoke) and liquid aerosols (mists), provided that the concentration of the dispersed phase of the aerosol does not exceed the value of 12 x NDS (P3 - 50 x NDS) when completed with a half mask, and 16.5 x NDS (P3 - 1000 x NDS) when completed with a mask. The P2 (P3) filter with carbon fleece additionally protects against

odours and unpleasant odours as well as the irritating effects of aerosols and organic vapours. This makes it possible to use protective equipment equipped with T-B P2 (P3) R-A filters in an atmosphere contaminated with organic substances, provided that their concentration does not exceed the MRL value.

- P2 Penetration: < 3%, P3 Penetration: < 0.05%
- P2 Breathing resistance (47.5 l/min.): < 160 Pa,
- P3 Breathing resistance (47.5 l/min.): < 260 Pa

MARKS	MEANING		CLASS	GAS FILTERS	PARTICULATE FILTE RS
A	Filter against organic gases and vapours with a boiling point > 65°C		1	Gas concentratio n 1000 ppm (0.1 %)	Penetration 20%
AX	Filter against filter against organic gases and vapours with a boiling point < 65°C		2	Gas concentratio n 5000 ppm (0.5 %)	Penetration 6%
В	Filter against inorganic gases and vapors excluding carbon monoxide		3	Gas concentratio n 10000 ppm (1% )	Penetration 0.05%
Е	Filter against sulfur dioxide and other aci d gases				
K	Filter against ammonia and organic vapo urs derived from ammonia		MARKS		
Р	Filter against particulate (dust and aeros ols)		T-B, T-BL, T-BM – filter type P2 and P3 – filter class according to EN 43:2000/A1:20		
R	Filter reusable		06  A- filter containing carbon fleece  R – reusable filter  VENTUM – filter manufacturer		
NR	Filter non reusable				
D	Filter passes the optional Dolomite clogging test				

- 1. P2 and P3 grade T-B filters are manufactured with three types of bayonet connectors. To distinguish the type of connector, the filters have appropriate extensions in the name, namely:
  - 1. VENT ESKA T-B P2 (P3) R and T-B P2 (P3) R-A filters have a bayonet connector that allows them to be mounted with half masks: SECURA 2000, Advantage 200, 300, 400 and masks: Advantage 1000, 3000 or MAG-2
  - 2. VENT ELKA T-BL P2 (P3) R and T-BL A P2 (P3) R filters have a bayonet connector that allows them to be mounted with half masks or masks with BLS connectors
  - 3. The VENT EMKA T-BM P2 (P3) R and T-BM A P2 (P3) R filters have a bayonet connector that allows them to be mounted with half masks or masks with a bayonet connector, such as those from 3M The use of T-B filters with other facepieces requires checking the compatibility of their bayonet connector with the filter connector.
- 2. Respirators and masks should be adjusted to the user's face before use in accordance with the instructions for

use of the protective equipment in question.

- 3. Assess whether the filters meet the requirements for existing hazards
- 4. Respirators and masks with T-B filters of class P2 (P3) do not protect against carbon monoxi de. Do not use half masks and masks with filters in the area of fires.
- 5. Half masks and masks with T-B filters of class P2 (P3) should not be used where oxygen defic iency (below 19% vol.) may occur, e.g. in manholes, ducts, unventilated rooms with small cubic capacity.

NOTE: If it is necessary to replace the filters, replace both filters in use with new ones at the same time. It is forbidden to replace one

filter and leave the filter previously used in the equipment.

P2 APPLICATION EXAMPLES	THREAT TYPE
<ol> <li>- Sanding softwoods (except beech and oak)</li> <li>- Mechanical rust removal (sanding), plaster and plastic sanding 3 – Mechanical processing of steel: cutting, machining, grinding– Powder coating (except paints containing lead chromate)</li> <li>- Mining and processing of hard coal and lignite, granite, marble, sand stone, dolomite</li> <li>- Mining and processing of metal ores (except zinc and lead)</li> <li>- Iron Casting &amp; Casting Machining</li> <li>- Mechanical machining of aluminium and aluminium alloys 9 – Sandi</li> </ol>	<ol> <li>- Fine particles and dust</li> <li>- Particles and fine particles</li> <li>- Metallic dusts, particles</li> <li>- Dust, fine particles 5 - Dust, fine particles</li> <li>- Dust, fine particles, mists 7 - Dust, fine particles, mists 8 - Dust, fine particles</li> <li>- Particles, fine particles, mists 1</li> </ol>
ng wood with copper-containing water  7. — Mechanical Paint StrippingTIG/MIG/MAG/ welding, oxy-fuel cutting, brazing, brazing  8. — Agriculture — artificial fertilizers (preparation, pouring, spreading).	<ul> <li>0 – Dust, fine particles</li> <li>7. – Dust, fine particles</li> <li>8. – Fumes</li> <li>9. – Fine particles, dusts</li> </ul>
P3 APPLICATION EXAMPLES	THREAT TYPE

- 1. Sanding softwoods (except beech and oak)
- 2. Dusts that cause pneumoconiosis
- especially silicosis dusts containing free silica (SiO2): quartz, chalce dony, tridinite, cristobalite, opal, quartz glass, cement, coal, lignite, talc , mineral wool, soil, grindstones.
- 4. Chemical, glass, optical, electronic, foundry, construction, etc.
- Agriculture artificial fertilizers (preparation, pouring, spreading).
   Asbestos dusts are classified as extremely harmful dusts.
- 6. Hardwood sanding
- 7. Mechanical rust removal (sanding), plaster and plastic sanding.
- 8. Welding: TIG/MIG/MAG/ welding, gas welding, oxy-fuel cutting, sold ering, brazing 9 –
- 9. Machining: cutting, machining, grinding

- 1. Fine particles and dust
- 2. Dust and fine pa
- 3. Dust and fine particles
- 4. Dust, fine particles
- 5. Dust, fine particles
- 6. Dust, fine particles
- 7. Particles and fine particles
- Fine metallic particles and fum es, ozone
- 9. Metallic dusts, Particles

**NOTE:** Italics in the application examples mean that it is sufficient to use P1 filters Filters with carbon fleece (letter A in the name) additionally protect against odours and unpleasant odours as well as the irritating effects of aerosols and organic vapours. Half masks and masks equipped with this type of filters effectively reduce the negative effects associated with exhaust emissions. This makes it possible to use protective equipment equipped with carbon fleece filters in an atmosphere contaminated with organic substances, provided that their concentration does not exceed the MRL value. Individual protective equipment with filters with carbon fleece can be used, for example, in electric welding, in the operation of trains powered by internal combustion engines, in the pharmaceutical industry, in breweries, in tanneries, in forensics, during service and maintenance works and other work in the atmosphere where unpleasant odours and odours may occur, e.g. removing waste from septic tanks and manholes, cleaning garbage cans. The use of a carbon layer in the filters slightly increases the breathing resistance, but significantly expands their protective parameters.

#### STORAGE & CLEANING

Filters should be stored in the factory packaging (plastic bag, cardboard) in dry rooms, under the conditions indicated on the pictogram. In case of damage or deterioration, replace the filter. DO NOT clean or maintain. The replacement of the filters must be determined through the implementation of a respiratory protection program which ensures that they are replaced before the end of their service life.

## **OBSOLESCENCE**

Filters stored in accordance with the recommendations retain their functional (protective) properties for 36 months from the date of manufacture.

#### **FILTER DISPOSAL**

Once filters have been used, they must be disposed of according to the current national legislation.

This document has been drawn up according to Regulation (EU) 2016/425 as amended to apply to GB for Personal Protective Equipment. The declaration of conformity can be accessed at <a href="www.sealey.co.uk">www.sealey.co.uk</a>.



#### **ENVIRONMENT PROTECTION**

Recycle unwanted materials instead of disposing of them as waste. All tools, accessories and packaging should be sorted, taken to a recycling centre and disposed of in a manner which is compatible with the environment. When the product becomes completely unserviceable and requires disposal, drain any fluids (if applicable) into approved containers and dispose of the product and fluids according to local regulations.

**Note:** It is our policy to continually improve products and as such we reserve the right to alter data, specifications and component parts without prior notice. Important: No Liability is accepted for incorrect use of this product. **Warranty:** Guarantee is 12 months from purchase date, proof of which is required for any claim.



EU | Sealey EU Ltd, Farney Street, Carrickmacross, Co. Monaghan, A81 PK68 Ireland UK | Sealey Group, Kempson Way, Suffolk Business Park, Bury St Edmunds, Suffolk. IP32 7AR

01284 757500 sales@sealey.co.uk www.sealey.co.uk

#### **Documents / Resources**



<u>SEALEY 9007 P3R Particulate Filter</u> [pdf] User Manual 9007 P3R Particulate Filter, 9007, P3R Particulate Filter, Particulate Filter, Filter

#### References

User Manual

Manuals+, Privacy Policy

This website is an independent publication and is neither affiliated with nor endorsed by any of the trademark owners. The "Bluetooth®" word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. The "Wi-Fi®" word mark and logos are registered trademarks owned by the Wi-Fi Alliance. Any use of these marks on this website does not imply any affiliation with or endorsement.