



# SecuRAM ProLogic Smart Safe Lock Instructions

[Home](#) » [SecuRAM](#) » SecuRAM ProLogic Smart Safe Lock Instructions

## Contents [ [hide](#) ]

- [1 SecuRAM ProLogic Smart Safe Lock](#)
- [2 STANDARD FEATURES](#)
- [3 CHANGING YOUR CODE](#)
- [4 CHANGING YOUR BATTERY](#)
- [5 Documents / Resources](#)
- [6 Related Posts](#)

# SECURAM

## SecuRAM ProLogic Smart Safe Lock



## STANDARD FEATURES

- WRONG TRY PENALTY

- Four (4) consecutive invalid codes initiates five minute delay period.

- **LOW BATTERY WARNING**

- Repeated audio and visual signal (LED flashing and repeated beeping) during opening indicates low battery.

- **AUDIO AND VISUAL SIGNAL**

- Double signal (LED flashes and unit beeps) indicates code entry is valid or accepted.
- Triple signal indicates code is invalid or not accepted.

## **OPENING THE LOCK**

1. Enter the valid six (6) digit code.
2. The lock will indicate a valid code entry with a double signal.
3. Within four (4) seconds, turn handle to the open position.
4. Pull door open.
5. Invalid code entry – Lock will signal three (3) times.

## **CHANGING YOUR CODE**

### **ALWAYS PERFORM THIS OPERATION WITH THE DOOR OPEN**

1. Enter “zero” six times.
2. Enter your existing six (6) digit code one time.
3. Enter your NEW six (6) digit code two times.
4. If a mistake is made wait thirty (30) seconds and repeat steps 1 – 3.
5. Test lock operation several times before closing door.

**VALID CODE ENTRY-** Double signal after valid six (6) digit code is entered

**INVALID CODE ENTRY-** Triple signal and old code still valid.

## **CHANGING YOUR BATTERY**

1. Slide the keypad housing up and carefully pull away from front of safe  
**CAUTION:** Do not over-stretch the wire this could cause damage!
2. Remove the 9 volt ALKALINE battery and replace with a new one. The connector is easily unclipped from the battery and reconnected.
3. Carefully position the keypad back onto the mounting pegs, ensuring you do not crush the wire and slide firmly back into position.

We recommend that your safe is serviced at regular intervals, 12 – 18 months would be the optimum period if the safe is used daily. Failure to service your safe may eventuate in an expensive breakdown, to avoid this please have your safe checked.

To have your safe serviced, please contact your supplier to arrange a time to suit you.

## **Documents / Resources**

**SecuRAM ProLogic Smart Safe Lock** [pdf] Instructions  
ProLogic, ProLogic Smart Safe Lock, Smart Safe Lock, Safe Lock.