



## SELECT HINGES SL31 Geared Continuous Hinge User Guide

[Home](#) » [SELECT HINGES](#) » SELECT HINGES SL31 Geared Continuous Hinge User Guide 

### Contents

- [1 SELECT HINGES SL31 Geared Continuous Hinge](#)
- [2 Mounting](#)
- [3 SELECT ADVANTAGES](#)
  - [3.1 MEETS LEED REQUIREMENTS](#)
  - [3.2 SELECT HINGE PERFORMANCE](#)
- [4 Important Warranty Information](#)
- [5 Documents / Resources](#)
  - [5.1 References](#)
- [6 Related Posts](#)




**SELECT HINGES SL31 Geared Continuous Hinge**




**Mounting**



**LOAD/FREQUENCY RATING:** For 1-3/4" doors. 48" max. door width in 16 gauge hollow metal (min.) or 1/8" aluminum (min.).




**Heavy Duty** — Tested per BHMA standards. Up to 200 lb. doors (high-frequency) and up to 400 lb. doors (medium-frequency) without frame or door reinforcement; up to 600 lb. doors (low-frequency) with the use of Rivnuts in the frame and door.



**CLOSERS:** Conventional overhead surface, concealed sliding arm overhead or floor closers may be used with SELECT hinges. Pivot-type floor closers (with a fixed, conflicting center pivot) must be replaced.

**ORDER:** Specify length, finish and heavy duty (HD). Also, specify door and frame screw applications. 12-24 x 3/4"

self-drilling, thread-forming 410SS Phillips undercut flathead screws are provided as a standard pack unless otherwise specified. Wood and thread-forming screws also available. Security screws optional at extra cost.



**AVAILABLE ELECTRIC PREPS:** EPT, ATW, EMS, CMG, AP and RP.  
**BHMA CERTIFICATION:** SL31HD geared continuous hinges conform to BHMA Standard ANSI/BHMA A156.26-2006 Grade 1.


SL31 HINGE SCREW COUNT		
HINGE LENGTH & DUTY RATING	DOOR SCREWS	FRAME SCREWS
83" HD	19	19
95" HD	21	21

SELECT ADVANTAGES



**PAIR-MATCHED™ HINGE LEAVES**  
Manufactured together, machined together and anodized together, making SELECT hinges fit your doors better

and last longer. An exclusive SELECT benefit.



#### **LIFETIME LUBRICATION**

Eliminates the need for periodic maintenance. Quiet performance. Fights gear cap wear. An exclusive SELECT benefit.



#### **ANODIZED AFTER MACHINING**

Delivers superior wear, durability and life. Inhibits corrosion. Few hinge makers follow SELECT's lead in using this superior manufacturing process.




#### **MEETS LEED REQUIREMENTS**

Made from recycled aluminum. Reduces environmental impact and qualifies for LEED points. An exclusive SELECT benefit.



### **PATENTED 3-HR. FIRE RATING**

Most SELECT hinges are fire rated for 90 minutes. 3-Hr. fire rating, optional at extra cost, approved for positive/negative pressure. No fire pins or studs required. Patented design innovation. An exclusive SELECT benefit.



### **CONSISTENT TEMPLATING**

Hole pattern is identical on both Standard and Heavy Duty models, so SELECT hinges line up precisely for easier and faster installation. An exclusive SELECT benefit.



## COATED FASTENERS

Provide additional corrosion protection with either self-drilling, thread-forming (SDTF) or thread-forming (TF) screws. An exclusive SELECT benefit.




## CUSTOM COLORS


Match any paint color on the gear cap or the entire hinge and fasteners, including our always-in-stock Bone White gear caps. Anodized colors also available.

## SELECT HINGE PERFORMANCE

- A SELECT geared continuous hinge has been tested in accordance with ANSI 250.4-1994 test procedure and acceptance criteria for physical endurance for steel doors and hardware and has surpassed 25,000,000 cycles during testing by an independent laboratory. On a door cycling 400,000 times per year, a SELECT hinge will be performing for over 62 years.
- SELECT geared continuous hinges are built to handle abuse from high-traffic applications. They are applied to the surface on the edge of the frame and door. No machining or reinforcement is required.
- The revolutionary SELECT geared continuous hinge puts an end to costly and irritating hinge failure problems, the most common cause of entrance failure.
- On conventional hinges, opening and “kick-back” energy concentrate on a few inches of fastened reinforcing plate — with the top hinge handling 100% of the force. Pin less SELECT hinges bond the door and frame into an integrated, sag-free unit. “Kick-back” energy dissipates along the entire length of the door and frame. (Compare this to a conventional hinge’s 4-1/2” to 5” at the top of the door and frame).
- SELECT geared continuous hinges eliminate the gap between the door and frame, providing a weatherproof, rust-proof, tamper-proof barrier. When the door is closed, there are no accessible screws, bolts or pins.
- SELECT SL31 geared continuous hinges are listed and tested by Underwriters Laboratories to meet the Positive and Negative pressure requirements of UL10B and UL10C, and are in accordance with UBC 7.2 (1997). SELECT SL31 geared continuous hinges are for use on swinging single fire doors (max. door opening of 4’x10’) or pairs of fire doors (max. door opening of 8’x10’), including double egress, installed in masonry or drywall. SELECT SL31 geared continuous hinges are rated for up to 1-1/2 hours for wood composite and wood core type fire doors. A special patented process can be added to increase the fire rating to 3 hours (NO FIRE PINS OR STUDS REQUIRED) for hollow metal or steel covered composite type doors.







**NOTE:** For double-door entrances with a mullion between the pair of doors, calculate each door width using the Single Door clearances. For double-door entrances with a mullion behind the pair of doors, calculate each door width using the Double Doors clearances.

### Tools Needed

- Metal-cutting saw
- Tape measure
- #13 or 3/16" drill bit
- 5/32" drill bit (wood frames/doors)
- #3 Phillips drive
- Shims

### Parts Supplied


- #12-24 self-drilling, thread-forming (SDTF) 410 SS Phillips undercut flathead screws

### Optional Parts

- #12 410 SS Phillips undercut flathead wood screws
- #12-24 thread-forming (TF) 410 SS Phillips undercut flathead screws
- Protective gloves are recommended

## How to Cut the Hinge to Fit


- Keep hinge in “door closed” position.



- Determine whether this will be a right-hand or left-hand installation.  
**IMPORTANT:** Cut only one end of hinge. Cut end will be installed at the bottom. Keep original templated six-hole pattern at top end of hinge.  
**NOTE:** SL11, SL27 and SL38 are non-handed and remain non-handed after cutting.
- Using a metal-cutting saw, begin the cut through the gear cap first.  
**NOTE:** DO NOT cut through a set screw bearing.
- Reinstall any set screw bearing that may have been cut off.

### Prepare Frame

1. Shim hinge to 1/8" below the header to allow for door clearance.
2. Hold hinge in “door open” position ,



making sure frame leaf alignment flange is tight against frame face.

3. Mark (or centerpunch) hole locations.

**NOTE:** TF screws and screws require pilot holes at marked locations. SDTF screws do not require pilot holes.


4. If using SDTF screws, go to Step 5. If using TF or wood screws, drill holes at marked locations. DO NOT attach hinge to the frame at this time.
  - Metal frame: Use #13 (.185") bit or 3/16" (.188") bit
  - Wood frame: Use 5/32" (.156") bit

#### **Attach Door to Hinge**

5. Align the door leaf alignment flange or the door leaf lip along full length of door edge (even if door is slightly warped).

**IMPORTANT:** Top end of the hinge must be flush with the top of the door.

- If installing hinge on a minute fire-rated wood door, mark or centerpunch only one hole in each pair of holes at the top and bottom of the door leaf. DO NOT install remaining screws in the six-hole pattern on the door leaf. See illustration below.




6. Mark (or centerpunch) holes. If using SDTF screws, go to Step 7. If using TF or wood screws, drill holes at

marked locations.

- Metal door: Use 13 (.185") bit or 3/16" (.188") bit
- Wood door: Use 5/32" (.156") bit

7. Fasten door leaf to door using #3 Phillips drive and fasteners provided.

#### **Attach Door to Frame**



8. Position door at 90 degrees to the frame. Shim door to the proper height so the door aligns with the top screw holes.
9. Install two screws at the top of hinge. Remove shim and align remaining holes. Install screws in middle and bottom two holes.
10. Check door for proper swing and clearance before installing remaining screws.

#### **Reinforcing & Rivnuts®**

No hinge reinforcement is necessary except on extremely high-frequency, extremely heavy or extra-wide doors. Rivnuts are recommended for use in the frame when the door exceeds 450 lb. (max. 600 lb.).

**NOTE:** Only SELECT steel Rivnuts are to be used with fire-rated SELECT hinge.

#### **Grouted/Slushed-in Frames**

For ease of installation, it is recommended some sort of mudguard be installed behind the frame. Do not use self-drilling, thread-forming (SD) to drill into grouted frames. If mudguards have not been used, carefully drill pilot holes through frame and remove grout for screw clearance. Do not oversize holes in frame.


#### **Fire-Rated Hinges**

All stock SELECT hinges are 90-minute UL-rated, without pins. Please contact SELECT for complete information about its fire-rated hinges.

Ph: 800-423-1174

Fax: 800-423-7107

## Documents / Resources

	<p><b><a href="#">SELECT HINGES SL31 Geared Continuous Hinge</a></b> [pdf] User Guide</p> <p>SL31 Geared Continuous Hinge, SL31, Geared Continuous Hinge, Geared Continuous Hinge, Continuous Hinge, Hinge</p>
---	--

## References

-  [Warranties & Ratings - SELECT Hinges](#)

Manuals±.