



Sercomm Z-Wave Smart Chime (Sound Switch) SW-SCM01N Manual

[Home](#) » [Sercomm](#) » Sercomm Z-Wave Smart Chime (Sound Switch) SW-SCM01N Manual 



Contents

- 1 Sercomm
- 2 Z-Wave Smart Chime (Sound Switch)
 - 2.1 SKU: SW-SCM01N
 - 2.2 Quickstart
 - 2.3 Important safety information
 - 2.4 What is Z-Wave?
 - 2.5 Product Description
 - 2.6 Prepare for Installation / Reset
 - 2.6.1 Reset to factory default
 - 2.6.2 Safety Warning for Mains Powered Devices
 - 2.7 Inclusion/Exclusion
 - 2.7.1 Inclusion
 - 2.7.2 Exclusion
 - 2.8 Quick trouble shooting
 - 2.9 Association – one device controls an other device
 - 2.9.1 Association Groups:
 - 2.10 Technical Data
 - 2.11 Supported Command Classes
 - 2.12 Explanation of Z-Wave specific terms
 - 2.13 Related Posts

Z-Wave Smart Chime (Sound Switch)

SKU: SW-SCM01N



Quickstart

This is a
secure
Sound Switch
for
U.S. / Canada / Mexico.

To run this device please connect it to your mains power supply.

To add this device to your network execute the following action:

Auto inclusion:1. Follow your Z-Wave controller's instructions on how to put the controller into "Add" mode.2.
Power on the device.3. The LED will blink during the inclusion process. This process may take up to 4 minutes.4.
If the device is successfully added to the network, the LED will turn off. The device will return to normal
operation.If the process fails, try repeating steps 1 – 3 again.Manual inclusion:1. Follow your Z-Wave controller's

instructions on how to put the controller into “Add” mode.2. Press the Paring button once to put the device into inclusion mode.3. The LED will blink during the inclusion process. This process may take up to 4 minutes.4. If the device is successfully added to the network, the LED will turn off. The device will return to normal operation.If the process fails, try repeating steps 1 – 3 again.

Please refer to the [Manufacturers Manual](#) for more information.

Important safety information

Please read this manual carefully. Failure to follow the recommendations in this manual may be dangerous or may violate the law.

The manufacturer, importer, distributor and seller shall not be liable for any loss or damage resulting from failure to comply with the instructions in this manual or any other material.

Use this equipment only for its intended purpose. Follow the disposal instructions.

Do not dispose of electronic equipment or batteries in a fire or near open heat sources.

What is Z-Wave?

Z-Wave is the international wireless protocol for communication in the Smart Home. This device is suited for use in the region mentioned in the Quickstart section.

Z-Wave ensures a reliable communication by reconfirming every message (**two-way communication**) and every mains powered node can act as a repeater for other nodes (**meshed network**) in case the receiver is not in direct wireless range of the transmitter.



This device and every other certified Z-Wave device can be **used together with any other certified Z-Wave device regardless of brand and origin** as long as both are suited for the same frequency range.

If a device supports **secure communication** it will communicate with other devices secure as long as this device provides the same or a higher level of security. Otherwise it will automatically turn into a lower level of security to maintain backward compatibility.

For more information about Z-Wave technology, devices, white papers etc. please refer to www.z-wave.info.

Product Description

This device is a security enabled Z-Wave Plus product that is able to use encrypted Z-Wave Plus messages to communicate to other security enabled Z-Wave Plus products. This device must be used in conjunction with a Security Enabled Z-Wave Controller in order to fully utilize all implemented functions.

Prepare for Installation / Reset

Please read the user manual before installing the product.

In order to include (add) a Z-Wave device to a network it **must be in factory default state**. Please make sure to reset the device into factory default. You can do this by

performing an Exclusion operation as described below in the manual. Every Z-Wave controller is able to perform this operation however it is recommended to use the primary controller of the previous network to make sure the very device is excluded properly from this network.

Reset to factory default

This device also allows to be reset without any involvement of a Z-Wave controller. This procedure should only be used when the primary controller is inoperable.

1. Hold the Pairing button for 10 second until the LED lights up. 2. When LED turns off, all Z-Wave information will be cleared, the Node ID will be excluded from the device, and all settings will be reset to factory defaults. Note: Please use this procedure only when the network's primary controller is missing or otherwise inoperable.

Safety Warning for Mains Powered Devices

ATTENTION: only authorized technicians under consideration of the country-specific installation guidelines/norms may do works with mains power. Prior to the assembly of the product, the voltage network has to be switched off and ensured against re-switching.

Inclusion/Exclusion

On factory default the device does not belong to any Z-Wave network. The device needs to be **added to an existing wireless network** to communicate with the devices of this network. This process is called **Inclusion**.

Devices can also be removed from a network. This process is called **Exclusion**. Both processes are initiated by the primary controller of the Z-Wave network. This controller is turned into exclusion respective inclusion mode. Inclusion and Exclusion is then performed doing a special manual action right on the device.

Inclusion

Auto inclusion: 1. Follow your Z-Wave controller's instructions on how to put the controller into "Add" mode. 2. Power on the device. 3. The LED will blink during the inclusion process. This process may take up to 4 minutes. 4. If the device is successfully added to the network, the LED will turn off. The device will return to normal operation. If the process fails, try repeating steps 1 – 3 again. Manual inclusion: 1. Follow your Z-Wave controller's instructions on how to put the controller into "Add" mode. 2. Press the Pairing button once to put the device into inclusion mode. 3. The LED will blink during the inclusion process. This process may take up to 4 minutes. 4. If the device is successfully added to the network, the LED will turn off. The device will return to normal operation. If the process fails, try repeating steps 1 – 3 again.

Exclusion

1. Follow your Z-Wave controller's instructions on how to put the controller into "Remove" mode. 2. Press the Pairing button once. 3. The LED will blink for one second while the device is being removed from the network. 4. If the device was successfully removed from the network, all Z-Wave information will be cleared, and the Node ID will be excluded from the device.

Quick trouble shooting

Here are a few hints for network installation if things don't work as expected.

1. Make sure a device is in factory reset state before including. In doubt exclude before include.
2. If inclusion still fails, check if both devices use the same frequency.
3. Remove all dead devices from associations. Otherwise you will see severe delays.
4. Never use sleeping battery devices without a central controller.

5. Dont poll FLIRS devices.
6. Make sure to have enough mains powered device to benefit from the meshing

Association – one device controls an other device

Z-Wave devices control other Z-Wave devices. The relationship between one device controlling another device is called association. In order to control a different device, the controlling device needs to maintain a list of devices that will receive controlling commands. These lists are called association groups and they are always related to certain events (e.g. button pressed, sensor triggers, ...). In case the event happens all devices stored in the respective association group will receive the same wireless command wireless command, typically a 'Basic Set' Command.

Association Groups:

Group NumberMaximum NodesDescription

1	5	All triggering report will be sent to the associated nodes.
---	---	---

Technical Data

Hardware Platform	ZM5101
Device Type	Sound Switch
Network Operation	Always On Slave
Firmware Version	HW: 1 FW: 1.09
Z-Wave Version	6.71.03
Certification ID	ZC10-18096238
Z-Wave Product Id	0x0151.0x0301.0x0001
Firmware Updatable	Updatable by Consumer via Internet
Color	White
Communications Protocol	Manufacturer Proprietary Protocol
Security V2	S2_UNAUTHENTICATED ,S2_AUTHENTICATED
Frequency	XXfrequency
Maximum transmission power	XXantenna

Supported Command Classes

- Association Grp Info
- Association V2
- Basic
- Device Reset Locally
- Firmware Update Md V4
- Manufacturer Specific V2
- Multi Cmd

- Powerlevel
- Security
- Security 2
- Sound Switch
- Supervision
- Transport Service V2
- Version V3
- Zwaveplus Info V2

Explanation of Z-Wave specific terms

- **Controller** — is a Z-Wave device with capabilities to manage the network.
Controllers are typically Gateways, Remote Controls or battery operated wall controllers.
- **Slave** — is a Z-Wave device without capabilities to manage the network.
Slaves can be sensors, actuators and even remote controls.
- **Primary Controller** — is the central organizer of the network. It must be a controller. There can be only one primary controller in a Z-Wave network.
- **Inclusion** — is the process of adding new Z-Wave devices into a network.
- **Exclusion** — is the process of removing Z-Wave devices from the network.
- **Association** — is a control relationship between a controlling device and a controlled device.
- **Wakeup Notification** — is a special wireless message issued by a Z-Wave device to announces that is able to communicate.
- **Node Information Frame** — is a special wireless message issued by a Z-Wave device to announce its capabilities and functions.