



SERVER IS 1 IntelliServ 1/3 Size Pan Warmer Instruction Manual

[Home](#) » [SERVER](#) » SERVER IS 1 IntelliServ 1/3 Size Pan Warmer Instruction Manual 

Contents

- 1 SERVER IS 1 IntelliServ 1/3 Size Pan Warmer
- 2 UNIT SET-UP
- 3 SAFETY
- 4 RETHERMALIZATION
- 5 HOT FOOD HOLDING
- 6 UNIT TAKE-DOWN
- 7 CLEANING
- 8 REMOVE LIMESCALE
- 9 CARE OF STAINLESS STEEL
- 10 CONTROL FUNCTIONS
- 11 WIRING
- 12 ACCESSORY ITEMS
- 13 TROUBLESHOOTING
- 14 GENERAL SERVICE, REPAIR OR RETURNS
- 15 NEED HELP?
- 16 Documents / Resources
 - 16.1 References
- 17 Related Posts




SERVER IS 1 IntelliServ 1/3 Size Pan Warmer



UNIT SET-UP

FILL UNIT BASIN WITH WATER




Fill 1 liter of water up to fill-line-ridge inside basin.

TIP:

- Check water levels throughout the holding period to ensure even heating.
- Filtered water is recommended to deter corrosion.

PUT PAN(S) INTO BASIN



- The product being served must always be inside pan(s). Never place food directly into basin of unit.
- **TIP:** Food pan(s) not included— modular design lets you choose pan(s), pump(s) or high-temp squeeze bottles for your food application.

3 PLUG CORD

into power source.

4 PRESS POWER BUTTON


to turn unit on.

UNITS WITH 230 VOLTS
also have a power switch.
Press to ON position.

5 SET THERMOSTAT

to recommended
serving temperature.

- Press Down ▼ or Up ▲ buttons to set temperature.
- See page 6 for control function details.



SAFETY



WARNING- **ELECTRICAL SHOCK COULD OCCUR**

This unit must be earthed or grounded.

This requires all three prongs (terminals) on cord
plug to be plugged into power source.

- According to food and safety regulations, most foods must be stored and/or served at certain temperatures or they could become hazardous. Check with local food and safety regulators for specific guidelines.
- Be aware of the product you are serving and the temperature the product is required to maintain. Server Products, Inc. can not be responsible for the serving of potentially hazardous product.

RE THERMALIZATION

Rethermalization of food products is achieved by this appliance when it elevates the food product temperature from a refrigerated 40°F (4°C) to a safe serving temperature of 165°F (74°C) within a period of 2 hours.

PRE-HEAT UNIT

for at least 5 minutes with:

- Correct amount of water in basin.
- Lid(s) closed.
- Temperature set at maximum setting.

ADD FOOD PRODUCT

- Put food into pans.
- Do not overfill.

HOT FOOD HOLDING

Hot Food Holding is achieved with this appliance when it maintains a food product temperature at or above 150°F (66°C), in all locations throughout the product, for a minimum of 2 hours, even if any lid, cover, or pump is removed. The lid, cover, or pump is recommended to help maintain product temperature.

PRE-HEAT UNIT

for at least 5 minutes with:

- Correct amount of water in basin.
- Lid(s) closed.
- Temperature set at maximum setting.

ADD FOOD PRODUCT

- Put food which has already been preheated to 150°F (66°C) into pans.
- Do not overfill.

MAINTAIN SAFE HOT FOOD HOLDING

- After food reaches safe serving temperature of 165°F (74°C), maintain product temperature at or above 150°F (66°C).
- Adjust controller if needed to avoid overheating food.

MONITOR FOOD CLOSELY FOR FOOD SAFETY.


The United States Public Health Service recommends that hot food be held at a minimum of 140°F (60°C) to help prevent bacteria growth

COLD FOOD IS NOT TO BE ADDED TO THE UNIT FOR RETHERMALIZATION WHILE HOT FOOD IS BEING HELD.

UNIT TAKE-DOWN

- 1 PRESS POWER BUTTON**
to turn unit off.

UNITS WITH 230 VOLTS
also have a power switch.
Press to OFF position.




- 2 UNPLUG CORD**

- 3 REMOVE PAN(S) FROM BASIN**



CAUTION- HOT
Allow unit to cool before continuing.



4**EMPTY WATER FROM BASIN**

after each use.


***TIP:** Remember to **empty** the water each day rather than **add**—*

This will greatly extend the life of your warmer.

5**DRY**

thoroughly with a soft dry cloth.

Proper drying after each use helps maintain the heat plate and the stainless steel.

**CLEANING****WARNING-**

ELECTRICAL SHOCK COULD OCCUR

- Electrical components of unit could be damaged from water exposure or any liquid.
- Never immerse unit into water or any liquid.
- Never use any water jet or pressure sprayer on unit.
- Ensure unit is “OFF” and unplugged.

CAUTION- HOT

Allow unit to cool before cleaning.

REMOVE LIMESCALE

RECOMMENDED ONCE A MONTH OR AS NEEDED: Use a non-corrosive limescale remover to eliminate mineral buildup on the interior of the basin.

This will greatly extend the life of your warmer.

AFTER TREATMENT:

Clean thoroughly with soap and hot water.

Prolonged exposure to caustic chemicals can negatively affect the performance of the heat plate.

CLEAN

- Before first use and after use daily, disassemble and clean unit.
- Ensure unit is “OFF” and unplugged.
- Wash with dishwashing soap and hot water.
- Do not use abrasive brushes or pads on the heat plate. Scratching the heat plate surface would compromise the Teflon™ coating. Teflon is a registered trademark of the Chemours Company.

RINSE fully with clear water.

SANITIZE all parts according to local sanitization requirements. All parts in contact with food must be sanitized.

DRY all parts fully with a clean soft cloth.

CLEAN EXTERNAL SURFACES

- Wipe daily with a clean damp cloth.
- Dry with a clean soft cloth.
- Glass and surface cleaners approved for use in food contact areas may be used.

CARE OF STAINLESS STEEL

This warmer is constructed of stainless steel— one of the best materials for food serving and storage. If you notice corrosion beginning on any stainless steel surface, you may need to change the cleansing agent, sanitizing agent, or cleaning procedures you are using.

- Fully rinsing and drying all parts can help prevent corrosion. Elements and minerals in tap water can accumulate on stainless steel parts and create corrosion.
- Do not use abrasive, caustic or ammonia-based cleansers.
- Do not use products containing acids, alkalines, chlorine, or salt. These agents can corrode stainless steel.
- Do not use metal scrapers or cleaning pads that could scratch surfaces.

CONTROL FUNCTIONS

DISPLAY MESSAGES

COL

COL = COOL
Heating element is off and cooling down to set temperature.

P-r-E

PRE = HEAT
Heating element is on and warming up to set temperature.

E-r-r

ERR = ERROR
Control board is not functioning. Repair is required.
(Please see page 12 for repairs.)

Temperature differential between cool and heat is 10°F (5.5°C) of set temperature.
Display will switch between control functions and set temperature until unit stabilizes.

DOWN & UP BUTTONS

Press and hold the Down or Up buttons to cycle through temperature range.

TEMPERATURE RANGES

For most units: 100°F (37°C)—220°F (104°C)

For unit 86254: 135°F (57°C)—220°F (104°C)


POWER BUTTON On/Off

HEATING INDICATOR

Light indicates heating element is active.

CELSIUS INDICATOR

Light indicates temperature display mode is °C.
No light indicates temperature display mode is °F.




TO SET DISPLAY °F OR °C

- Turn unit off.
- Press and hold Down button, then simultaneously press and hold Power button for 30 seconds.
- Celsius indicator will activate to display °C or deactivate to display °F.



WIRING

- UNITS 86090, 86254, 86481, 100419 (120V)
- UNIT 86479 (100V JAPAN)
- UNITS 86338, 86339, 86341 (CONT. EURO, AU, UK)
- UNIT 86478 (230V BRAZIL)



1. Cord Assembly 230V
 - Blue
 - Brown
 - Yellow/Green
2. Bushing/Strain Relief
3. Rocker Switch
4. White Wire Assembly
5. Black Wire Assembly
6. White Wire Assembly
7. 500W Heating Element
8. Black Wire Assembly
9. Bushing
10. Thermistor Assembly
11. Temperature Controller

ACCESSORY ITEMS



TROUBLESHOOTING

UNIT DOES NOT HEAT?

- Ensure cord is securely plugged in.
- Ensure power is available from source.
- Ensure unit is on.
- Ensure thermostat is set correctly.
- Ensure that the correct amount of water is in basin.

UNIT TRIPS THE BREAKER? (GROUND FAULT INTERRUPTER)

- Never expose electrical components to water or liquid. This may result in damage. Unit may not function.
If electrical components have gotten wet:
 - Turn off unit and unplug.
 - Allow unit to dry completely.

SERVER PRODUCTS LIMITED WARRANTY

2 YEAR WARRANTY

Server Products equipment is backed by a two-year limited warranty against defects in materials and workmanship.

For complete warranty information go to:

www.Server-Products.com

GENERAL SERVICE, REPAIR OR RETURNS

Before sending any item to Server Products for service, repair, or return, contact Server Products customer service to request a Return Authorization Number. Merchandise must be sent to Server Products with this number. Service is extremely prompt. Typically, units are repaired and ship out within 48 hours. Merchandise being returned for credit must be in new and unused condition and not more than 90 days old and will be subject to a 20% restocking charge. Electrical parts (thermostats, heating elements, etc.) are not returnable.


Servicing Cord: Specific tools are required for safe and proper power supply cord removal and installation. If cord must be replaced, only a representative of the OEM (original equipment manufacturer) or a qualified technician may replace cord. Cord must meet code designation H05 RN-F requirements.

NEED HELP?

- Server Products Inc.
- 3601 Pleasant Hill Road
- Richfield, WI 53076 USA
- 262.628.5600 | 800.558.8722
- SPSALES@SERVER-PRODUCTS.COM

Please be prepared with your Model, Part and Series Numbers. This information and other important data is located on the base of the unit.

Documents / Resources

| | |
|---|--|
|  | <p>SERVER IS-1 IntelliServ 1/3-Size Pan Warmer [pdf] Instruction Manual IS-1, IntelliServ 1-Size Pan Warmer, IntelliServ 3-Size Pan Warmer</p> |
|---|--|

References

- products.com
- [Server Products](#)

