



SHARPER IMAGE BS6-G40-CC 6ct Led G40 Globe String Lights Color Changing Instruction Manual

[Home](#) » [Sharper Image](#) » SHARPER IMAGE BS6-G40-CC 6ct Led G40 Globe String Lights Color Changing Instruction Manual 

Contents

- [1 SHARPER IMAGE BS6-G40-CC 6ct Led G40 Globe String Lights Color Changing](#)
- [2 INSTALLATION INSTRUCTIONS](#)
- [3 Documents / Resources](#)
- [4 Related Posts](#)

SHARPER IMAGE®

SHARPER IMAGE BS6-G40-CC 6ct Led G40 Globe String Lights Color Changing



INSTALLATION INSTRUCTIONS

IMPORTANT: Review important safety instructions before installation.

WARNING: When used outdoors basic safety precautions should always be followed to reduce the risk of fire, electric shock and personal injury. Install in accordance with these instructions and current electrical codes such as the National Electric Code (NEC).

When used outdoors in wet locations, Ground Fault Circuit Interrupter protection (GFCI) is to be provided on the circuits or outlets. Extension cords rated for outdoor use must be used, such as type: SEW, SEOW, SOW, SOOW, STW, STOW, SJEW, SJEOW, SJEOOW, SJW, SJOW, SJOOW, SJTW, SJTOW or SJTOOW. The receptacle cover should always be in place to prevent the entry of water (unless a plug is inserted).

Caution: Rise of electric shock. Avoid making connections or disconnections when the equipment is wet. Do not use with extension cord near water or where water may accumulate. Do not submerge. Keep lamps at least 3.6m/12ft from pools and spas. Keep receptacles dry.

CAUTION: To reduce the risk of fire, electric shock or injury to persons:


1. LED Dip String Lights is intended for installation by trained, qualified, electrical contractors.
2. String Lights must be supported by suitable supporting hardware such as s-hooks, screw hooks, or zip ties (not included) whenever span distances exceed 12 feet. Proper diameter cabling must be used according to local building codes. See Installation Methods on revers.
3. Light sockets must be installed base up so that bulbs are facing down ONLY.
4. Keep combustible material clear of bulbs. Do NOT allow lamps or sockets to come into contact with walls, ceilings, fabrics associated with shades, blinds or other material. Lamps should hang freely in a downward direction with a minimum of 3 inch space from the nearest object.
5. Do not cluster the bulbs.
6. Not intended for installation in ceilings, soffits, cabinets or other enclosed spaces.

- 7. Do NOT secure light string to buildings or other structural supports using nails, staples or other sharp, conducting materials. DO NOT DAMAGE THE WIRE.
- 8. Avoid damage to the insulation during installation. Do NOT pierce or otherwise compromise wire's or sockets outer covering, jacket or sheathing.
- 9. Periodically inspect wire and sockets for degradation due to weather, UV light or other damage. Promptly replace worn out light string.
- 10. DO NOT OVERLOAD ANY SOCKETS MAXIMUM WATTAGE RATING!

WARNING: RISK OR ELECTRIC SHOCK

Disconnect power at source prior to wiring, replacing light bulbs or servicing in any way.

Documents / Resources

	<p>SHARPER IMAGE BS6-G40-CC 6ct Led G40 Globe String Lights Color Changing [pdf] Inst ruction Manual</p> <p>BS6-G40-CC 6ct Led G40 Globe String Lights Color Changing, BS6-G40-CC, 6ct Led G40 Glo be String Lights Color Changing, String Lights Color Changing, Color Changing, Changing</p>
---	--