



# SHURE A2WS-BLK Locking Microphone Windscreen Instruction Manual

[Home](#) » [Shure](#) » SHURE A2WS-BLK Locking Microphone Windscreen Instruction Manual 

## Contents

- [1 SHURE A2WS-BLK Locking Microphone Windscreen](#)
- [2 Product Information](#)
- [3 Specifications](#)
- [4 Product Usage Instructions](#)
- [5 Frequently Asked Questions \(FAQ\)](#)
- [6 General Description](#)
- [7 Installation](#)
- [8 Documents / Resources](#)
  - [8.1 References](#)
- [9 Related Posts](#)

# SHURE

**SHURE A2WS-BLK Locking Microphone Windscreen**



## Product Information

The Shure Model A2WS Windscreen is designed to reduce unwanted breath and wind noise in close talk and outdoor applications. It effectively prevents pops and ticks when a talker or performer speaks or sings closely into the microphone, and also shields the microphone from rushing and whistling sounds in adverse wind conditions. The A2WS is compatible with both hand-held and stand-mounted SM57 and 545 Series microphones. It is available in two colors: gray (A2WS-GRA) and black (A2WS-BLK).

## Specifications

- **Type:** Windscreen
- **Compatibility:** SM57 and 545 Series microphones
- **Colors:** Gray (A2WS-GRA) and Black (A2WS-BLK)

## Product Usage Instructions

### Installation

1. Before installation, ensure that the windscreen matches the model of your microphone (SM57 or 545 Series).
2. Locate the setscrew on the windscreen. Note that the setscrew connects to the bushing rather than the microphone body.
3. Hold the windscreen with one hand and gently twist it onto the microphone's grill using the other hand. Make sure it is securely fastened.

### Close Talk Applications

When using the A2WS Windscreen for close talk applications, follow these guidelines:

1. Position the microphone approximately 1-2 inches away from the talker's mouth.
2. Ensure that the talker speaks directly into the front of the microphone.
3. Adjust the microphone angle and distance as needed to achieve optimal sound quality.

## Outdoor Applications

When using the A2WS Windscreen for outdoor applications, follow these guidelines:

1. Position the microphone close to the sound source while considering the wind direction.
2. Place the windscreen between the microphone and the sound source, ensuring it covers the entire grill area.
3. Adjust the microphone angle and distance as needed to achieve optimal sound quality.

## Frequently Asked Questions (FAQ)

### **Q: Can I use the A2WS Windscreen with other microphone models?**

A: The A2WS Windscreen is specifically designed for use with SM57 and 545 Series microphones. It may not fit or function properly with other models.

### **Q: Is the A2WS Windscreen compatible with both hand-held and stand-mounted microphones?**

A: Yes, the A2WS Windscreen is compatible with both hand-held and stand-mounted SM57 and 545 Series microphones.


## General Description

Use the Shure Model A2WS Windscreens to attenuate unwanted breath and wind noise in closetalk and outdoor applications. It prevents annoying pops and ticks when a talker or performer speaks or sings closely into the microphone and shields the microphone from rushing and whistling sounds in adverse wind conditions. Effective and rugged, the A2WS fastens securely to both hand-held and stand-mounted SM57 and 545 Series microphones. It is available in gray (A2WS-GRA) and black (A2WS-BLK).

## Installation

1. Slip the windscreen over the microphone until the inside of the windscreen barely makes contact.
2. Move the windscreen 3 to 6 mm (1/8 to 1/4 in.) away from the microphone top.
3. Tighten the setscrew to securely fasten the windscreen. Note that the setscrew connects to the bushing rather than the microphone body.

## Documents / Resources

	<p><b><a href="#">SHURE A2WS-BLK Locking Microphone Windscreen</a></b> [pdf] Instruction Manual A2WS-BLK Locking Microphone Windscreen, A2WS-BLK, Locking Microphone Windscreen, M icrophone Windscreen, Windscreen</p>
---	---

## References

- [User Manual](#)

