



SIIG 1×2 mDP 1.2 DisplayPort MST Splitter User Guide

[Home](#) » [SIIG](#) » SIIG 1×2 mDP 1.2 DisplayPort MST Splitter User Guide 



Contents

- [1 SIIG 1×2 mDP 1.2 DisplayPort MST Splitter User Guide](#)
- [2 Features](#)
- [3 Package contents](#)
- [4 System Requirements](#)
- [5 Notice](#)
- [6 Documents / Resources](#)
- [7 Related Posts](#)

SIIG 1×2 mDP 1.2 DisplayPort MST Splitter User Guide



Dear Valued Customer (UST WANTED YOU TO KNOW) WE REALLY APPRECIATE YOUR PURCHASE

-Thank you-

Features

- Support Max one 4K@60Hz display, or two 3840×2160@30Hz display
- Support 7.1 ch surround audio
- Support AMD Eyefinity, Intel collage, NVIDIA Surround
- Plug-n-play, no software or driver installation needed

Package contents

- 1×2 mDP 1.2 to DisplayPort MST Splitter
- Micro USB power cable
- Quick Start Guide

System Requirements

- System and graphic card which support DP1.2&MST
- Windows 10 / 8.1 / 8 / 7 (32/64 bit)
- MST only support on Windows

Notice

- USB power is required. (5V/500mA)
- Use on DP 1.1 or Mac system will only support Splitter (SST) mode
- Please set monitor color bit depth to 8bit. 10bit or 12bit will spend more bandwidth may cause the bandwidth not enough.
- DP 1.2 4K@60 monitor have to setup to DP 1.1 mode for 4K@30 use.
- Every graphic card has different display support. Please confirm how many displays can output from your graphic card.



Support

Copyright© 2019 by SIIG, Inc. All rights reserved.

Read More About This Manual & Download PDF:

Documents / Resources

[illegible]