



## Contents [ [hide](#) ]

### 1 FUSERBLOC TS T1 4X250A FC

#### 1.1 Switch-discon-fuse FUSERBLOC-Cent Ext&Dir F OP-250A-4P-DINFuse S1

##### 1.1.1 Technical Characteristics

##### 1.1.2 Classification

##### 1.1.3 Commerce

##### 1.1.4 ETIM – Electrical characteristics

##### 1.1.5 ETIM – Mechanical characteristics

##### 1.1.6 ETIM – Technical features

##### 1.1.7 Logistics

##### 1.1.8 Norms

### 2 Documents / Resources

#### 2.1 References

## FUSERBLOC TS T1 4X250A FC

**38376024**

**Switch-discon-fuse FUSERBLOC-Cent Ext&Dir F OP-250A-4P-DINFuse S1**

### Strong points

- Improved safety
- High breaking capacity
- Multi-use
- Simplified use

## General characteristics

- For fuses up to 1250 A.
- 2P, 3P or 4P available.
- Up to 690 VAC.
- Up to 100 kA.
- Available in versions with right front-side, left side and central front operation handles.

## Compliance with standards

- IEC 60947-3
- IEC 60269-1
- IEC 60269-2

## Access to resources (ex: manuals)

FUSERBLOC NFC/DIN units are manually operated multipolar fuse load break switches. They provide make and break on load and safety isolation and protection against overcurrent for any low voltage electrical circuit.

This range is available in right front-side, left side and central front, direct or external operation, with 2, 3 and 4 poles and up to 1250 A.

## Technical Characteristics

Control operator	Direct : H12 / External : S2
Fuse size	NH1
Number of poles	4
Rated current [A]	250
Type	I-0-Test
Frame size	15

## Classification

UNSPSC	39122233
--------	----------

ETIM Class	EC001040
IGCC	5291

#### Commerce

Effective date	2002-12-19
Offer Life Cycle Code	40
Country of origin	FR

#### ETIM – Electrical characteristics

Max. rated operation voltage Ue AC [V]	690
Rated permanent current Iu [A]	250
Rated operation power at AC-23, 400 V [kW]	132
Conditioned rated short-circuit current Iq [kA]	100
Number of poles	4

#### ETIM – Mechanical characteristics

Cable entry	Top/bottom
Equipped with connectors	No
Suitable for floor mounting	Yes
Suitable for front mounting	Yes
Suitable for busbar mounting	No
Degree of protection (IP), front side	IP20

#### ETIM – Technical features

Version as main switch	Yes
Version as safety switch	Yes
Suitable for fuses	NH1
With error protection	No
Type of electrical connection of main circuit	Bolt connection
Type of control element	Long rotary handle
Position control element	Front side
Motor drive optional	No
Motor drive integrated	No
Version as emergency stop installation	Yes


#### Logistics

GTIN/EAN	3596031651856
Customs number	8536309000
Price unit	PC
Weight of the packing unit [kg]	18.925
Length of the packing unit [m]	0.34
Width of the packing unit [m]	0.203
Depth of the packing unit [m]	0.21

#### Norms

Conformity to standards	IEC
-------------------------	-----

# Documents / Resources



[socomec TS T1 4X250A FC Switch Discon Fuse \[pdf\]](#) Owner's Manual  
TS T1 4X250A FC Switch Discon Fuse, TS T1 4X250A FC, Switch Discon Fuse, Discon Fuse, Fuse

## References

- [User Manual](#)

Discon Fuse, Fuse, Socomec, Switch Discon Fuse, TS T1 4X250A FC, TS T1 4X250A FC Switch Discon Fuse

## Leave a comment

Your email address will not be published. Required fields are marked \*

Comment \*

Name

Email

Website

---

☐ Save my name, email, and website in this browser for the next time I comment.

**Post Comment**

**Search:**

e.g. whirlpool wrf535swhz

**Search**

[Manuals+](#) | [Upload](#) | [Deep Search](#) | [Privacy Policy](#) | [@manuals.plus](#) | [YouTube](#)

This website is an independent publication and is neither affiliated with nor endorsed by any of the trademark owners. The "Bluetooth®" word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. The "Wi-Fi®" word mark and logos are registered trademarks owned by the Wi-Fi Alliance. Any use of these marks on this website does not imply any affiliation with or endorsement.