

# **SONOFF POWR2 Diy Power Measuring Wi-Fi Switch User Manual**

**Home** » **SonOFF** » **SONOFF POWR2** Diy Power Measuring Wi-Fi Switch User Manual

SONOFF POWR2 Diy Power Measuring Wi-Fi Switch




# Contents [ hide

- 1 Operating Instruction
- 2 Power off
  - 2.1 Wiring instruction
  - 2.2 Download APP
  - 2.3 Power on
  - 2.4 Add the device
- 3 Compatible Pairing Mode
- **4 Specifications**
- **5 Product Introduction**
- 6 Wi-Fi LED indicator status instruction
- -
- 7 Features
- **8 Switch Network**
- **9 Factory Reset**
- **10 Common Problems**
- 11 Documents / Resources
- **12 Related Posts**

# **Operating Instruction**


Power off




 $\triangle$  To avoid electric shocks, please consult the dealer or a qualified professional for help when installing and repairing! Please do not touch the switch during use.

# Wiring instruction

• Light fixture wiring instruction:



• Appliance wiring instruction(Don't need to connect if no ground wire):




Make sure the neutral wire and live wire connection is correct.

#### **Download APP**




#### Power on



After powering on, the device will enter the quick pairing mode (Touch) during the first use. The Wi-Fi LED indicator changes in a cycle of two short and one long flash and release.

The device will exit the quick pairing mode (Touch) if not paired within 3mins. If you want to enter this mode, please long press the manual button for about 5s until the Wi-Fi LED indicator changes in a cycle of two short and one long flash and release.



Tap "+" and select "Quick Pairing", then operate following the prompt on the APP.

## **Compatible Pairing Mode**


If you fail to enter Quick Pairing Mode (Touch), please try "Compatible Pairing Mode" to pair.

- Long press Pairing button for 5s until the Wi-Fi LED indicator changes in a cycle of two short flashes and one long flash and release. Long press Pairing button for 5s again until the Wi-Fi LED indicator flashes quickly. Then, the device enters Compatible Pairing Mode.
- ② Tap "+" and select "Compatible Pairing Mode" on APP.
  Select Wi-Fi SSID with ITEAD-\*\*\*\*\*\* and enter the password 12345678, and then go back to eWeLink APP and tap "Next". Be patient until pairing completes.

## **Specifications**

| Model               | POWR2                    |
|---------------------|--------------------------|
| Input               | 100-240V AC 50/60Hz      |
| Output              | 100-240V AC 50/60Hz      |
| Max.Load            | 15A/3500W                |
| Wi-Fi               | IEEE 802.11 b/g/n 2.4GHz |
| Operating systems   | Android & iOS            |
| Working temperature | -10°C~40°C               |
| Material            | PC V0                    |
| Dimension           | 114x52x33mm              |

#### **Product Introduction**



The device weight is less than 1 kg.
The installation height of less than 2 m is recommended.

## Wi-Fi LED indicator status instruction

| Wi-Fi LED indicator status       | Status instruction                                 |
|----------------------------------|--|
| Flashes (one long and two short) | Quick Pairing Mode                                 |
| Keeps on                         | Device is connected successfully                   |
| Flashes quickly                  | Compatible Pairing Mode                            |
| Flashes quickly once             | Unable to discover the router                      |
| Flashes quickly twice            | Connect to the router but fail to connect to Wi-Fi |
| Flashes quickly three times      | Upgrading  |

#### **Features**

This device is a Wi-Fi smart switch with power monitoring that allows you to remotely turn on/off the device, schedule it on/off or share it with your family to control together.





Single/Countdown Timing



**Power Monitoring** 



Smart Scene



Voice Control



**Share Control** 




Power-on State



LAN Control

## **Switch Network**

If you need to change the network, long press the pairing button for 5s until the Wi-Fi LED indicator changes in a cycle of two short and one long flash and release, then the device enters quick pairing mode and you can pair again.



## **Factory Reset**

Deleting the device on the eWeLink app indicates you restore it to factory setting.

#### **Common Problems**

## Q: Why my device stays "Offline"?

A: The newly added device needs 1 – 2mins to connect Wi-Fi and network. If it stays offline for a long time, please judge these problems by the blue Wi-Fi indicator status:

- 1. The blue Wi-Fi indicator quickly flashes once per second, which means that the switch failed to connect your Wi-Fi:
  - ① Maybe you have entered a wrong Wi-Fi password.
  - ② Maybe there's too much distance between the switch your router or the environment causes interference, consider getting close to the router. If failed, please add it again.
  - ③ The 5G Wi-Fi network is not supported and only supports the 2.4GHz wireless network.

- Maybe the MAC address filtering is open. Please turn it off.
- If none of the above methods solved the problem, you can open the mobile datanetwork on your phone to create a Wi-Fi hotspot, then add the device again.
- 2. Blue indicator quickly flashes twice per second, which means your device has connected to Wi-Fi but failed to connect to the server.

Ensure steady enough network. If double flash occurs frequently, which means you access an unsteady network, not a product problem. If thenetwork is normal, try to turn off the power to restart the switch.



# Shenzhen Sonoff Technologies Co., Ltd.

MADE IN CHINA 1001, BLDG8, Lianhua Industrial Park, shenzhen, GD, China ZIP code: 518000

Website: sonoff.tech

#### **Documents / Resources**



SONOFF POWR2 Diy Power Measuring Wi-Fi Switch [pdf] User Manual POWR2, Diy Power Measuring Wi-Fi Switch

Manuals+, home privacy