



SPEEDATA SD100 Orion II MD Mobile Computer User Guide

[Home](#) » [SPEEDATA](#) » SPEEDATA SD100 Orion II MD Mobile Computer User Guide 



SD100 Orion II MD Quick Guide



Contents

- [1 General Specifications](#)
- [2 Data Collection](#)
- [3 Interface](#)
- [4 Performance](#)
- [5 Documents / Resources](#)
- [6 Related Posts](#)

General Specifications

Dimensions	254mm*176mm*17.4mm
Weight	800g
OS	Android 11 GMS (AER)
CPU	Octa-core 2.2GHz
RAM	4GB
ROM	64GB
Camera	5MP Pixels Front camera FF / 13MP Pixels Rear camera AF
Display/ Touchscreen	10.1" IPX 1200*1920 LCD resol 5 points capacitive touch screen
GPS	GPS/BeiDou/GLONASS
NFC	ISO14443A/B & ISO15693, reading distance: 0~5cm
Battery	9000mAh Li-ion battery

Wireless Specifications

Bluetooth	BT5.1, BLE
Wi-Fi	IEEE 802.11 a/b/g/n/ac 2.4G, 5G Dual band
2G/3G/4G/5G	FDD-LTE B1/B3/B5/B7/B8/ B28A TDD-LTE B34/B38/B39/B40/B41 WCDMA B1/B2/B5/B8 GSM B2/B3/B5/B8 CDMA1x/CDMA2000 BC0 NR N1/N3/N28A/N41/N77/N78/N79

Data Collection

Supported symbologies	AZTEC, CODABAR, CODE11, CODE128, EAN128, CODE39, CODE49, CODE93, COMPOSITE, DATAMATRIX, EAN8, EAN13, INT25, MAXICODE, MICROPDF, PDF417, POSTNET, OCR, QR, RS S, UPCA, UPCE, ISBT, BPO, CANPOST, AUS POST, IATA25, CODABLOCK, JAPOST, PLANET, DUTCHPOST, MSI, TLC39, TRIOPTIC, CODE32, STRT25
-----------------------	--

Interface

SIM card slot	2 Micro SIM card slot
SD card slot	1 Micro SD card slot, up to 128gbb
Earphone jack	3.5mm earphone jack
USB	USB TYPE-C, support OTG
Connectors	Docking, expansion interface

Performance

Working temperature	-20 °C to 55 °C
Storage temperature	-30 °C to 70 °C
Humidity	5%~95%
ESD protection	Air discharge $\pm 15\text{kV}$, contact discharge $\pm 8\text{kV}$

Newland EMEA
+ 31 (0) 345 87 00 33
info@newland-id.com
Rolex 25
4104 AV Culemborg
The Netherlands
Newland-id.com

Documents / Resources

	SPEEDATA SD100 Orion II MD Mobile Computer [pdf] User Guide SD100 Orion II MD Mobile Computer, SD100, Orion II MD Mobile Computer
---	--