

SPS ASR-X3XD UHF RFID Reader Owner's Manual



Contents

- 1 Specification: UHF RFID Reader
 - 1.1 Model Name : ASR-X3XD Project Name : UHF RFID Reader Revision : Rev.0
 - 1.2 Supplier Approval
 - 1.3 Customer Approval
 - 1.4 Revision Descriptions
 - 1.5 1. Scope
 - 1.5.1 1.1. Introduction
 - 1.5.2 1.2. Product Views
 - 1.6 2. Mechanical Specifications
 - 1.6.1 5.1. Dimensions (mm)
 - 1.6.2 5.2. Lead-free/RoHS
 - 1.6.3 5.3. Weight
 - 1.6.4 Certification and Safety Approvals FCC Compliance Statement
 - 1.6.5 FCC RF Exposure Statement
 - 1.6.6 FCC Caution
 - 1.6.7 Industry Canada(IC) Statement
- 2 Documents / Resources
- 3 Related Posts

Specification: UHF RFID Reader

Model Name : ASR-X3XD
Project Name : UHF RFID Reader
Revision : Rev.0

Supplier Approval

Made by	Checked by	Approved by
YB Kim		
2022-08-19		

Customer Approval

Checked by	Checked by	Approved by

Smart Power Solutions, Inc.

Products	Dongle RFID	Reversion	Rev.0
Document No	SQP-0621-xx	Released	2022-08-19
Created By	Youngbeom Kim	Revised By	
Page	2/6 page	Revision Date	

Revision Descriptions

Rev	ECN	Description	Approved by	Date
A101		Initial draft		2022.08.19

1. Scope

1.1. Introduction

Mobile UHF RFID reader allow you to read RFID tags and transmit the data to any Bluetooth Low Energy(BLE) enabled device. It complies RFID standard (Air Protocol: EPC Gen2 V2 / ISO 180006C). It uses Li-ion battery (700mAh) as internal power. Also, it can charge RFID's battery by using Magconn cable.

1.2. Product Views

Case Materials	PC (Poly Carbonate)
Charging	Magconn
Trigger TAGGING button	2 EA

< ASR-030D >



2. Mechanical Specifications

5.1. Dimensions (mm)

5.1.1. Width x Vertical x Height (64 x 119.6 x 9.7mm)



5.2. Lead-free/RoHS

Materials and process compliant with 2002/95/EC RoHS Directive

5.3. Weight

Less than 68g

Certification and Safety Approvals FCC Compliance Statement

This device complies with part 15 of the FCC rules. Operation is subject to the following two conditions:

- (1) This device may not cause harmful interference, and
- (2) This device must accept any interference received, including interference that may cause undesired operation.

This equipment has been tested and found to comply with the limits for a Class B digital device pursuant to part 15 of the FCC rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment on and off, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antennae
- Increase the separation between the equipment and the receiver
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

FCC RF Exposure Statement

This equipment complies with FCC radiation exposure limits set forth for an uncontrolled environment. End users must follow the specific operating instructions for satisfying RF exposure compliance. The antenna used for this transmitter must not transmit simultaneously with any other antenna or transmitter, except in accordance with FCC multi-transmitter product procedures.

FCC Caution

Any changes or modifications to the equipment not expressly approved by the party responsible for compliance could void user's authority to operate the equipment.

Industry Canada(IC) Statement


This device complies with Industry Canada license-exempt RSS standard(s). Operation is subject to the following two conditions:

- (1) this device may not cause interference, and
- (2) this device must accept any interference, including interference that may cause undesired operation of the device.

► Contains transmitter module IC: **MBN52832 (FCC ID: HSW2832 / IC: 4492A-2832)**

SQP-0621 (Rev.0) Smart Power Solutions

Documents / Resources

	<p>SPS ASR-X3XD UHF RFID Reader [pdf] Owner's Manual 2AJXE-ASR-X3XX, 2AJXEASRX3XX, ASR-X3XD UHF RFID Reader, ASR-X3XD, ASR-X3XD RFID Reader, UHF RFID Reader, RFID Reader, UHF Reader, Reader</p>
---	---

[Manuals+](#).