

STATE BICYCLE Co Core-Line Sizing And Specs Bicycle User **Manual**

Home » STATE BICYCLE CO » STATE BICYCLE Co Core-Line Sizing And Specs Bicycle User Manual



Contents

- 1 STATE BICYCLE Co Core-Line Sizing And Specs **Bicycle**
- 2 FAQ
- **3 COMPONENTS AND FRAME GEOMETRY**
- **4 DETAILED SIZING AND SPEC GUIDE**
- **5 DETAILED SIZING AND SPEC GUIDE**
- 6 Documents / Resources
 - **6.1 References**



STATE BICYCLE Co Core-Line Sizing And Specs Bicycle



FAQ

Q: What is the warranty on the frame of the Core-Line bike?

A: The frame of the Core-Line bike comes with a 5-year warranty.

Q: What type of tires does the Core-Line bike have?

A: The Core-Line bike comes equipped with 25c Kenda tires for a smooth ride.

Q: Are the brakes pre-installed on the Core-Line bike?

A: Yes, the Core-Line bike comes with front and rear brakes pre-installed for your convenience.

COMPONENTS AND FRAME GEOMETRY



- 1. Frame & Fork Durable Steel with 5-year warranty
- 2. **Handlebars** Riser Handlebars with **VANS** Grips
- 3. Wheels 40mm Deep-V Style Rims
- 4. Tires 25c Kenda Tires for a Smooth Ride
- 5. Brakes Front and Rear Brakes Pre-Installed
- 6. **Pedals** Plastic Platform Pedals

SIZES

- **SMALL (50 CM)** Riders 5'4" 5'7"
- **MEDIUM (54 CM)** Riders 5'7" 5'11"
- LARGE (58 CM) Riders 5'11" 6'2"

DETAILED SIZING AND SPEC GUIDE

	46cm	50cm	54cm	58cm
ACTUAL TOP TUBE L ENGTH	499mm	513mm	537mm	554mm
BB DROP	50mm	50mm	50mm	50mm
BB HEIGHT	268.5mm	268.5mm	268.5mm	268.5mm
CHAIN STAY LENGTH	405mm	405mm	405mm	405mm
COMPLETE BIKE WE	11,406g	11,580g	11,740g	11,870g
CRANK ARM LENGT H	170mm	170mm	170mm	170mm
EFFECTIVE TOP TUB E LENGTH	513mm	522mm	538mm	555mm
FORK LENGTH	402mm	402mm	402mm	402mm
FORK OFFSET	45mm	45mm	45mm	45mm
HEAD TUBE ANGLE	71.5°	72°	71°	73°
HEAD TUBE LENGTH	105mm	105mm	105mm	135mm
REACH	368mm	374mm	380mm	386mm
SEAT TUBE	460mm	500mm	540mm	580mm
SEAT TUBE ANGLE	74°	74°	73°	73°
STACK	508mm	522mm	536mm	570mm
STANDOVER HEIGHT	733mm	751mm	775mm	811mm
WHEEL BASE	975mm	985mm	989mm	1003mm

DETAILED SIZING AND SPEC GUIDE

BOTTOM BRACKET

- Sealed Cartridge
- JIS Square Taper
- English Threaded
- 68mm x 103mm

• BRAKES

- Dual Pivot
- Forged Alloy
- Clamp Diameter: 23.8mm

CHAIN

YAB Chain

• CHAINRING

- 。44T
- 130 BCD

CRANK

- Forged 6061 Aluminum
- Crank Arm Length: 170mm

FORK

- · Hi Tensile Steel
- 11/8" threadless steerer

• FRAME

Hi Tensile Steel

HANDLEBARS

- Aluminum
- Bullhorn: 420mm
- Drop: 450mm
- Riser: 570mm

• HEADSET

11/8" threadless

• HUBS

- Sealed Bearing, Flip-Flop Hub
- 16T Freewheel and Fixed Cog
- Spacing: F: 100mm / R: 120mm
- Bolts: F: M10 / R: M10

• PEDALS

Plastic Platform Pedal

• SADDLE

- Polyurthene
- Steel Rails

• SEAT POST

- Alloy
- o Diameter: 27.2mm

• Length: 220mm

• SEAT POST CLAMP

Aluminum

o Diameter: 29.5mm

• SPOKES

14G Steel, 3 Cross PatternSpoke Length F/R: 269mm

STEM

Steel

Clamp Diameter: 25.4mm

Length: 90mmRise: +/- 7°

• TIRES

Kenda Brand

• 700c x 25mm

Suggested Max Tire: 28mm

WHEELS

700c Aluminum Wheel Set

• Rim Depth: 40mm

Documents / Resources



<u>STATE BICYCLE Co Core-Line Sizing And Specs Bicycle</u> [pdf] User Manual Core-Line Sizing And Specs Bicycle, Core-Line, Sizing And Specs Bicycle, And Specs Bicycle, Specs Bicycle, Bicycle

References

• User Manual

Manuals+, Privacy Policy

This website is an independent publication and is neither affiliated with nor endorsed by any of the trademark owners. The "Bluetooth®" word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. The "Wi-Fi®" word mark and logos are registered trademarks owned by the Wi-Fi Alliance. Any use of these marks on this website does not imply any affiliation with or endorsement.