

steinhauer Hanging Lamp and Ceiling Lamp Instruction **Manual**

Home » steinhauer » steinhauer Hanging Lamp and Ceiling Lamp Instruction Manual



Contents

- 1 steinhauer Hanging Lamp and Ceiling
- 2 Manual hanging lamp and ceiling lamp
- 3 Documents / Resources
- **4 Related Posts**





Manual hanging lamp and ceiling lamp

- Before use first carefully read these instructions and save these instructions for later use or maintenance.
- This product, just like all other light fittings by Steinhauer, was subjected, produced and tested based on the European Standard for lighting equipment (EN 60598).
- Steinhauer examined this light fitting for possible manufacturing flaws. Should a fault occur within 2 years after purchase you can return this product, together with the receipt, via your supplier for repairs.
- The guarantee is cancelled in case the fitting is not installed according to the instructions in this manual or is altered by an unqualified person.
- The connection to the mains can only be executed by a qualified person.
- The applicable installation instructions must be respected. In case of doubt always contact a certified electrician.
- Prior to the assembly, replacing a lamp or maintenance you must always turn off the power.
- Always ensure that the correct light source and the correct load are used, as indicated on the fitting.
- Gilded, brass, bronze and steel coloured parts can only be cleaned with a soft cloth, without cleansing agents.
- If you are replacing a fuse pay attention that the same type of fuse is used.
- The manufacturer does not accept any liability for damage or injury that is caused as a result of incorrect assembly, connection or application of this product.

Manual for assembly, use and maintenance of hanging lamp and ceiling lamp and explanation of the symbols

1. Only use this light fitting in regular (not damp) spaces.

- 2. Check if this light fitting is suitable for assembly on the intended ceiling.
- 3. In case the light fitting is supplied with symbol (fig 1) it may be assembled to all common ceilings.
- 4. Do not assemble the light fitting in the immediate vicinity of heating radiators or other hot parts.
- 5. The minimum distance between the light fitting and the spotlighted area, such as walls and curtains, must be in accordance with the affixed symbol in case this fitting has a direct spot.
- 6. The light fitting must first be assembled mechani-cally to the ceiling or to the distribution junction box before making the connection to the mains.
- 7. In case holes are drilled in the ceiling in order to fit the light fitting make sure cables are not damaged.
- 8. Assemble the ceiling plate against the ceiling or suspend the fitting from the distribution junction box, depending on the version (fig 4,5,6,7,8)
- 9. Remove 8 mm of the isolation of the power cables and connect it to the connector in the distribution junction box. If boots are supplied with the product you need to slide these over the stripped power ca-bles. (fig 9) Make sure the cables are properly inserted in the connector. In case the lighting equipment has to be earthed attach the green-yellow terminal cable for earthing to the terminal marked with the symbol for safety earthing. (fig 2)
- 10. Check that no cables are jammed between the moun-ting or other parts of the light fitting and the wall and make sure the isolation of the cables is not damaged by screws, brackets or other sharp parts.
- 11. Screw the light source(s) in the lamp and turn the power back on.
- 12. In case the light fitting cannot be installed directly on to a distribution junction box the following needs to be done:
 - First determine the location of the light fitting and assemble the product against the ceiling.
 - Assemble a case or flat tube between the distribution junction box and the lighting equipment. (fig 10)
 - Pay attention that the case or flat tube is inserted in the fitting completely. To this end a suitable opening needs to be made in the product. Extend the wires from the distribution junction box and complete the connection as described.... starting from point 9...
 - Cover the distribution junction box with a device cover plate for distribution junction boxes or a special box for flat tube systems. (fig 11)
- 13. In case the fitting is supplied with a halogen lamp you must install this lamp using a shielding cover. Lamps that were touched can be cleaned with me-thylated spirits or alcohol. (fig 12+13)
- 14. In case the light fitting is supplied with a protection glass this immediately needs to be replaced in case of breakage or damage. (fig 14+15)
- 15. Light fittings that are supplied with the symbol (fig 16) are exclusively suitable for self-shielded halogen lamps.

 A defect lamp must therefore always be replaced with the same type light source.
- 16. Light fittings that have become useless contain components and materials that can be recycled.
 Do not treat this product as domestic waste and therefore do not add to household refuse but hand in separately (for example at the municipal recycling centre or waste processing company). (fig 17)
- 17. The packaging can be recycled. Therefore do not throw it in with the household refuse but submit it for recycling. (fig 18)



Documents / Resources



steinhauer Hanging Lamp and Ceiling Lamp [pdf] Instruction Manual Hanging Lamp and Ceiling Lamp

Manuals+,