




SuperLightingLED SP639E SPI RGBW LED Controller Instructions

[Home](#) » [SuperLightingLED](#) » SuperLightingLED SP639E SPI RGBW LED Controller Instructions 

SUPERLIGHTINGLED

SP639E Instructions
SP639E SPI RGBW LED Controller



Contents

- [1 Brief](#)
- [2 Features:](#)
- [3 APP](#)
- [4 Work With 2.4G Touch Remote Control](#)
- [5 Technical Parameters:](#)
- [6 Wiring](#)
- [7 Documents / Resources](#)
- [8 Related Posts](#)

Brief

SPI four-channel addressable RGBW LED controller, with unique dynamic, music and DIY effects to meet your lighting and ambiance needs.

Features:

1. Support App control, 2.4G touch remote control and 2.4G touch 86-type control panel;
2. Support up to 450 single-wire RZ RGBW LED driver ICs;
3. Built-in a variety of music and dynamic effects, support effects pause, multi-parameter adjustable;
4. Capture music through the phone microphone, player streamer and on-board microphone;
5. Support effect collection;
6. support DIY effects;
7. With a variety of ON/OFF animation effects;
8. With sequential channel calibration and ON/OFF timer functions;
9. Support OTA firmware upgrade.



APP



<https://download.ledhue.com/page/scenex/>

1. SP639E supports App control for iOS and Android devices.
2. Apple devices require iOS 10.0 or higher, and Android devices require Android 4.4 or higher.
3. You can search “BanlanX” in App Store or Google Play to find the APP, or scan the QR code to download and install.

Operations

- Open the App, click the  icon in the top right corner of the home page to add device;
- Click the  icon in the upper right corner of the App to enter the settings page, where you can modify the device name, set the timings, set the on/off effect, OTA firmware upgrade, etc.

Work With 2.4G Touch Remote Control

The 2.4G touch remote control models (RB3 and RC3) matched with SP639E are as follows:

- Support one-to-many control, one remote control can control multiple controllers.
- Support many-to-one control, each controller can bind up to 5 remote controls.
- Support unified control and 4-zones control.

NOTE For more information refer to “2.4G Touch Remote Control Instructions”




(Requires separate purchase)

Technical Parameters:

Working Voltage: DC5V-24V	Working Current: 1mA-10mA
Working Temp: -20t-60°C	Dimension: 78mm*56mm*20mm

Wiring



Documents / Resources

<p>SP639E Instructions</p>  <p>SP639E SPI RGBW LED Controller CE FCC RoHS</p>	<p>SuperLightingLED SP639E SPI RGBW LED Controller [pdf] Instructions</p> <p>SP639E SPI RGBW LED Controller, SP639E, SP639E LED Controller, SPI RGBW LED Controller, RGBW LED Controller, SPI LED Controller, LED Controller, Controller</p>
--	--