

# **TECH CONTROLLERS EU-R-8 bw Wireless Room Regulator** with Humidity Sensor User Manual

Home » TECH CONTROLLERS » TECH CONTROLLERS EU-R-8 bw Wireless Room Regulator with Humidity Sensor User Manual

# 1 EU-R-8 bw Wireless Room Regulator with Humidity Sensor 2 Product Information 3 Warranty Information 4 Safety Information 5 Product Usage Instructions 5.1 How to Use the Controller 6 How to Register the Room Regulator in a Particular Zone 7 WARRANTY CARD 8 Safety 8.1 Description 8.2 How to change the pre-set temperature 9 How to use the controller 10 Technical data 11 EU Declaration of conformity

Contents

12 Service:

14 Related Posts

13 Documents / Resources



# **EU-R-8 bw Wireless Room Regulator with Humidity Sensor**



# **Product Information**

# **EU-R-8bw Room Regulator**

The EU-R-8bw room regulator is a device manufactured by TECH company that is intended for use in cooperation with the EU-L-8 external controller. It is designed to be installed in heating zones and provides temperature information to the external controller, which is then used to control thermostatic valves. The current temperature is displayed on the main screen, and users can change the pre-set temperature either permanently or for a limited period of time directly from the sensor. The device is powered by 2xAAA 1.5V batteries, and a "Lo" message will appear on the screen when the battery is low.

# **Warranty Information**

The TECH company provides a 24-month warranty for the EU-R-8bw room regulator from the date of sale. The Guarantor undertakes to repair the device free of charge if the defects occurred through the manufacturer's fault. The user must deliver the device to the Guarantor along with a correctly filled-in warranty card and sales proof (receipt, VAT invoice, etc.). The Warranty Card is the only basis for repair free of charge. The complaint repair time is 14 days. The costs of unjustifiable service call to a defect will be borne exclusively by the buyer.

# **Safety Information**

TECH company is committed to protecting the environment. The crossed-out bin symbol on a product means that the product may not be disposed of to household waste containers. Recycling of wastes helps to protect the environment. The user is obliged to transfer their used equipment to a collection point where all electric and electronic components.

# **Product Usage Instructions**

#### How to Use the Controller

- 1. The EU-R-8bw room regulator is intended for use in cooperation with the EU-L-8 external controller.
- 2. Install the EU-R-8bw room regulator in the heating zones.
- 3. The temperature information sent by the EU-R-8bw room regulator to the external controller is used to control the thermostatic valves.
- 4. The current temperature is displayed on the main screen.
- 5. Users can change the pre-set temperature permanently or for a limited period of time directly from the sensor.
- 6. The device is powered by 2xAAA 1.5V batteries. If the "Lo" message appears on the screen, change the batteries to ensure correct operation of the regulator.

# How to Register the Room Regulator in a Particular Zone

- 1. Each EU-R-8bw room regulator should be registered in a zone.
- 2. Go to the EU-L-8 menu and select Sensor in the submenu of a given zone (Zone/Registration/Sensor).
- 3. After selecting the Register icon, press the communication button on the back of the EU-R-8bw room regulator.

#### **WARRANTY CARD**

TECH company ensures to the Buyer proper operation of the device for the period of 24 months from the date of sale. The Guarantor undertakes to repair the device free of charge if the defects occurred through the manufacturer's fault. The device should be delivered to its manufacturer. Principles of conduct in the case of a complaint are determined by the Act on specific terms and conditions of consumer sale and amendments of the Civil Code (Journal of Laws of 5 September 2002).

CAUTION! THE TEMPERATURE SENSOR CANNOT BE IMMERSED IN ANY LIQUID (OIL ETC). THIS MAY RESULT IN DAMAGING THE CONTROLLER AND LOSS OF WARRANTY! THE ACCEPTABLE RELATIVE HUMIDITY OF THE CONTROLLER'S ENVIRONMENT IS 5÷85% REL.H. WITHOUT THE STEAM CONDENSATION EFFECT.

THE DEVICE IS NOT INTENDED TO BE OPERATED BY CHILDREN.

Activities related to setting and regulation of the controller parameters described in the Instruction Manual and parts wearing out during normal operation, such as fuses, are not covered by warranty repairs. The warranty does not cover damages arising as a result of improper operation or through the user's fault, mechanical damage or damage created as a result of fi re, fl ood, atmospheric discharges, overvoltage or short-circuit. The interference of an unauthorized service, wilful repairs, modifi cations and construction changes cause the loss of Warranty. TECH controllers have protective seals. Removing a seal results in the loss of Warranty. The costs of unjustifi able service call to a defect will be borne exclusively by the buyer. The unjustifi able service call is defi ned as a call to remove damages not resulting from the Guarantor's fault as well as a call considered unjustifi able by the service after diagnosing the device (e.g. damage of the equipment through the fault of the client or not subject to Warranty), or if the device defect occurred for reasons lying beyond the device. In order to execute the rights arising from this Warranty, the user is obliged, at his own cost and risk, deliver the device to the Guarantor along with a correctly fi lled-in warranty card (containing in particular the sale date, the seller's signature and a description of the defect) and sales proof (receipt, VAT invoice, etc.). The Warranty Card is the only basis for repair free of charge. The complaint repair time is 14 days. When the Warranty Card is lost or damaged, the manufacturer does not issue a duplicate.

# Safety

Before using the device for the fi rst time the user should read the following regulations carefully. Not obeying the rules included in this manual may lead to personal injuries or controller damage. The user's manual should be stored in a safe place for further reference. In order to avoid accidents and errors it should be ensured that every person using the device has familiarized themselves with the principle of operation as well as security functions of the controller. If the device is to be sold or put in a diff erent place, make sure that the user's manual is there with the device so that any potential user has access to essential information about the device. The manufacturer does not accept responsibility for any injuries or damage resulting from negligence; therefore, users are obliged to take the necessary safety measures listed in this manual to protect their lives and property.

#### **WARNING**

- The regulator should not be operated by children.
- Any use other than specifi ed by the manufacturer is forbidden.



We are committed to protecting the environment. Manufacturing electronic devices imposes an obligation of providing for environmentally safe disposal of used electronic components and devices. Hence, we have been entered into a register kept by the Inspection For Environmental Protection. The crossed-out bin symbol on a product means that the product may not be disposed of to household waste containers. Recycling of wastes helps to protect the environment. The user is obliged to transfer their used equipment to a collection point where all electric and electronic components.

#### **Description**

EU-R-8bw room regulator is intended for cooperation with EU-L-8 external controller. EU-R-8bw room regulators are installed in the heating zones. Temperature information sent by them to the external controller is used to control the thermostatic valves (by opening them when the room temperature is too low and closing them when the pre-set room temperature has been reached).

Current temperature is displayed in the main screen. The user may also change the pre-set temperature permanently or for a limited period of time directly from the sensor.

# **Controller equipment:**

- built-in temperature sensor
- · air humidity sensor
- wall-mountable cover

#### **Battery low**

In case of low battery, the "Lo" message will appear on the screen. To ensure correct operation of the regulator please change the batteries (2xAAA 1,5V).

#### How to register the room regulator in a particular zone

Each room regulator should be registered in a zone. In order to register, go to the EU-L-8 menu and select Sensor in the submenu of a given zone (Zone/Registration/Sensor). After selecting the Register icon, press the communication button on the back of the room regulator. If the registration process has been completed successfully, EU-L-8 screen displays an appropriate message whereas the room sensor screen displays "Scs". If

the room sensor displays "Err", an error has occurred during the registration process.

#### **NOTE**

Only one room regulator may be assigned to each zone.

#### How to change the pre-set temperature


The pre-set zone temperature may be adjusted directly from EU-R-8bw room sensor using PLUS and MINUS buttons. During controller inactivity, the main screen displays current zone temperature. After pressing PLUS or MINUS, the current temperature is replaced with the pre-set temperature (the digits are fl ashing). Using PLUS and MINUS the user may adjust the pre-set temperature value. After setting desired value wait for 3 seconds – after this time the display shows a panel to defi ne how long the new setting should apply.

# Time settings may be adjusted:

- permanently press PLUS button until Con appears on the screen (the pre-set value will apply all the time regardless of schedule settings)
- for a specifi ed number of hours press PLUS or MINUS until the desired number of hours appears on the screen e.g. 01h (the pre-set value will apply for a specifi ed period of time; after that the weekly schedule will apply)
- if the temperature value defi ned in the weekly schedule settings should apply, press MINUS until the screen displays OFF.

#### How to use the controller

- 1. Display current zone temperature
- 2. MINUS button
- 3. PLUS button
- 4. Icon
  - flashing the set temperature has not been reached
  - highlighted the set temperature has been reached



# The following rules must be kept in mind:

- once registered, the regulator cannot be unregistered, but only switched off in the submenu of a given zone.
- if the user attempts to assign a sensor to the zone to which other sensor has already been assigned, the first sensor becomes unregistered and it is replaced by the second one.
- if the user attempts to assign a sensor which has already been assigned to a diff erent zone, the sensor is

unregistered from the first zone and registered in the new one.

It is possible to set individual pre-set temperature value and weekly schedule for each room regulator assigned to a given zone. The settings may be confi gured both in the main menu of EU-L-8 external controller (Main menu/Sensors) and via <a href="www.emodul.eu">www.emodul.eu</a> (using EU-505 or WiFi RS). The pre-set temperature may also be adjusted directly from the room sensor using PLUS and MINUS button.

# Description of the functions available in the menu

In order to enter the menu, press and hold PLUS and MINUS buttons. Use PLUS and MINUS buttons to navigate among menu functions.

- 1. rHu This function allows to check the air humidity value. After changing function to rHU, screen blinks for 3 seconds and afterwards shows air humidity value.
- 2. Bat this function enables the user to check the battery level (%). After Bat function has been selected, the screen fl ashes for 3 seconds and displays the battery level.
- 3. Cal This function enables the user to view sensor calibration. After Cal function has been selected, the screen fl ashes for 3 seconds and displays the calibration value.
- 4. Loc This function enables the user to activate button lock. After Loc function has been selected, the screen fl ashes for 3 seconds and you are asked if you want to activate the lock (yes/no). Confi rm using PLUS or MINUS button. In order to confi rm your choice, wait 3 seconds. Once the lock has been activated, the buttons are locked automatically after 10 seconds of inactivity. In order to unlock, press and hold PLUS and MINUS at the same time. When Ulc appears on the screen, the buttons have been unlocked.
- 5. Def This function enables the user to restore factory settings. Once Def function has been selected, the screen fl ashes for 3 seconds and you are asked if you want to restore factory settings (yes/no). Select using PLUS or MINUS. Wait 3 seconds to confi rm your choice.
- 6. Ret exit the menu. Once Ret has been selected, the screen fl ashes for 3 seconds and returns from the menu to the main screen view.

# **Technical data**

Room temperature adjustment range	5°C-35°C
Power supply	batteries 2xAAA 1,5V
Measurement error	+/-0,5°C
Humidity Measurement range	10-95%RH
Frequency	868MHz

# **EU Declaration of conformity**

Hereby, we declare under our sole responsibility that EU-R-8bw manufactured by TECH, head-quartered in Wieprz Biała Droga 31, 34-122 Wieprz, is compliant with Directive 2014/53/EU of the European parliament and of the Council of 16 April 2014 on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment, Directive 2009/125/EC establishing a framework for the setting of ecodesign requirements for energy-related products as well as the regulation by the MINISTRY OF ENTREPRENEURSHIP AND TECHNOLOGY of 24 June 2019 amending the regulation concerning the essential requirements as regards the restriction of the use of certain hazardous substances in electrical and electronic equipment, implementing provisions of Directive (EU) 2017/2102 of the European Parliament and of the Council of 15 November 2017 amending Directive 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment (OJ L 305, 21.11.2017, p. 8).

For compliance assessment, harmonized standards were used:

- PN-EN IEC 60730-2-9 :2019-06 par.3.1a Safety of use
- ETSI EN 301 489-1 V2.1.1 (2017-02) par.3.1 b Electromagnetic compatibility
- ETSI EN 301 489-3 V2.1.1 (2017-03) par.3.1 b Electromagnetic compatibility
- ETSI EN 300 220-2 V3.1.1 (2017-02) par.3.2 Effective and coherent use of radio spectrum
- ETSI EN 300 220-1 V3.1.1 (2017-02) par.3.2 Effective and coherent use of radio spectrum

Wieprz, 11.02.2021

PAWER JURA JANUSZ MASTER

# **Central headquarters:**

ul. Biafa Droga 31, 34-122 Wieprz

# Service:

ul. Skotnica 120, 32-652 Bulowice

**phone:** +48 33 875 93 80

e-mail: serwis@techsterowniki.pl

# **Documents / Resources**



TECH CONTROLLERS EU-R-8 bw Wireless Room Regulator with Humidity Sensor [pdf] U

EU-R-8 bw Wireless Room Regulator with Humidity Sensor, EU-R-8 bw, Wireless Room Regulator with Humidity Sensor, Wireless Room Regulator, Room Regulator, Regulator, Humidity Sensor, Sensor

Manuals+,