



TESLOGIC 3 Boost Performance Kit Instruction Manual

[Home](#) » [TESLOGIC](#) » TESLOGIC 3 Boost Performance Kit Instruction Manual 

Contents

- [1 TESLOGIC 3 Boost Performance Kit](#)
- [2 INSTALLATION](#)
- [3 PRECAUTIONS](#)
- [4 IMPACT ON THE TESLA WARRANTY](#)
- [5 Documents / Resources](#)
 - [5.1 References](#)
- [6 Related Posts](#)

TESLOGIC

TESLOGIC 3 Boost Performance Kit




INSTALLATION

1. Move the passenger seat all the way back.



2. Open the hood and the passenger door. Important! Do not close them until the installation is complete.
3. Turn off the car's power in the safety menu.




4. Power Disconnect.

1. Remove the rear underhood apron. It is attached with clips.




2. Disconnect the LV battery connector from the LV battery: release the green locking tab, pull the black

connector lock outwards to release the connector, and then pull up to aerannnh0ΛΛΛΛ0Λ·ΛΥ



3. Disconnect the first responder loop.




5. Plastic Parts Disassembly.


1. Remove the rubber door seal.



2. Remove the rectangular plastic cover. @Unclip the triangular side cap from the dashboard. Lift the wood-textured trim to access the screws underneath.




3. Using the tool provided, remove the piston.



4. Remove the plastic door sill.



5. Removing Lower Plastic Cover for Model 3.
6. Remove the plastic cover located at the passenger's feet, under the glove compartment. To do this, use the supplied tool to unclip 4 clips.





7. Disconnect the speaker and the light on this cover.



6. Removing the Lower Airbag.

If your package includes a lower airbag, remove it.


1. Remove the bolts (x2) that attach the front passenger knee airbag to the instrument panel.



2. While supporting the front passenger knee airbag, remove and discard the bolts (x4) that attach the front passenger knee airbag to the instrument panel.



3. Disconnect the electrical connector from the front passenger knee airbag.




7. Removing The Glove Compartment.

1. Remove the screws (x6) that attach the glove box to the IP carrier.





2. Disconnect the electrical harness from the glove box solenoid connector, the damper connector, and the puddle light connector.



3. Remove the glove box from the vehicle.



8. General connection diagram.




9. Teslogic Pro Device Connection.

1. Disconnect the plug from the lower connector. Connect it to the short T-shaped wiring, and then connect the T-shaped wiring to the lower connector. The kit includes 2 T-shaped wiring harnesses – one for Model


3 and one for Model Y. The wiring for Model Y can be identified by an additional grounding wire (which only needs to be connected if you have HW 4.0).



2. Disconnect the plug from the upper connector, connect it to the long wiring harness and then connect the long wiring harness to the upper connecto



3. Connect the upper and lower wiring harnesses by attaching the corresponding plugs.



4. Plug the free connector into the Teslogic Pro device.



5. Place Teslogic Pro device in the recess below.



10. Reassemble everything. Don't forget to connect all 3 connectors on the glove compartment.
11. Connect the disconnect switch under the hood, then the negative terminal of the 12v battery.
12. Install the plastic battery cover.
13. If you also want to use your phone as a dashboard, attach the supplied phone holder to the steering column (using double-sided tape on the casing) and attach to it a magnetic disk for the phone (with the Teslogic logo).

PRECAUTIONS

There is a possibility that future Tesla software updates may cause some Teslogic Pro functions to be disabled. Teslogic will release updates to our application to address this.
The Drift mode and Track mode functions should only be used off public roads.

IMPACT ON THE TESLA WARRANTY


When Teslogic Pro is installed, you may encounter a denial of warranty service for your vehicle, so before making a warranty claim, we recommend uninstalling Teslogic Pro.
Teslogic is not liable for any warranty service denial or any issues arising during the warranty service of your Tesla vehicle.

Teslogic Inc.

2093 Philadelphia Pike #3248 Claymont, DE 19703

info@teslogic.co

Documents / Resources

 The image shows the front of a white product box for the 'TESLOGIC PRO BOOST / PERFORMANCE KIT'. At the top, the 'TESLOGIC' logo is visible. Below it, the text 'TESLOGIC PRO BOOST / PERFORMANCE KIT' is printed, followed by 'Performance Upgrade For Model 3 with Range 300'. The central graphic is a line drawing of a car's interior, focusing on the dashboard and steering wheel, with a small rectangular device mounted on the dashboard.	<p>TESLOGIC 3 Boost Performance Kit [pdf] Instruction Manual</p> <p>Model 3, 3 Boost Performance Kit, Boost Performance Kit, Performance Kit, Kit</p>
--	---

References

- [User Manual](#)

Manuals+, Privacy Policy

This website is an independent publication and is neither affiliated with nor endorsed by any of the trademark owners. The "Bluetooth®" word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. The "Wi-Fi®" word mark and logos are registered trademarks owned by the Wi-Fi Alliance. Any use of these marks on this website does not imply any affiliation with or endorsement.