

thomann BP 108 A active 2-way speaker User Manual

Home » Thomann » thomann BP 108 A active 2-way speaker User Manual





fur generation **BP 108 A** active 2-way speaker

user manual



Contents

- 1 General information
 - 1.1 Further information
 - 1.2 Notational conventions
 - 1.3 Symbols and signal words
- 2 Safety instructions
- 3 Features
- 4 Starting up
 - 4.1 Dealing with lithium batteries
- **5 Connections and controls**
- 6 Playback via Bluetooth
- 7 Technical specifications
- 8 Plug and connection assignment
- 9 Cleaning
- 10 Protecting the environment
- 11 Documents / Resources
 - 11.1 References
- 12 Related Posts

General information

his user manual contains important information on the safe operation of the device. Read and follow all safety notes and all instructions. Save this manual for future reference. Make sure that it is available to all persons using this device. If you sell the device to another user, be sure that they also receive this manual.

Our products and user manuals are subject to a process of continuous development. We, therefore, reserve the right to make changes without notice. Please refer to the latest version of the user manual which is ready for download under www.thomann.de.

Further information

On our website (www.thomann.de) you will find lots of further information and details on the following points:

Download	This manual is also available as a PDF file for you to download.	
Keyword search	Use the search function in the electronic version to find the topics of interest for you quickly	
Online guides	Our online guides provide detailed information on technical basics and terms.	
Personal consultation	For a personal consultation please contact our technical hotline.	
Service If you have any problems with the device the customer service will gladly assist you.		

Notational conventions

This manual uses the following notational conventions:

Letterings	The letterings for connectors and controls are marked by square brackets and italics. Examples: [VOLUME] control, [Mono] button.	
Displays	Texts and values displayed on the device are marked by quotation marks and italics. Examples: '24ch', 'OFF'.	

Symbols and signal words

In this section, you will find an overview of the meaning of symbols and signal words that are used in this manual.

Signal word	Meaning	
DANGER!	This combination of symbols and signal words indicates an immediately dangerous situation that will result in death or serious injury if it is not avoided.	
WARNING!	This combination of symbol and signal word indicates a posa possible dangerous situation that can result in death or serious injury if it is not avoided.	
CAUTION!	This combination of symbol and signal word indicates a posa possible dangerous situation that can result in minor injury if it is not avoided.	
NOTICE!	This combination of symbol and signal word indicates a posa possible dangerous situation that can result in material and environmental damage if it is not avoided.	
Warning signs	Type of danger	
	Warning – high-voltage.	

Warning signs	Type of danger
\triangle	Warning – danger zone.

Safety instructions

Intended use

This device is designed for sound reinforcement. Use the device only as described in this user manual. Any other use or use under other operating conditions is considered to be improper and may result in personal injury or property damage. No liability will be assumed for damages resulting from improper use.

This device may be used only by persons with sufficient physical, sensorial, and intellectual abilities and having corresponding knowledge and experience. Other persons may use this device only if they are supervised or instructed by a person who is responsible for their safety.



DANGER! Danger for children Ensure that plastic bags, packaging, etc. are disposed of properly and are not within reach of babies and young children. Choking hazard! Ensure that children do not detach any small parts (e.g. knobs or the like) from the unit. They could swallow the pieces and choke! Never let children unattended use electrical devices.

DANGER!

Electric shock caused by high voltages inside

Within the device, there are areas where high voltages may be present. Never remove any covers. There are no user-serviceable parts inside. Do not use the device if covers, protectors or optical components are missing or damaged.

DANGER!

Electric shock caused by short-circuit

Always use proper ready-made insulated mains cabling (power cord) with a protective contact plug. Do not modify the mains cable or the plug. Failure to do so could result in electric shock/death or fire. If in doubt, seek advice from a registered electrician.

CAUTION!

Possible hearing damage

The device can produce volume levels that may cause temporary or permanent hearing impairment. Over an extended period of time, even levels that seem to be uncritical can cause hearing damage. Decrease the volume level immediately if you experience ringing in your ears or hearing impairment. If this is not possible, keep a greater distance or use sufficient ear protectors.

WARNING!

Incorrect handling of lithium batteries can result in injury

In the event of a short circuit, overheating or mechanical damage, lithium batteries can cause severe injuries. Follow the advice on the correct handling of lithium batteries in the present section.

NOTICE!

Risk of fire

Do not block areas of ventilation. Do not install the device near any direct heat source. Keep the device away from naked flames.

NOTICE!

Risk of fire due to the incorrect polarity

Incorrectly inserted batteries may destroy the device or the batteries. Ensure that proper polarity is observed when inserting batteries.

NOTICE!

Operating conditions

This device has been designed for indoor use only. To prevent damage, never expose the device to any liquid or moisture. Avoid direct sunlight, heavy dirt, and strong vibrations. Only operate the device within the ambient conditions specified in the chapter 'Technical specifications' of this user manual. Avoid heavy temperature fluctuations and do not switch the device on immediately after it was exposed to temperature fluctuations (for example after transport at low outside temperatures). Dust and dirt inside can damage the unit. When operated in harmful ambient conditions (dust, smoke, nicotine, fog, etc.), the unit should be maintained by qualified service personnel at regular intervals to prevent overheating and other malfunction.

NOTICE!

Possible damage by leaking batteries

Leaking batteries can cause permanent damage to the device. Take batteries out of the device if it is not going to be used for a longer period.

NOTICE!

Possible damage to lithium-ion batteries through incorrect storage

By deep discharge, lithium-ion batteries can be permanently damaged or lose some of their capacity. Before long breaks, charge the batteries to around 50 % of their capacity and then switch off the device. Store the device at room temperature or cooler in an envi- content as dry as possible. If the batteries are stored for a longer period, recharge them to 50 % every three months. Fully charge the batteries only shortly before use at room temperature.

NOTICE!

Possible staining

The plasticizer contained in the rubber feet of this product may possibly react with the coating of your parquet, linoleum, laminate or PVC floor and after some time cause permanent dark stains. In case of

doubt, do not put the rubber feet directly on the floor, but use felt-pad floor protectors or a carpet.

Features

The mobile PA system is characterized by the following features:

- 2-way active speaker box for PA and DJ application
- · Maximum output power: 60 W
- 8" woofer
- 1" compression driver
- 2-band equalizer
- Built-in media player with display, SD/MMC card slot, USB port and Bluetooth receiver
- 2 × MIC input (1/4" phone socket, unbalanced)
- 1 × RCA socket pair
- · Solid plastic housing with pole mount and handles
- Includes power adapter

Starting up

Unpack and check carefully there is no transportation damage before using the unit. Keep the equipment packaging. To fully protect the product against vibration, dust and moisture during transportation or storage use the original packaging or your own packaging material suitable for transport or storage, respectively.

Create all connections while the device is off. Use the shortest possible high-quality cables for all connections. Take care when running the cables to prevent tripping hazards.



NOTICE!

Possible property damage by magnetic fields

Loudspeakers produce a static magnetic field. Therefore, maintain an appropriate distance to devices that can be adversely affected or damaged by an external magnetic field.

The unit can be mounted on a stand or set up on the floor or a sufficiently sized and stable surface, e.g. a wall bracket.



NOTICE!

Use of stands

When mounting the device onto a stand, ensure that the stand is in a safe and stable position and that the weight of the device does not exceed the maximum permissible load capacity of the stand.

Dealing with lithium batteries



WARNING!

Incorrect handling of lithium batteries can result in injury

In the event of a short circuit, overheating or mechanical damage, lithium batteries can cause severe

injuries

Follow the advice on the correct handling of lithium batteries in the present section.

When handled correctly and appropriately lithium batteries pose no risk.

Store lithium batteries in a cool, dry place, ideally in the original packaging.

Store lithium batteries away from heat sources (e.g. radiators or sunlight). Lithium batteries are hermetically sealed. Never attempt to open a lithium battery.


If the battery housing is damaged small amounts of the electrolyte may leak out. If this should happen, seal the lithium battery in airtight packaging and wipe up the traces of electrolyte using absorbent paper towels. You must wear protective rubber gloves when doing so. Clean your hands and the affected surface thoroughly with cold water.

Never attempt to recharge non-rechargeable lithium batteries. When charging lithium batteries you must use a suitable charging device intended for the purpose.

Before disposing of the device remove the lithium batteries. Protect used lithium batteries against potential short circuits, e.g. by covering the poles with adhesive tape.

Only use powder extinguishers or other suitable extinguishing agents to extinguish a burning lithium battery.

Connections and controls



1	Media player
2	USB port
3	Display
	Selection and control buttons of the built-in media player:
4	Hold down the button to decrease the volume. If you press the button briefly, it has a different function depending on the mode: USB / SD / Bluetooth: Skip back, Line: no function
	Depending on the mode, this button has a different function: USB / SD / Bluetooth: Pause playback, Line: Mute

	Hold down the button to increase the volume. If you press the button briefly, it has a different function depending on the mode: USB / SD / Bluetooth: Skip ahead, Line: no function
	[M] Button for selecting the mode (USB / SD / Bluetooth, line input).
5	SD / MMC card slot
6	VOLUME] Use this control to adjust the volume of your microphone, instrument, or another audio source.
7	BASS] Use this control to adjust the low frequencies of your microphone, instrument, or another audio sour ce.
8	[TREBLE] Use this control to adjust the high frequencies of your microphone, instrument, or another audio sou rce.

9	[M.ECHO] Use this control to adjust the echo effect of your microphone or instrument.
10	[M.VOL] Use this control to adjust the volume of your microphone or instrument.
11	Connection socket for a power supply 15 V DC 1 A
12	Main switch to turn the device on and off.
	LEDs
13	Blue: Lights up when the device is turned on
13	Red: Lights up when the device is connected to the mains or being charged
	Green: Lights when the battery is fully charged
14	1/4" phone socket to connect the microphone or instrument.
15	RCA input sockets for connecting an external audio device.

Playback via Bluetooth

You can play music wirelessly from mobile Bluetooth devices such as smartphones, tablets, or laptops via the built-in Bluetooth receiver of the device. Observe the user's guide of your Blue- tooth device. Place the Bluetooth device near the box and turn it on.

Press [MODE] repeatedly until the display shows 'BT'. After a few seconds, your Bluetooth device will be detected (name 'BP-108A') and the display shows 'BT' permanently.

You can then play the music files stored on the Bluetooth device. Use the buttons of the built-in player for control.

Technical specifications

	T		
	1 × RCA socket pair, stereo		
Inputs	2 × 1/4" phone socket, unbalanced		
Speaker	Two-way system with 1" compression driver and 8" woofer		
Max. sound pressure I evel	109 dB		
Frequency range	75 Hz 18 kHz		
Storage media	SD card, USB devices		
Playback formats	MP3, WAV		
	Frequency of operation		2.402 GHz 2.480 G Hz
Bluetooth®	Max. transmission power		+2 dBm
	Standard		Version 5.0
	Name		BP-108A
	RMS: 15 W		
Output power	Peak: 60 W		
Supply voltage	External power adapter, 100 – 240 V 50/60 Hz		
Operating voltage	15 V / 1000 mA, center positive		
Mounting option	Standing or on a tripod		
Dimensions (W × H × D)	245 mm × 390 mm × 195 mm		
Weight	4.6 kg		
Ambient conditions	Temperature range	−5 °C…45 °C	
	relative humidity	20 %80 % (non condensing)	
t			

Further information

Multifunctional housing	Yes
Tripod flange	Yes
Truss-capable	No
Outdoor capable	No

Plug and connection assignment

Introduction

This chapter will help you select the right cables and plugs to connect your valuable equipment in such a way that a perfect sound experience is ensured.

Please note these devices, because especially in 'Sound & Light' caution is indicated: Even if a plug fits into the socket, an incorrect connection may result in a destroyed power amp, a short circuit or 'just' in poor transmission quality!

Balanced and unbalanced trans-mission

Unbalanced transmission is mainly used in semi-professional environments and in hifi use.

Instrument cables with two conductors (one core plus shielding) are typical representatives of the unbalanced transmission. One conductor is ground and hielding while the signal is transmitted through the core.

Unbalanced transmission is susceptible to electromagnetic interference, especially at low levels, such as microphone signals and when using long cables.

In a professional environment, therefore, balanced transmission is preferred, because this enables an undisturbed transmission of signals over long distances. In addition to the conductors 'Ground' and 'Signal', in a balanced transmission, a second core is added. This also transfers the signal but is phase-shifted by 180°.

Since the interference affects both cores equally, by subtracting the phase-shifted signals, the interfering signal is completely neutralized. The result is a pure signal without any noise inter-ference.

Plug and connection assignment

1/4" TS phone plug (mono, unbalanced)



1	Signal
2	Ground, shielding

RCA connection



Drawing and table indicate the pin assignment of an RCA plug.

1	Signal
2	Ground, shielding

Cleaning

Device components

Clean the device components that are accessible from the outside regularly. The cleaning frequency depends on the operating environment: damp, smoky or particularly dirty environments can cause a greater accumulation of dirt on the device components.

- · Clean with a dry soft cloth.
- Stubborn dirt can be removed with a slightly dampened cloth.
- Never use solvents or alcohol for cleaning.

Protecting the environment

Disposal of the packaging material



For the packaging, environmentally friendly materials have been chosen that can be supplied to normal recycling. Ensure that plastic bags, packaging, etc. are properly disposed of.

Do not just dispose of these materials with your normal household waste, but make sure that they are collected for recycling. Please follow the notes and markings on the packaging.

Disposal of batteries



Batteries do contain some hazardous chemicals so they should not be thrown away with normal household waste. They should be returned to the manufacturer for disposal or recycled elsewhere in accordance with your local regulations.

Dispose of lithium batteries only in discharged condition. Remove lithium batteries from the device before disposal. Protect used lithium batteries against potential short circuits, e.g. by covering the poles with adhesive tape. Dispose of the built-in lithium batteries together with the device. Please check for an appropriate reception facility.

Disposal of your old device



This product is subject to the European Waste Electrical and Electronic Equipment Directive (WEEE) in its currently valid version. Do not dispose with your normal household waste.

Dispose of this device through an approved waste disposal firm or through your local waste facility. When discarding the device, comply with the rules and regulations that apply in your country. If in doubt, consult your local waste disposal facility.

Musikhaus Thomann · Hans-Thomann-Straße 1 · 96138 Burgebrach · Germany · <u>www.thomann.de</u>

Musikhaus Thomann Thomann GmbH Hans-Thomann-Straße 1 96138 Burgebrach

Germany

Telephone: +49 (0) 9546 9223-0 E-mail: <u>info@thomann.de</u> Internet: <u>www.thomann.de</u> 05.07.2021, ID: 471746 (V2)

Documents / Resources



thomann BP 108 A active 2-way speaker [pdf] User Manual BP 108 A, active 2-way speaker

References

Manuals+,