



TOPFLY Tech TorchX-110 GPS Tracker Owner’s Manual

[Home](#) » [TOPFLY tech](#) » TOPFLY Tech TorchX-110 GPS Tracker Owner’s Manual 

TOPFLY Tech TorchX-110 GPS Tracker



Features

- 70.0g (2.6oz)



- -30°C ~ +80°C (-22°F ~ 176°F)



- 52.8mm x 47.8mm x 24.8mm (2.08" X 1.88" X 0.98")



- Operating Voltage: 7V to 32V DC with internal Li-Polymer battery



- Light and Heavy Vehicle Data Reading



- Firmware Over the Air



- Built-in Buzzer for Driver Coaching



- Global Bands Supported



- Driving Behavior Monitoring



- Crash Detection



- BLE 5.0



- Towing Alarm



- Light Car



- Heavy Duty



- Fleet management



Specification

Network/Operating Band	
Models	Torch X 110
Operating Band	LTE FDD Cat 1: B1/ B2/ B3/B4/B5/B7 /B8/B12/B13/B17 /B18/B19/ B20/ B25/B26/ B28/B66 LTE TDD Cat 1 :B34/B38/ B39/B40/B41 GSM/EDGE: 850/900/1800/1900MHz
Data Transmission	LTE-FDD: Max.10Mbps (DL), Max.5Mbps (UL) L TE-TDD: Max.8.96Mbps(DL),Max.3.1Mbps(U L) GPRS: Max. 85.6Kbps (DL), Max. 85.6Kbps (UL)
GNSS Specifications	

GNSS Chipset	All-In-One GNSS Receiver
Parallel GNSS	GPS+ Beidou + Galileo+ QZSS (SBAS)
Receiver Type	24 tracking / 64 acquisitions- channel GNSS receiver
Sensitivity	Acquisition: -148 dBm Reacquisition: 159 dBm Tracking: -162 dBm
Position Accuracy in open sky (CEP-50)	Autonomous: < 2 m
Standalone TTFF	Cold Start: < 20s (30s) Warm Start: < 2 (2s) Hot Start: < 2s (2s)
Interfaces	
08D11 Connector (The function varies based under different configurations)	ISO 15765, SAE J1939,ISO 14230(KWP2000) ISO9142-2,SAE J1708
SIM card	Nano SIM card slot
LTE/GNSS/Wi-Fi/BLE Antenna	Internal only
Indicator LED	Network, GNSS, Wi-Fi and Diagnostic
FOTA	Yes
BLE (Bluetooth Low Energy)	5.0
USB	Mirco USB /Configuration, upgrade and debug
Buzzer	Event triggering
Air Interface Protocol	
Transmit Protocol	TCP, UDP, MOTT, SMS
Data Security & Encryption Option	MOS/ AES128
BLE Accessory Support	Yes
OBDII Data Reading	Yes
Diagnostic Trouble Code (DTC)	Read and Erase
Scheduled Timing/angle/distance Report	Report position and status at preset intervals
External Power Status Alarm	Report when external power is disconnected
Network Signal Jamming Detection	Report network jamming
Driving Behavior Monitoring	Aggressive driving behavior detection, e.g., harsh braking and acceleration

Crash Detection	Accident data collection for reconstruction and analysis
Data Roaming Control	Avoid additional data consumption
General Specifications	
Dimensions	52.8mm*47.8mm*24.8mm (2.08" *1.88" *0.98")
Weight	70.0g (2.6oz)
Backup Battery	Li-Polymer 100 mAh/3. 7V
Operating Voltage	7V to 32V DC
Operating Temperature	-30°C ~ +80°C (-22°F ~ 176°F)
Storage Temperature	-40°C ~ +85°C (-40°F ~ 185°F)
Industry Certifications (Planned)	
CE, RCM, IC, FCC, TDRA, NBTC, CITC, Anatel	

CUSTOMER SUPPORT



www.topflytech.com



sales@topflytech.com




+86-755-26060058



Contents

- 1 Documents / Resources**
- 1.1 References**

Documents / Resources

	<p>TOPFLY Tech TorchX-110 GPS Tracker [pdf] Owner's Manual TorchX-110 GPS Tracker, TorchX-110, GPS Tracker, Tracker</p>
---	---

References

- [User Manual](#)

[Manuals+](#), [Privacy Policy](#)

This website is an independent publication and is neither affiliated with nor endorsed by any of the trademark owners. The "Bluetooth®" word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. The "Wi-Fi®" word mark and logos are registered trademarks owned by the Wi-Fi Alliance. Any use of these marks on this website does not imply any affiliation with or endorsement.