

# TorchStar 6" Recessed Slim LED Panel Light LED Illumination Solution User Manual

[Home](#) » [TorchStar](#) » TorchStar 6" Recessed Slim LED Panel Light LED Illumination Solution User Manual 

## Contents

- [1 CAUTIONS](#)
- [2 DESCRIPTIONS](#)
- [3 FEATURES](#)
- [4 Technical Parameter](#)
- [5 Installation Instructions](#)
- [6 WARRANTY](#)
- [7 MANUFACTURER CONTACT INFO](#)
- [8 Related Posts](#)



## CAUTIONS

Before assembling your lighting fixture, please read the following notes in this manual and heed all warnings. Please keep this for future reference

- Before starting the installation, disconnect electricity at the circuit breaker or the fuse box.
- power Recycling wall switch is not sufficient for prevent electrical shock.
- use with Recessed Slim LED Panel Light.
- All electrical connections must be in accordance with local code and ordinances. Consult a qualified
- This device may not be compatible with all dimmers.

- Suitable for damp locations but not wet locations or where directly exposed for water.
- Indoor use only

## DESCRIPTIONS


Welcome to buy our Recessed Slim LED Panel Light. It completes with an external driver in a junction box. This allows for standard 100-130VAC ceiling wiring and pre-drywall installation of the driver. It is a very cost effective ceiling light, which is perfect for residential and commercial new construction and actions.

## FEATURES


Air tight- Reducing both heat and cooling  
 Fast & Easy to install-Saving labour cost  
 isolated External Driver Inside Junction Box-No housing required  
 Dimmable, damp location approved  
 ETL& Energy Star Listed, 2700K/3000K/4000K/5000K available

## Technical Parameter

6" Recessed Slim LED Panel Light				
Voltage	AC 100 - 130V			
Wattage	12W			
Working Temperature	4°F - 104°F			
Material	Aluminum			
Color Temperature	2700K Soft White	3000K Warm White	4000K Cool White	5000K Daylight
Lumens	850lm			
Dimming Range	5% - 100%			
CRI	80+			
Product Dimensions	6.8(D) × 0.5(H)inch			
Beam Angle	110°			
Lifespan	36,000hrs			
Cutout Size	ø6.22inch			



## Installation Instructions



<p>1. Use wire nuts to connect the fixture wires with corresponding house supply wires, then connect the hermaphrodite connectors of downlight and LED driver.</p>	<p>2. Squeeze the snap springs and put downlight into the ceiling.</p>	<p>3. The installation is complete.</p>

According to the three steps as showing in above pictures. please refer for the above specification list for cutout size. Please make sure the correct cutout size in order to make the light fit well within the ceiling and have no risk of falling of.

## WARRANTY

TORCHSTAR warrants that this product is free from defects in materials and workmanship for a period of **5 years** from the day of purchase. If the product has been misused, damaged by accident or in any other way of improper use, this warranty becomes void.

## MANUFACTURER CONTACT INFO

Website: [www.torchstar.us](http://www.torchstar.us)

E-mail Address: [info@torchstar.us](mailto:info@torchstar.us)

Phone Number: 800-990-7688

TorchStar 6" Recessed Slim LED Panel Light LED Illumination Solution User Manual – [Download \[optimized\]](#)

TorchStar 6" Recessed Slim LED Panel Light LED Illumination Solution User Manual – [Download](#)