

# **TRAILFX DHS019B Drop Down Step Installation Guide**

Home » TRAILFX » TRAILFX DHS019B Drop Down Step Installation Guide 12

#### **Contents**

- 1 TrailFX Drop Down Step Part No. DHS019B
  - 1.1 Mounting Kit Images
  - **1.2 INSTALLATION PROCEDURE**
  - 1.3 COMPLETE INSTALLATION
  - 1.4 PRODUCT CARE
  - 1.5 FAQ's
- 1.6 Check out these other TrailFX

Products!!

- 2 Documents / Resources
- 3 Related Posts

TrailFX Drop Down Step Part No. DHS019B






Fits: Toyota Tacoma Double Cab 2005-2019

www.TrailFX.com Product image

TO AVOID BEING SCRATCHED, PLEASE PROTECT THE SURFACE OF THE TAILGATE VENT COVER CAREFULLY.



support@trailfx.com


**Drilling Not Required** 

POLISHED STAINLESS STEEL LIMITED LIFETIME POWDER COATED BLACK 3 YEARS


## PARTS LIST:

| Item | Qty | Part Description                      | Tools Needed          |
|------|-----|---------------------------------------|-----------------------|
| 1    | 1   | Step Bar Driver Side                  | 13 MM SOCKET & WRENCH |
| 2    | 1   | Step Bar Passenger Side               | 14 MM SOCKET & WRENCH |
| 3    | 1   | Front Mounting Bracket Driver Side    | 15 MM SOCKET & WRENCH |
| 4    | 1   | Front Mounting Bracket Passenger Side | RATCHET               |
| 5    | 2   | Mounting Bracket Driver Side          | TORQUE WRENCH         |
| 6    | 2   | Mounting Bracket Passenger Side       |                       |
| 7    | 12  | M8 Bolt                               |                       |
| 8    | 12  | M8 Lock Washer                        |                       |
| 9    | 12  | M8 Flat Washer                        |                       |
| 10   | 12  | M10 Flange Bolt                       |                       |
| 11   | 12  | M10 Flange Nut                        |                       |


# **Mounting Kit Images**



## **INSTALLATION PROCEDURE**




#### www.TrailFX.com Item 3




Center Driver Side Shown

- 1. Start at the front driver side of vehicle and grab Driver Side Mount Bracket. Use (2) M8 hex head bolts, (2) M8 flat washer, and (2) M8 lock washer to loosely mount bracket to rocker panel. See Figure 2.
- 2. Move to the center driver side of vehicle and grab the Mount Bracket. Use (2) M8 hex head bolts, (2) M8 flat washer, and (2) M8 lock washer to loosely mount

bracket to rocker panel. See Figure 3. Rear Mounting Position installs the same.



4. Grab Driver Side Bar and install to loosely mount brackets with (6) M10 Flange bolts and (6) Serrated Flange Nuts.



- 5. Repeat for passenger side.
- 6. Align and adjust step bars as needed and tighten all hardware.

#### **COMPLETE INSTALLATION**



### **PRODUCT CARE**

- 1. Periodically check the product to ensure all fasteners are tight and components are intact.
- 2. Mild soap may be used to clean the product.

### FAQ's


- Mounting bracket are not getting Installed properly.
  In some cases Illustration images shown in Installation manual may not be the exactly same as per actual vehicle images, also if Driver / Passenger side mounting brackets are very identical in the design, suggest referring Parts Identification guide to avoid fitment issue.
- 2. Products are thumping / rattling after installation. Please ensure that all required mounting brackets / hardware's are installed & tighten correctly. Suggest using white lithium / regular grease between the metal to metal contact surfaces.
- 3. Missing / Excess Hardware. Recheck hardware count as per the part list.
- 4. Product not installing properly. Ensure make model year, cab length and bed size of your vehicle is listed in the application. All installation steps are followed correctly.

#### Check out these other TrailFX Products!!











www.TrailFX.com

Keystone Automotive Operations Inc. (KAO) warrants this product to be free of defects in material and workmanship at the time of purchase by the original retail consumer. KAO disclaims any other warranties, express or implied, including the warranty of fitness for a particular purpose or an intended use. If the product is found to be defective, KAO may replace or repair the product at our option, when the product is returned prepaid, with proof of purchase. Alteration to, improper installation, or misuse of this product voids the warranty. KAO's liability is limited to repair or replacement of products found to be defective, and specifically excludes liability for any incidental or consequential loss or damage.

## **Documents / Resources**



TRAILFX DHS019B Drop Down Step [pdf] Installation Guide DHS019B, Drop Down Step

Manuals+,