



# TRIPLETT TMP15 Stem Thermometer with Alarm User Manual

[Home](#) » [TRIPLETT](#) » TRIPLETT TMP15 Stem Thermometer with Alarm User Manual 



**TMP15 Stem Thermometer with Alarm  
User Manual**



**TMP15  
Waterproof Digital Thermometer**

## Contents

### [1 Features](#)

### [2 Operation](#)

### [3 Specification](#)

### [4 Warranty](#)

### [5 Documents / Resources](#)

#### [5.1 References](#)

### [6 Related Posts](#)

## Features

Congratulations on your purchase of the Triplett TMP15 Pocket Thermometer. The thermometer is designed for measuring temperatures of liquids and semi-solids.

- 2.9" (73mm) food grade stainless steel probe
- Data Hold freezes the reading on the display
- Min/Max with reset
- Includes CR2032 battery and protective probe cover.

## Operation

- To use the thermometer, remove the protective sheath, long press the ON/OFF Button and insert at least "1/2" of the stem into the testing area, the current temperature will be displayed.
- To save battery life, the thermometer will automatically turn off after approximately 10 minutes.
- When the temperature is higher than 100°C/212°F, the alarm red light is on, when the temperature is lower than 0°C/32°F, the alarm green light is on.

## Power On/Off

- Long press the ON/OFF & Backlight Button to power ON/OFF.

## Changing Units (°F/°C)

- The temperature unit can be changed from changing °C to °F by long pressing the °C/°F & MAX/MIN Button.

## DATA Hold Temperature Function

- From "Normal" mode, press the Data HOLD Button once, the "HOLD" will appear on the display.
- Press the Data HOLD Button once more to return to normal mode.

## Backlight ON/OFF

- Press the ON/OFF & Backlight Button to turn backlight On/Off.

## MAX/MIN Mode

- To recall the highest temperature: From “Normal” mode, press the °C/°F & MAX/MIN Button, the “MAX” will appear on the display.
- Press the °C/°F & MAX/MIN Button once more to recall the lowest temperature, the “MIN” will appear on the display.
- Press the °C/°F & MAX/MIN Button once more to return to “Normal” mode.

## Specification

	<b>TMP15</b>
Temperature Range	-58 to 572°F (-50 to 300°C)
Accuracy	±1.8°F / 1°C within -4 to 212°F (-20 to 100°C);
	±3.6°/2°C -58 to -4°F (-50 to -20°C) and 212 to 482°F (100 to 250°C)
Resolution	0.1°F/°C(-58 to 391.9°F/-50 to 199.9°C) 1°F/°C(392 to 572°F/200 to 300°C )
Stem	2.5"(63.5mm) Food Grade Stainless Steel
Power	CR2032
Dimensions/Weight	6.25 x 1.25 x 0.75" (159 x 32 x 19mm) / 1.6oz (45.4g)

## Warranty

Triplett / Jewell Instruments extends the following warranty to the original purchaser of these goods for use. Triplett warrants to the original purchaser for use that the products sold by it will be free from defects in workmanship and material for a period of (1) one year from the date of purchase. This warranty does not apply to any of our products which have been repaired or altered by unauthorized persons in any way or purchased from unauthorized distributors so as, in our sole judgment, to injure their stability or reliability, or which have been subject to misuse, abuse, misapplication, negligence, accident or which have had the serial numbers altered, defaced, or removed. Accessories, including batteries are not covered by this warranty



Copyright © 2022 Triplett

[www.triplett.com](http://www.triplett.com)

## Documents / Resources



Manuals+.