



# TRIPP-LITE B006-VU4-R 4 Port Desktop KVM Switch Owner's Manual

[Home](#) » [Tripp Lite](#) » TRIPP-LITE B006-VU4-R 4 Port Desktop KVM Switch Owner's Manual 

## Contents

- [1 TRIPP-LITE B006-VU4-R 4 Port Desktop KVM Switch](#)
- [2 4-Port Desktop KVM Switch \(USB\)](#)
- [3 Description](#)
- [4 Features](#)
- [5 Highlights](#)
- [6 Package Includes](#)
- [7 Specifications](#)
- [8 Documents / Resources](#)
- [9 Related Posts](#)

# TRIPP-LITE

## TRIPP-LITE B006-VU4-R 4 Port Desktop KVM Switch



1000 Eaton Boulevard Cleveland, OH 44122 United States

4-Port Desktop KVM Switch (USB)

**MODEL NUMBER:** B006-VU4-R



## Description

Tripp Lite's 4-port Desktop USB KVM Switch is the optimal solution for controlling up to 4 USB computers from one VGA monitor and USB keyboard/mouse. Manually switch between connected computers using pushbuttons or hotkey controls; or, monitor connected computers automatically via Auto Scan Mode. The B006-VU4-R is operating system independent, and works with all computers that have an available VGA and USB port. It supports video resolutions up to 2048 x 1536, and features a compact design that does not require software or complicated set-up procedures. Constructed of heavy-duty steel housing. Order P758 Cables separately.

## Features

- Control up to 4 USB computers from a single VGA monitor and USB keyboard/mouse
- Order P758 Cables separately
- Port LEDs illuminate Dim Orange to indicate a computer is connected, and Bright Orange to indicate it is the selected port
- Supports video resolutions up to 2048 x 1536, DDC2B
- No software or complicated set-up procedures required
- Manually switch between connected computers via front panel pushbuttons or hotkey commands
- Automatically monitor connected computers via Auto Scan Mode
- Compatible with all major operating systems
- Compatible with most mice; including scroll mice
- Constructed of heavy-duty steel housing

## Highlights

- Control up to 4 USB computers from a single VGA monitor and USB keyboard/mouse
- Switch between connected computers via pushbuttons or hotkey commands
- Auto Scan Mode allows monitoring of connected computers without manually switching between them
- Compatible with all major operating systems
- Supports video resolutions up to 2048 x 1536, DDC2B

Package Includes

- B006-VU4-R 4-port USB KVM Switch
- External Power Supply with NEMA 1-15P Plug (Input: 100-240V, 50/60Hz, 0.5A /Output: 5.3V, 2.4A )
- Owner’s manual

Specifications

|  |                          |
|--|--------------------------|
| OVERVIEW                                       |                          |
| UPC Code                                       | 037332152947             |
| Console  | No                       |
| Max CPU  | 4                        |
|  |                          |
| Technology                                     | VGA/SVGA                 |
| VIDEO  |                          |
| Max Supported Video Resolution                 | 2048 X 1536, DDC2B       |
| POWER  |                          |
| External Power Supply Plug(s)                  | NEMA 1-15P North America |
| External Power Supply Input Specs (V / Hz / A) | 100-240V/ 50/60Hz/ 0.5A  |
| External Power Supply Output Specs (V / A)     | 5.3V/ 2.4A               |
| External Power Supply Cord Length (ft.)        | 5                        |
| USER INTERFACE, ALERTS & CONTROLS              |                          |
| LED Indicators                                 | Online Selected (Orange) |
| PHYSICAL                                       |                          |


|                                 |                       |
|---------------------------------|-----------------------|
| LCD Monitor (cm)                | Not Applicable        |
| Shipping Dimensions (hwd / in.) | 3.50 x 9.80 x 8.70    |
| Shipping Dimensions (hwd / cm)  | 8.89 x 24.89 x 22.10  |
| Shipping Weight (lbs.)          | 2.20                  |
| Shipping Weight (kg)            | 1.00                  |
| Unit Dimensions (hwd / in.)     | 1.700 x 7.900 x 2.900 |
| Unit Dimensions (hwd / cm)      | 4.32 x 20.07 x 7.37   |
| Unit Weight (lbs.)              | 1.50                  |
| Unit Weight (kg)                | 0.68                  |
| <b>ENVIRONMENTAL</b>            |                       |
| BTUs                            | 7.1694 BTU/Hr         |
| <b>COMMUNICATIONS</b>           |                       |
| Port Control                    | Push Buttons, Hotkeys |
| IP Remote Access                | No                    |
| <b>CONNECTIONS</b>              |                       |
| Number of Ports                 | 4                     |
| PC/Server Connections           | USB; VGA              |
| Side A – Connector 1            | (4) HD15 (MALE)       |
| Side A – Connector 2            | (4) USB B (FEMALE)    |

|                                       |                                   |
|---------------------------------------|-----------------------------------|
| Side B – Connector 1                  | (1) HD15 (FEMALE)                 |
| Side B – Connector 2                  | (2) USB A (FEMALE)                |
| Computer Keyboard and Mouse Interface | USB                               |
| Computer Monitor Interface            | VGA                               |
| Console Keyboard and Mouse Interface  | USB                               |
| Console Monitor Interface             | VGA                               |
| <b>FEATURES &amp; SPECIFICATIONS</b>  |                                   |
| Autoscan (Y,N)                        | Y                                 |
| Autoscan Duration                     | 11 TO 99 SECONDS; USER-DEFINEABLE |
| Number of Users                       | 1                                 |
| NIAP-Certified Secure                 | No                                |
| USB Specification                     | USB 2.0 (up to 480 Mbps)          |
| Cat5 KVM Switch                       | No                                |
| <b>WARRANTY &amp; SUPPORT</b>         |                                   |
| Product Warranty Period (Worldwide)   | 3-year limited warranty           |

© 2022 Eaton. All Rights Reserved.

Eaton is a registered trademark. All other trademarks are the property of their respective owners.

## Documents / Resources

|   |   |
|---|---|
|  | <p><b><a href="#">TRIPP-LITE B006-VU4-R 4 Port Desktop KVM Switch</a></b> [pdf] Owner's Manual<br/> B006-VU4-R, 4 Port Desktop KVM Switch, B006-VU4-R 4 Port Desktop KVM Switch, Desktop KVM Switch, KVM Switch, Switch</p> |
|---|---|