



TRIPP-LITE B119-2X2 2×2 HDMI Matrix Switch with Remote Control Owner's Manual

[Home](#) » [Tripp Lite](#) » TRIPP-LITE B119-2X2 2×2 HDMI Matrix Switch with Remote Control Owner's Manual 

Contents

- [1 TRIPP-LITE B119-2X2 2×2 HDMI Matrix Switch with Remote Control](#)
- [2 Highlights](#)
 - [2.1 Package Includes](#)
- [3 Description](#)
- [4 Features](#)
- [5 Specifications](#)
- [6 Documents / Resources](#)
- [7 Related Posts](#)



TRIPP-LITE B119-2X2 2×2 HDMI Matrix Switch with Remote Control



MODEL NUMBER: B119-2X2

Highlights

- Share multiple HDMI sources between multiple monitors
- Supports computer video resolutions up to 1920 x 1200, and HD resolutions up to 1080p @ 60Hz
- Plug-and-play; No software or drivers are required
- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases

Package Includes

- B119-2X2 Local Transmitter Unit
- External Power Supply with NEMA 1-15P Plug (Input: 100-240V, 50/60Hz, 0.5A; Output: 5V, 2A)
- 3.5 mm to DB9 Adapter Cable
- Mounting Hardware
- Remote Control
- Owner's Manual



Connect 2 HDMI source devices to 2 HDMI displays and either share video on both or switch between them.

Description

Tripp Lite's B119-2X2 is a 2x2 HDMI Matrix Switch that routes high-definition video from any two HDMI sources to any two HDMI displays. It supports computer video resolutions up to 1920 x 1200, and HD resolutions up to 1080p @ 60Hz. The 2x2 Matrix eliminates the need to disconnect and reconnect HDMI sources. It works with any HDMI source that connects to an HDMI display, and each source is accessible at all times by any display by selecting it with an IR remote or using the RS232 port to switch the unit. Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases.

Features

- Share multiple HDMI sources between multiple monitors (2 Input, 2 Output)
- Allows any input to be routed to any output; or the same input to be routed to multiple outputs
- Switch between inputs via pushbuttons, remote control, or RS-232 serial
- Monitors can be located up to 25 ft. from the switch
- Supports computer video resolutions up to 1920 x 1200, and HD resolutions up to 1080p @ 60Hz
- HDCP and EDID compatible
- Mounting hardware included
- Plug-and-play; No software or drivers are required
- Compatible with all operating systems
- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases

Specifications

OVERVIEW	
UPC Code	037332180186
Technology	
HDMI; IR	
VIDEO	
Supported Resolutions	1920x1080 (1080p)
POWER	
AC Adapter	Input: 100-240V, 50/60Hz, 0.5A; Output: 5V, 2A
PHYSICAL	
Color	Black
Included Mounting Accessories	Yes
Rackmountable	Yes
Shipping Dimensions (hwd / in.)	10.24 x 2.17 x 6.46


Shipping Dimensions (hwd / cm)	26.01 x 5.51 x 16.41
Shipping Weight (lbs.)	1.50
Shipping Weight (kg)	0.68
Unit Dimensions (hwd / in.)	1.200 x 9.200 x 3.900
Unit Dimensions (hwd / cm)	3.05 x 23.37 x 9.91
Unit Weight (lbs.)	1.45
Unit Weight (kg)	0.66
COMMUNICATIONS	
Port Control	Push Buttons
Signal Range (ft.)	60
Signal Range (m)	18
IP Remote Access	Yes
EDID Compatible	Yes
RS-232 Serial Extension Support	Yes
CONNECTIONS	
Number of Ports	2
Side A – Connector 1	(2) HDMI (FEMALE)
Side B – Connector 1	(2) HDMI (FEMALE)
WARRANTY & SUPPORT	
Product Warranty Period (Worldwide)	3-year limited warranty

© 2022 Eaton. All Rights Reserved.

Eaton is a registered trademark. All other trademarks are the property of their respective owners.

Downloaded from [Arrow.com](https://www.arrow.com).

Documents / Resources

	<p>TRIPP-LITE B119-2X2 2x2 HDMI Matrix Switch with Remote Control [pdf] Owner's Manual B119-2X2, 2x2 HDMI Matrix Switch with Remote Control, B119-2X2 2x2 HDMI Matrix Switch with Remote Control, B119-2X2 2x2 HDMI Matrix Switch, 2x2 HDMI Matrix Switch, Matrix Switch, Switch</p>
---	---

