TurboTorch **TurboTorch** X-3B Standard **Torch Kits**





TurboTorch X-3B Standard Torch Kits Instruction Manual

Home » TurboTorch » TurboTorch X-3B Standard Torch Kits Instruction Manual



Contents

- 1 TurboTorch X-3B Standard Torch
- **2 Product Specifications**
- **3 Frequently Asked Questions**
- **4 Kit Components**
- **5 Product Usage Instructions**
- 6 Documents / Resources
 - **6.1 References**



TurboTorch X-3B Standard Torch Kits



Product Specifications

• Brand: ExtremeTM

Product Type: Standard Torch Kits

• Technology: Extreme Swirl Technology

• Features: Quick disconnect couplings, color-coded O-rings for gas identification

Frequently Asked Questions

Q: How do I know which tip to use for a specific soldering task?

A: Refer to the user manual or product specifications for guidance on tip selection based on the type of soldering task.

Q: What is the recommended gas pressure for this torch kit?

A: The recommended gas pressure may vary based on the specific model. Refer to the instruction manual for detailed information on gas pressure settings.

Q: Can I use this torch kit for brazing silver?

A: Yes, this torch kit is suitable for silver brazing. Ensure you use the appropriate tip and follow recommended procedures for silver brazing.

EXTREME™ STANDARD TORCH KITS

This line of kits has been the industry standard for decades. Reliable and well engineered, the standard line of kits combines our Extreme Swirl Technology with a traditional manual lighting torch. All tips feature quick disconnect couplings and color coded O-rings for gas identification.

Kit Components

The kit includes a torch handle, hoses, tips, and a regulator. Ensure all components are securely connected before use.

- AR-B (CGA 520) Regulator
- G-4 Handle
- AH-12 Hose
- A-3 Tip
- A-11 Tip
- Soft solders to 3" (75 mm)
- Silver brazes to 1-5/8" (40 mm)
- "B" Tank Connection
- · Instruction Manual

Kit N o.	Model	Soft Solders	Silver Bra zes	Regulator	Hand le	Hos e	Tips	Tank Conne ction	Valve Posi tion
X-3B	0386-0 335	3" 75 mm	1-5/8″ 40 mm	AR-B (CGA-52 0)	G4	AH- 12	A-3, A -11	В	Rear
X-4B	0386-0 336	3-1/2" 90 mm	2" 50 mm	AR-B (CGA-52 0)	G4	AH- 12	A-5, A -14	В	Rear
X-5B	0386-0 338	1-1/2" 40 mm	3/4" 20 mm	AR-B (CGA-52 0)	G4	AH- 12	A-5	В	Rear
X-5M C	0386-0 384	1-1/2" 40 mm	3/4" 20 mm	AR-MC (CGA- 200)	G4	AH- 12	A-5	MC	Rear
X-6M C	0386-0 339	2" 50 mm	1″ 30 mm	AR-MC (CGA- 200)	G4	AH- 12	A-3, A -8	MC	Rear
MSK A-1	0386-0 366	3" 75 mm	3/4" 20 mm	AR-B (CGA-52 0)	G4	AH- 12	MSA-8	В	Rear

Product Usage Instructions

Setting Up:

Attach the appropriate tip to the torch handle using the quick disconnect couplings. Connect the hoses to the regulator and the gas supply tank.

Gas Identification:

Use the color-coded O-rings to identify the type of gas being used with each tip.

Lighting the Torch:

Follow the manual lighting instructions provided with the torch. Ensure a safe distance from the work area before igniting the torch.

Adjusting Flame:

Use the regulator to adjust the flame intensity based on your requirements. Always follow safety guidelines when working with flames.

International Customer Care: 940-381-1212 / FAX 940-483-8178

TurboTorch.com

Documents / Resources



TurboTorch X-3B Standard Torch Kits [pdf] Instruction Manual

X-3B 0386-0335, X-4B 0386-0336, X-5B 0386-0338, X-5MC 0386-0384, X-6MC 0386-0339, MS KA-1 0386-0366, X-3B Standard Torch Kits, X-3B, Standard Torch Kits, Torch Kits, Kits

References

• User Manual

Manuals+, Privacy Policy

This website is an independent publication and is neither affiliated with nor endorsed by any of the trademark owners. The "Bluetooth®" word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. The "Wi-Fi®" word mark and logos are registered trademarks owned by the Wi-Fi Alliance. Any use of these marks on this website does not imply any affiliation with or endorsement.