



ULINE H-5271 Bar Code Printer User Guide

[Home](#) » [ULINE](#) » ULINE H-5271 Bar Code Printer User Guide 



ULINE H-5271 Bar Code Printer

ZEBRA GK420T, GK420D

Maximum Print Area

Width: 4.09"

Length: 39"

Resolution: 203 dpi

Maximum Print Speed: 5"/sec

Memory: 4 MB Flash,

8 MB SDRAM

Physical Characteristics

H-2526

Width: 7.6"

Height: 7.5"

Depth: 10"

Weight: 4.6 lbs.

H-2550, H-5271

Width: 6.75"

Height: 6.0"

Depth: 8.25"

Weight: 3.0 lbs.

Media Specifications

Label & Liner Width: .75" – 4.25"

Ribbon Width: 1.33" – 4.3"

**H-2526, H-2550, H-5271 BAR CODE PRINTER TECHNICAL SPECIFICATIONS
STANDARD FEATURES**

- Print method:
- H-2526 Direct thermal and/or Thermal Transfer
- H-2550, H-5271 Direct Thermal only
- 5 status Icon 3 button user Interface
- Dual wall construction
- USB, Parallel, Serial (H-5271 – Ethernet)
- Open Access design for easy media loading

OPERATION CHARACTERISTICS

Environment

- Operating Temp 40°F – 105°F
- Storage Temp -40°F – 140°
- Operating Humidity 10 – 90% non-condensing

Agency Approvals

- Emissions: FCC Part 15, Subpart B, ICES003, CQC, EAC, KCC, BSMI, VCCI, C-Tick
- Emissions and Susceptibility: (CE): EN55022 Class-B, EN61000-3-2, EN61000-3-3, and EN55024
- Safety: CB Scheme IEC 60950:1991 +A1 +A2 +A3 +A4, UL 60950 and C-UL, IRAM, NOM, AAMI, and CCC

Electrical

- Auto detectable external power supply with C14 type connector
- Output 24VDC, 2.5A
- Input: 100-240 VAC, 50-60 Hz
- Energy Star qualified

FONTS/GRAPHICS

Fonts & Character Sets

- 16 resident expandable ZPL fonts, one resident scalable ZPL font, f Ne resident expandable EPL2 fonts. supports user-defined fonts and graphics – including custom logos.
- Native open type font support
- Unicode™ compliant for multi-language, on-demand thermal printing
- ZPL II drawing commands – for boxes and lines.

PROGRAMMING LANGUAGES

- These printers support ZPL™, ZPL II, and EPL

MEDIA CHARACTERISTICS

Labels

Max. roll size: 5" OD on a 1" ID core

Thickness (Label & Liner)

.003" – .0075"

Media Types

Roll-fed or fan-fold, die-cut or continuous direct thermal or thermal transfer labels with or without black line, tag stock, continuous receipt paper, and wristbands

Ribbons

Max. roll size: 4.3' OD on a .5" ID core

Standard Lengths

244' capacity; provides 1:1 media to ribbon ratio for 5" OD media

Ribbon Setup

- Ribbon wound ink side out
- The ribbon is recommended to be at least as wide as media

SYMBOLOGIES

Bar Code Symbologies

Linear Bar Codes:

Code 11, Code 39, Code 93, Code 128, UPC-A, UPC-E, EAN-8, EAN-13, EAN-14, UPCA and UPC-E with EAN 2 or 5 digit extensions, Plessey, POSTNET, Standard 2 of 5, Industrial 2 of 5, Interleaved 2 of 5, LOGMARS, MSI, Codabar, and GS1 DataBar™ (formerly RSS)

2-Dimensional:

Code block (ZPL), Code 49 (ZPL), Data Matrix, MaxiCode, QR Code, PDF417, MicroPDF417, Aztec (For EPL and ZPL except where noted)

Contents

[1 Documents /](#)

[Resources](#)

[2 Related Posts](#)

Documents / Resources

	ULINE H-5271 Bar Code Printer [pdf] User Guide H-2526, H-2550, H-5271, Bar Code Printer
---	--