

V-Mark Temp Tag Gen2 Thread Device User Guide

Home » V-Mark » V-Mark Temp Tag Gen2 Thread Device User Guide 🖫



Contents

- 1 Introduuction
- 2 Out of the box
- **3 Workinng Parammeter**
- 4 Documents /

Resources

4.1 References

Introduuction

The Temp Tag described in this user guide is using a Thread device, it has been tested to work with Thread Mesh network. This device can be controlled by NFC NDEF messages. This device can support the external Probe. It is with a 6 pin connector for the most of I²C sensors.

In the picture below we can see the Temp Tag with LED. The NFC Coil Antenna is around the LED cover.



Out of the box

The Temp Tag comes in a deep sleep state to extend battery life, at this point it can only be triggered by NFC reader. This device should join a network to be able to interact with other ones via Thread commands.

User interface

The Temp Tag has one LED for display; the device can execute different actions depending on the NDEF messages. The following table shows the according actions:

NFC NDEF message	LED indicator	Action
activate	Fast blink 10 times	Network steering / finding
hibernate	Keep on about 2s	Set the device into deep sleep mode
reset	Keep on about 2s	Reset the device

Workinng Parammeter

Parameter	Value
Work Frequency	Thread 2.4GHz and NFC 13.56MHz
TX Power	Max 8dBm
Battery	ER14250, 3.6V, 1200mAH
	TMP117 on board: -40°C~85°C, ±0.1°C (-20°C~55°C
Measuring range	SHTC3: -40°C~85°C, ±0.2°C (-20°C~55°C);
	SHTC3: 0~100%RH, ±2% (20%RH-80%RH);
Battery Life	5 years
Operating Temperature	-40°C~85°C
Storage Environment	-40°C~85°C, No condensation
Size	88mm*45mm*19mm

FCC Warnings

Changes or modifications not expressly approved by the party responsible for compliance couldvoid the user's authority to operate the equipment. This equipment has been tested and found tocomply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules.

Theselimits are designed to provide reasonable protection against harmful interference in a residentialinstallation. This equipment generates uses and can radiate radio frequency energy and, if notinstalled and used in accordance with the instructions, may cause harmful interference to radiocommunications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try tocorrect the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

This device complies with part 15 of the FCC Rules. Operation is subject to the followingtwo conditions:

- 1. This device may not cause harmful interference, and
- 2. this device must accept any interference received, including interference that may cause undesired operation.

NOTE:This device and its antenna(s) must not be co-located or operation in conjunction with any other antenna or transmitter.

RF Exposure Statement

To maintain compliance with FCC's RF Exposure guidelines, this equipment should beinstalled and operated with minimum distance of 20cm the radiator your body. This deviceand its antenna(s) must not be co-located or operation in conjunction with any other antenna or transmitter.



Add.: 400-601 West Broadway, Vancouver BC, Canada V5Z 4C2 Phone: 604.588.6178,

Fax: 604.859.8818, Email: <u>info@v-mark.com</u>

Documents / Resources



V-Mark Temp Tag Gen2 Thread Device [pdf] User Guide

KRGEN2TS004, 2AQ7V-KRGEN2TS004, 2AQ7VKRGEN2TS004, krgen2ts004, Temp Tag Thr ead Device, Temp Tag, Thread Device, Temp Tag Gen2 Thread Device, Temp Tag Gen2

References

• • Mark · We help people buy, rent and sell great domain names

Manuals+.